



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (1.6 GHz Intel Xeon Processor 5110)

SPECfp_rate2000 = 31.5

SPECfp_rate_base2000 = 31.5

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Jun-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|--------------|-------------|--------------|------------|--------|---------|-------|
| 168.wupwise | 2 | 71.5 | 51.9 | 2 | 71.5 | 51.9 |
| 171.swim | 2 | 261 | 27.5 | 2 | 261 | 27.5 |
| 172.mgrid | 2 | 181 | 23.0 | 2 | 181 | 23.0 |
| 173.applu | 2 | 189 | 25.8 | 2 | 189 | 25.8 |
| 177.mesa | 2 | 85.8 | 37.9 | 2 | 85.8 | 37.9 |
| 178.galgel | 2 | 94.7 | 71.1 | 2 | 94.7 | 71.1 |
| 179.art | 2 | 68.6 | 87.9 | 2 | 68.6 | 87.9 |
| 183.equake | 2 | 121 | 24.9 | 2 | 121 | 24.9 |
| 187.facerec | 2 | 120 | 36.7 | 2 | 120 | 36.7 |
| 188.amp | 2 | 197 | 26.0 | 2 | 197 | 26.0 |
| 189.lucas | 2 | 187 | 24.9 | 2 | 187 | 24.9 |
| 191.fma3d | 2 | 203 | 24.1 | 2 | 203 | 24.1 |
| 200.sixtrack | 2 | 182 | 14.0 | 2 | 182 | 14.0 |
| 301.apsi | 2 | 251 | 24.0 | 2 | 251 | 24.0 |

Hardware

CPU: Intel Xeon Processor 5110 (1.6 GHz, 4MB L2, 1066MHz system bus)
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 4096KB(I+D) on chip (per chip), shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 2048MB ECC FB-DIMM DDR2-667
 Disk Subsystem: 1 x 73GB 10000RPM SAS HDD
 Other Hardware:

Software

Operating System: Red Hat Enterprise Linux 4 Advanced Server Update 3 EM64T
 Compiler: Intel C++ 9.1 for EM64T build 20060323 and Fortran Compiler 9.1 for EM64T build 20060323
 File System: ext3
 System State: Runlevel 3

Notes/Tuning Information

GENERAL

ONESTEP=yes for all benchmarks
 +FDO : PASS1= -prof_gen PASS2= -prof_use

PORTABILITY FLAGS

-DSPEC_CPU2000_LP64 applied to all benchmarks
 178.galgel: -FI for fixed-format Fortran

BASE TUNING

Baseline optimizations for C and Fortran: -fast +FDO

PEAK TUNING

basepeak=yes set for all benchmarks

This result was measured on the Acer Alto R720.
 The Altos R520 and Altos R720 are electronically equivalent.