



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 505 (2100 Mhz, 1 CPU, SLES)

SPECfp2000 = 3293
SPECfp_base2000 = 2773

SPEC license #: 11 Tested by: IBM Austin Test date: Oct-2006 Hardware Avail: Aug-2006 Software Avail: Dec-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	47.3	3379	41.0	3902
171.swim	3100	91.2	3398	73.9	4194
172.mgrid	1800	75.8	2375	58.4	3082
173.applu	2100	96.6	2173	72.9	2879
177.mesa	1400	97.8	1431	97.8	1431
178.galgel	2900	52.1	5561	32.0	9066
179.art	2600	18.1	14340	15.9	16367
183.quake	1300	24.2	5366	19.3	6730
187.facerec	1900	67.4	2819	67.4	2819
188.amp	2200	158	1392	156	1415
189.lucas	2000	58.2	3437	34.6	5785
191.fma3d	2100	121	1738	111	1899
200.sixtrack	1100	120	916	116	949
301.apsi	2600	127	2043	127	2044

Hardware

CPU: POWER5+
CPU MHz: 2100
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (SMT off)
CPU(s) orderable: 1,2 core
Parallel: No
Primary Cache: 64 KB I + 32 KB D on chip per core
Secondary Cache: 1920 KB I+D on chip per chip
L3 Cache: 36 MB I+D off chip per chip
Other Cache: None
Memory: 16 GB (8x2GB)
Disk Subsystem: 1x73GB SCSI, 15K RPM
Other Hardware: None

Software

Operating System: SLES
SUSE Linux Enterprise Server 10 (ppc) VERSION = 10
w/2.6.16.21-0.8-ppc64 Linux kernel
Compiler: IBM XL C/C++ Advanced Edition V8.0.1 for Linux
IBM XL Fortran Advanced Edition V10.1.1 for Linux
Other software:
- IBM Engineering and Scientific Subroutine
Library (ESSL) for Linux - Version 4.2.5
File System: reiserfs
System State: Multi-User

Notes/Tuning Information

+FDO

Feedback directed optimization enabled by: PASS1=-qpdf1 PASS2=-qpdf2

FP compilers

C: invoked as xlc

Fortran 77 and Fortran 90: invoked as xlf90, except as noted below

FP Portability Flags

-qfixed used in: 168.wupwise, 171.swim, 172.mgrid, 173.applu,
178.galgel, 200.sixtrack, 301.apsi

-qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

FP Base Optimization Flags:

C: +FDO -O5

Fortran: +FDO -O5



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 505 (2100 Mhz, 1 CPU, SLES)

SPECfp2000 = 3293

SPECfp_base2000 = 2773

SPEC license #: 11 | Tested by: IBM Austin | Test date: Oct-2006 | Hardware Avail: Aug-2006 | Software Avail: Dec-2006

Notes/Tuning Information (Continued)

Floating Point Peak Flags

```
168.wupwise
  +FDO -O5 -qsave -lmass
  -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
171.swim
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
172.mgrid
  +FDO -O4 -q64
  -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
173.applu
  +FDO -O5 -q64
  -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
177.mesa
  basepeak=1
178.galgel
  Fortran invoked as xlf90_r
  +FDO -O5 -qessl -lessl -lmass
  -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
179.art
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
183.quake
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
187.facerec
  basepeak=1
188.amp
  +FDO -O3 -qalign=linuxppc
189.lucas
  +FDO -O3 -qarch=auto -qtune=auto
  -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
191.fma3d
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
200.sixtrack
  +FDO -O3 -qarch=auto -qtune=auto
  -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
301.apsi
  Fortran invoked as xlf90_r
  +FDO -O5 -qessl
  -B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-link=BDT
  extra_libs = -lessl
```

System Settings:

```
-- ulimit stack size set to unlimited
```

SMT: Acronym for 'Simultaneous Multi-Threading'. A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. SMT is enabled by default.

Large pages reserved as follows by root user:

```
echo 30 > /proc/sys/vm/nr_hugepages
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 505 (2100 Mhz, 1 CPU, SLES)

SPECfp2000 = 3293

SPECfp_base2000 = 2773

SPEC license #: 11 | Tested by: IBM Austin | Test date: Oct-2006 | Hardware Avail: Aug-2006 | Software Avail: Dec-2006

Notes/Tuning Information (Continued)

System configured with libhugetlbfs library for application access to large pages
Environment variables set as follows:
export HUGETLB_MORECORE=yes

Linux booted with the options:
maxcpus=1 smt-enabled=off

Each process was bound to a cpu using submit= with the taskset command
submit = taskset -p -c \[extract_itex]SPECUSERNUM \[/extract_itex]\[extract_itex] >/dev/null ;[/extract_itex]command

This result was measured on an IBM System p5 510. IBM System p5 505 and IBM System p5 510 (2-core version) are electronically equivalent.