



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3250 (2.13 GHz Xeon 3050, 4MB L2 Cache)

SPECfp_rate2000 = --

SPECfp_rate_base2000 = 38.0

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Oct-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	53.7	69.1			
171.swim	2	215	33.5			
172.mgrid	2	150	27.8			
173.applu	2	172	28.4			
177.mesa	2	66.8	48.7			
178.galgel	2	104	64.5			
179.art	2	89.7	67.2			
183.quake	2	66.5	45.4			
187.facerec	2	100	44.0			
188.amp	2	210	24.3			
189.lucas	2	134	34.7			
191.fma3d	2	155	31.5			
200.sixtrack	2	132	19.4			
301.apsi	2	184	32.7			

Hardware

CPU: Intel Xeon processor 3050 (2.13 GHz, 1066 MHz bus)
 CPU MHz: 2133
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
 Secondary Cache: 4096KB(I+D) on chip (per chip)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4 x 1024 MB ECC PC2-5300
 Disk Subsystem: 73GB SAS 15K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
 Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
 Build 20060323Z
 Microsoft Visual Studio 2005 (for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
```