



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec ZX400 (Intel Xeon 7140M processor)

SPECint_rate2000 = 83.1

SPECint_rate_base2000 = 83.1

SPEC license #: 9001 | Tested by: Itautec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	194	67.1	8	194	67.1
175.vpr	8	237	54.9	8	237	54.9
176.gcc	8	95.5	107	8	95.5	107
181.mcf	8	178	94.0	8	178	94.0
186.crafty	8	162	57.4	8	162	57.4
197.parser	8	206	81.1	8	206	81.1
252.eon	8	106	114	8	106	114
253.perlbnk	8	197	84.8	8	197	84.8
254.gap	8	141	72.4	8	141	72.4
255.vortex	8	132	133	8	132	133
256.bzip2	8	176	79.2	8	176	79.2
300.twolf	8	325	85.6	8	325	85.6

Hardware

CPU: Intel Xeon 7140M processor (3.40 GHz, 2x1MB L2, 16MB L3, 800 MHz system bus)
CPU MHz: 3400
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip, per core
Secondary Cache: 1024KB(I+D) on chip, per core
L3 Cache: 16MB on chip, per chip
Other Cache: N/A
Memory: 16x1GB DDR2-RAM PC2-3200R (CAS 3-3-3)
Disk Subsystem: 1 x 36GB SCSI 10000 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio .NET 7.0.9466 (for libraries),
MicroQuill SmartHeap for SMP Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for C programs: -fast +FDO sh1SMPMt.lib
for C++ programs: -fast -Qcxx_features +FDO

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>