



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec LX201 (Intel Xeon 5130 processor, 2.00GHz)

SPECfp_rate2000 = 36.0

SPECfp_rate_base2000 = 36.0

SPEC license #: 9001 | Tested by: Itautec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	66.9	55.5	2	66.9	55.5
171.swim	2	225	32.0	2	225	32.0
172.mgrid	2	162	25.8	2	162	25.8
173.applu	2	177	27.6	2	177	27.6
177.mesa	2	76.8	42.3	2	76.8	42.3
178.galgel	2	76.5	88.0	2	76.5	88.0
179.art	2	68.2	88.4	2	68.2	88.4
183.equake	2	79.0	38.2	2	79.0	38.2
187.facerec	2	111	39.6	2	111	39.6
188.amp	2	194	26.3	2	194	26.3
189.lucas	2	174	26.6	2	174	26.6
191.fma3d	2	172	28.3	2	172	28.3
200.sixtrack	2	140	18.2	2	140	18.2
301.apsi	2	222	27.2	2	222	27.2

Hardware

CPU: Intel Xeon 5130 processor (2.00 GHz, 4MB L2, 1333 MHz system bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4096KB(I+D) on chip, per chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 4x1024MB + 4x512MB FB-DIMM DDR2 SDRAM ECC CL5 667MHz
Disk Subsystem: 1 x 200GB Serial ATA 7200 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060519Z (for 32-bit applications),
Intel Fortran Compiler 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio .NET 7.0.9466 (for libraries),
MicroQuill SmartHeap for SMP Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

178.galgel: -FI /F32000000

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO

for C programs: -fast +FDO shlSMPMt.lib

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>