



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB8(1.86GHz, Intel Xeon E5320 processor)

SPECint2000 = 1963

SPECint_base2000 = 1957

SPEC license #01176 Tested by: Supermicro Test date: Oct-2006 Hardware Avail: Nov-2006 Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000	2000	3000	4000
164.gzip	1400	121	1156	121	1162				
175.vpr	1400	98.3	1425	95.8	1462				
176.gcc	1100	52.1	2112	52.1	2112				
181.mcf	1800	56.3	3198	56.3	3198				
186.crafty	1000	58.2	1717	58.3	1716				
197.parser	1800	125	1446	125	1443				
252.eon	1300	53.9	2414	53.4	2436				
253.perlbmk	1800	78.3	2300	78.3	2300				
254.gap	1100	56.2	1959	56.2	1959				
255.vortex	1900	57.6	3300	57.6	3300				
256.bzip2	1500	100	1498	100	1493				
300.twolf	3000	141	2129	141	2133				

Hardware

CPU: Intel Xeon E5320 processor (1.86 GHz,1066MHz bus)
CPU MHz: 1860
FPU: Integrated
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
CPU(s) orderable: 1 chip
Parallel: N/A
Primary Cache: 32KBI + 32KBD on chip per core
Secondary Cache: 8 MB I+D on chip, per chip (4 MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 X 2GB DDR2 ECC CL5 667MHz FBDIMM
Disk Subsystem: 1 X Seagate Barracuda 120GB 7200 RPM
Other Hardware: N/A

Software

Operating System: Windows Server 2003 Enterprise Edition 32-bits w/ SP1
Compiler: Intel C++ Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_CC_P_9.1.020
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB8(1.86GHz, Intel Xeon E5320 processor)

SPECint2000 = 1963

SPECint_base2000 = 1957

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO
300.twolf: -fast -O3 +FDO shlw32m.lib

Tested systems can be used with SC816S-R700 case,
To ensure system stability, a 500W (minimum) ATX power supply [4-pin (+12V), 8-pin (+12V) and 24-pin are required]
Product description located as of <http://www.supermicro.com/products/motherboard/Xeon1333/5000P/X7DB8.cfm>

The system bus runs at 1066 MHz

shlw32m-80.lib is the V8.0 SmartHeap library renamed to co-exist with older versions