



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3650 (1.86 GHz Xeon 5120, 4MB L2 Cache)

SPECfp_rate2000 = --

SPECfp_rate_base2000 = 35.2

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	68.5	54.2			
171.swim	2	235	30.6			
172.mgrid	2	173	24.1			
173.applu	2	200	24.3			
177.mesa	2	76.8	42.3			
178.galgel	2	79.5	84.7			
179.art	2	63.3	95.3			
183.quake	2	79.4	38.0			
187.facerec	2	112	39.4			
188.amp	2	195	26.1			
189.lucas	2	146	31.9			
191.fma3d	2	182	26.8			
200.sixtrack	2	149	17.1			
301.apsi	2	255	23.7			

Hardware

CPU: Intel Xeon processor 5120 (1.86 GHz, 1066 MHz bus)
CPU MHz: 1866
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1, 2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
Secondary Cache: 4096KB(I+D) on chip (per chip)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1024 MB ECC PC2-5300F
Disk Subsystem: 73GB SAS 15K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
```