



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor X5355, 2.66 GHz

SPECfp_rate2000 = 60.8

SPECfp_rate_base2000 = 60.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	98.7	75.2	4	98.7	75.2
171.swim	4	425	33.8	4	425	33.8
172.mgrid	4	266	31.4	4	266	31.4
173.applu	4	291	33.5	4	291	33.5
177.mesa	4	53.5	121	4	53.5	121
178.galgel	4	75.3	179	4	75.3	179
179.art	4	68.2	177	4	68.2	177
183.quake	4	184	32.8	4	184	32.8
187.facerec	4	111	79.7	4	111	79.7
188.amp	4	127	80.4	4	127	80.4
189.lucas	4	251	37.0	4	251	37.0
191.fma3d	4	229	42.5	4	229	42.5
200.sixtrack	4	110	46.5	4	110	46.5
301.apsi	4	201	60.0	4	201	60.0

Hardware

CPU: Intel Xeon processor X5355 (2.66 GHz, 2x4MB L2, 1333 MHz system bus)
CPU MHz: 2666
FPU: Integrated
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10
Kernel 2.6.16.21-0.8-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.1 for EM64T
Build 20060816 (for 64-bit applications)
File System: ext2
System State: Multi-user runlevel 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
for Fortran and C programs: -fast +FDO

Peak tuning flags
same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor X5355, 2.66 GHz

SPECfp_rate2000 = 60.8

SPECfp_rate_base2000 = 60.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

BIOS Configuration:

Adjacent Sector Prefetch = disable

The PRIMERGY RX300 S3 and the PRIMERGY TX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>