



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX200 S3, Intel Xeon processor 5110, 1.60 GHz

SPECint_rate2000 = 70.3

SPECint_rate_base2000 = 70.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	4	144	45.0	4	144	45.0
175.vpr	4	126	51.4	4	126	51.4
176.gcc	4	63.0	81.1	4	63.0	81.1
181.mcf	4	128	65.3	4	128	65.3
186.crafty	4	68.6	67.7	4	68.6	67.7
197.parser	4	144	58.1	4	144	58.1
252.eon	4	62.9	95.8	4	62.9	95.8
253.perlbnk	4	95.2	87.7	4	95.2	87.7
254.gap	4	76.2	67.0	4	76.2	67.0
255.vortex	4	72.8	121	4	72.8	121
256.bzip2	4	133	52.5	4	133	52.5
300.twolf	4	164	84.6	4	164	84.6

Hardware

CPU: Intel Xeon processor 5110 (1.60 GHz, 4MB L2, 1066 MHz system bus)
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 4MB(I+D) on chip, per chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)
 Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)
 Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
 Compiler: Intel C++ Compiler 9.1
 Build 20060323Z (for 32-bit applications),
 Microsoft Visual Studio .Net 2003
 7.1.3088 (for libraries),
 SmartHeap Library Version 8.0
 from <http://www.microquill.com>
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32m.lib
 for C++ programs: -fast -Qcxx_features +FDO shlw32m.lib

Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 1066 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX200 S3, Intel Xeon processor 5110, 1.60 GHz

SPECint_rate2000 = 70.3

SPECint_rate_base2000 = 70.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>