



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460  
(Intel Xeon processor 5110,1.60GHz)

SPECfp<sup>®</sup>2006 = **9.88**

SPECfp\_base2006 = **9.69**

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2007

Hardware Availability: Mar-2007

Software Availability: Dec-2006



**Hardware**

CPU Name: Intel Xeon 5110  
 CPU Characteristics: 1.60 GHz, 4 MB L2, 1066 MHz system bus  
 CPU MHz: 1600  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 to 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip

*Continued on next page*

**Software**

Operating System: SuSE Linux Enterprise Server 10 (EM64T) kernel 2.6.16.21-0.8-smp  
 Compiler: Intel C++ Compiler for Intel EM64T-based applications, Version 9.1  
 Package ID l\_cc\_c\_9.1.045 Build no 20061101  
 Intel Fortran Compiler for Intel EM64T-based applications, Version 9.1  
 Package ID l\_fc\_c\_9.1.040 Build no 20061101  
 Auto Parallel: No

*Continued on next page*



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460  
(Intel Xeon processor 5110,1.60GHz)

SPECfp2006 = **9.88**

SPECfp\_base2006 = **9.69**

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2007

Hardware Availability: Mar-2007

Software Availability: Dec-2006

L3 Cache: None  
Other Cache: None  
Memory: 24 GB (12x2 GB) FB-DIMM PC2-5300F ECC CL5  
Disk Subsystem: 1x73 GB SAS, 15000 RPM  
Other Hardware: None

File System: ext2  
System State: Multi-user run level 3  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	<b>922</b>	<b>14.7</b>	923	14.7	922	14.7	<b>917</b>	<b>14.8</b>	918	14.8	917	14.8
416.gamess	1780	11.0	<b>1782</b>	<b>11.0</b>	1784	11.0	1930	10.1	<b>1929</b>	<b>10.2</b>	1927	10.2
433.milc	1142	8.04	<b>1142</b>	<b>8.04</b>	1143	8.03	<b>1145</b>	<b>8.02</b>	1145	8.02	1145	8.01
434.zeusmp	1014	8.97	1014	8.97	<b>1014</b>	<b>8.97</b>	1049	8.67	1049	8.68	<b>1049</b>	<b>8.68</b>
435.gromacs	739	9.66	731	9.77	<b>731</b>	<b>9.76</b>	712	10.0	706	10.1	<b>708</b>	<b>10.1</b>
436.cactusADM	1122	10.7	1136	10.5	<b>1130</b>	<b>10.6</b>	1137	10.5	<b>1146</b>	<b>10.4</b>	1150	10.4
437.leslie3d	1046	8.98	1045	9.00	<b>1046</b>	<b>8.99</b>	<b>1052</b>	<b>8.94</b>	1052	8.93	1052	8.94
444.namd	953	8.42	<b>954</b>	<b>8.41</b>	955	8.40	969	8.28	<b>968</b>	<b>8.28</b>	968	8.29
447.dealII	<b>759</b>	<b>15.1</b>	759	15.1	760	15.1	<b>738</b>	<b>15.5</b>	739	15.5	738	15.5
450.soplex	<b>924</b>	<b>9.02</b>	924	9.02	924	9.03	906	9.21	<b>907</b>	<b>9.19</b>	911	9.16
453.povray	479	11.1	480	11.1	<b>480</b>	<b>11.1</b>	<b>367</b>	<b>14.5</b>	368	14.5	367	14.5
454.calculix	966	8.54	<b>966</b>	<b>8.54</b>	967	8.53	<b>942</b>	<b>8.76</b>	942	8.75	942	8.76
459.GemsFDTD	<b>1206</b>	<b>8.80</b>	1206	8.80	1206	8.80	1212	8.75	<b>1212</b>	<b>8.75</b>	1212	8.75
465.tonto	1101	8.94	<b>1108</b>	<b>8.88</b>	1110	8.87	1053	9.34	1057	9.31	<b>1056</b>	<b>9.31</b>
470.lbm	2778	4.95	<b>2783</b>	<b>4.94</b>	2785	4.93	<b>2783</b>	<b>4.94</b>	2780	4.94	2785	4.93
481.wrf	1021	10.9	1021	10.9	<b>1021</b>	<b>10.9</b>	<b>1063</b>	<b>10.5</b>	1064	10.5	1062	10.5
482.sphinx3	1637	11.9	<b>1652</b>	<b>11.8</b>	1653	11.8	1495	13.0	<b>1497</b>	<b>13.0</b>	1501	13.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Environment stack size set to 'unlimited'

system was booted uniprocessor by setting "maxcpus=0"  
kernel parameter in menu.lst

/usr/bin/taskset utility used to bind CPU(s) to processes

## General Notes

The NovaScale R440 and the NovaScale R460 models are electronically equivalent.  
The results have been measured on a NovaScale R460 model.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460  
(Intel Xeon processor 5110,1.60GHz)

SPECfp2006 = 9.88

SPECfp\_base2006 = 9.69

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Bull SAS

Test date: May-2007  
Hardware Availability: Mar-2007  
Software Availability: Dec-2006

## Base Compiler Invocation

C benchmarks:  
icc  
  
C++ benchmarks:  
icpc  
  
Fortran benchmarks:  
ifort  
  
Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-fast  
  
C++ benchmarks:  
-fast  
  
Fortran benchmarks:  
-fast  
  
Benchmarks using both Fortran and C:  
-fast



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460  
(Intel Xeon processor 5110,1.60GHz)

SPECfp2006 = 9.88

SPECfp\_base2006 = 9.69

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: Bull SAS

Test date: May-2007  
Hardware Availability: Mar-2007  
Software Availability: Dec-2006

## Peak Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast -auto\_ilp32

C++ benchmarks:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast -auto\_ilp32

Fortran benchmarks:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast

Benchmarks using both Fortran and C:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast -auto\_ilp32

The flags file that was used to format this result can be browsed at  
[http://www.spec.org/cpu2006/flags/EM64T\\_Intel91\\_flags.html](http://www.spec.org/cpu2006/flags/EM64T_Intel91_flags.html)

You can also download the XML flags source by saving the following link:  
[http://www.spec.org/cpu2006/flags/EM64T\\_Intel91\\_flags.xml](http://www.spec.org/cpu2006/flags/EM64T_Intel91_flags.xml)



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460  
(Intel Xeon processor 5110,1.60GHz)

SPECfp2006 = 9.88

SPECfp\_base2006 = 9.69

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** Bull SAS

**Test date:** May-2007  
**Hardware Availability:** Mar-2007  
**Software Availability:** Dec-2006

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 11:10:04 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 12 June 2007.