



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint®\_rate2006 = 90.2

PowerEdge 6950 (AMD Opteron 8216, 2.40 GHz)

SPECint\_rate\_base2006 = 83.0

CPU2006 license: 55


Test date: Oct-2007

Test sponsor: Dell Inc.

Hardware Availability: Dec-2006

Tested by: Dell Inc.

Software Availability: Oct-2007



## Hardware

CPU Name: AMD Opteron 8216  
 CPU Characteristics:  
 CPU MHz: 2400  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip  
 CPU(s) orderable: 2,4 chips  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core  
 L3 Cache: None  
 Other Cache: None  
 Memory: 32 GB (16x2GB, DDR2-667 CL5 ECC Dual Rank)  
 Disk Subsystem: 1 x 250 GB SATA 7200 RPM  
 Other Hardware: None

## Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10 SP1  
 Compiler: The Portland Group (PGI)  
 PGI pgcc 7.1-0 C Compiler  
 PGI pgCC 7.1-0 C++ Compiler  
 Auto Parallel: No  
 File System: ReiserFS  
 System State: Multi-user, run level 3  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap 8.0 32-bit Library for Linux



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = 90.2

PowerEdge 6950 (AMD Opteron 8216, 2.40 GHz)

SPECint\_rate\_base2006 = 83.0

CPU2006 license: 55

Test date: Oct-2007

Test sponsor: Dell Inc.

Hardware Availability: Dec-2006

Tested by: Dell Inc.

Software Availability: Oct-2007

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	957	81.7	955	81.9	<b>956</b>	<b>81.8</b>	8	797	98.1	786	99.5	<b>786</b>	<b>99.5</b>
401.bzip2	8	1187	65.0	<b>1193</b>	<b>64.7</b>	1195	64.6	8	<b>1171</b>	<b>65.9</b>	1171	65.9	1173	65.8
403.gcc	8	1286	50.1	<b>1295</b>	<b>49.7</b>	1299	49.6	8	954	67.5	<b>955</b>	<b>67.5</b>	956	67.4
429.mcf	8	1127	64.8	1125	64.9	<b>1125</b>	<b>64.8</b>	8	836	87.2	<b>837</b>	<b>87.1</b>	838	87.1
445.gobmk	8	885	94.9	<b>885</b>	<b>94.8</b>	885	94.8	8	822	102	<b>822</b>	<b>102</b>	823	102
456.hmmer	8	602	124	601	124	<b>601</b>	<b>124</b>	8	566	132	569	131	<b>567</b>	<b>132</b>
458.sjeng	8	1077	89.9	<b>1075</b>	<b>90.1</b>	1074	90.1	8	1022	94.8	<b>1022</b>	<b>94.7</b>	1031	93.9
462.libquantum	8	1192	139	<b>1184</b>	<b>140</b>	1180	140	8	1192	139	<b>1184</b>	<b>140</b>	1180	140
464.h264ref	8	<b>1343</b>	<b>132</b>	1343	132	1349	131	8	<b>1343</b>	<b>132</b>	1343	132	1349	131
471.omnetpp	8	877	57.0	<b>876</b>	<b>57.1</b>	875	57.1	8	877	57.0	<b>876</b>	<b>57.1</b>	875	57.1
473.astar	8	<b>886</b>	<b>63.4</b>	885	63.4	890	63.1	8	<b>886</b>	<b>63.4</b>	885	63.4	890	63.1
483.xalancbmk	8	626	88.1	<b>627</b>	<b>88.0</b>	628	87.9	8	623	88.5	624	88.4	<b>623</b>	<b>88.5</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

```
'ulimit -s unlimited' was used to set environment stack size
'ulimit -l 2457600' was used to set environment locked pages in memory quantity
'numactl' was used to bind one copy per core, and memory to a local NUMA node
Set vm/nr_hugepages=1200 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages
Environment variable PGI_HUGE_PAGES set to 150
```

## Base Compiler Invocation

C benchmarks:  
pgcc

C++ benchmarks:  
pgcpp

## Base Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = 90.2

PowerEdge 6950 (AMD Opteron 8216, 2.40 GHz)

SPECint\_rate\_base2006 = 83.0

CPU2006 license: 55

Test date: Oct-2007

Test sponsor: Dell Inc.

Hardware Availability: Dec-2006

Tested by: Dell Inc.

Software Availability: Oct-2007

## Base Portability Flags (Continued)

458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-fast -Mipa=fast -Mipa=inline -Mipa=noarg -Mfprelaxed  
-Msmartalloc=huge:64 -tp k8-64 -Bstatic\_pgi

C++ benchmarks:

-fastsse -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartalloc --zc\_eh  
-tp k8-32 -Bstatic\_pgi -lsmartheap

## Base Other Flags

C benchmarks:

-w

C++ benchmarks:

-w -L/proj/qa/smartheap/SmartHeap\_8/lib

## Peak Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgcpp

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64  
445.gobmk: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = 90.2

PowerEdge 6950 (AMD Opteron 8216, 2.40 GHz)

SPECint\_rate\_base2006 = 83.0

CPU2006 license: 55

Test date: Oct-2007

Test sponsor: Dell Inc.

Hardware Availability: Dec-2006

Tested by: Dell Inc.

Software Availability: Oct-2007

## Peak Optimization Flags

C benchmarks:

400.perlbench: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=inline(pass 2) -fast  
-O4 -Mfp relaxed -Msmartalloc=huge:8 -Mnounroll -tp k8-64  
-Bstatic\_pgi

401.bzip2: -Mpfi(pass 1) -Mpfo(pass 2) -fast -O4  
-Msmartalloc=huge:64 -tp k8-64 -Bstatic\_pgi

403.gcc: -fastsse -Mfp relaxed -Msmartalloc=huge:32 -Mipa=fast  
-Mipa=inline -tp k8-32 -Bstatic\_pgi

429.mcf: -fastsse -Mipa=fast -Mipa=inline -Msmartalloc=huge:16  
-tp k8-32 -Bstatic\_pgi

445.gobmk: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2) -fast -O4  
-Msmartalloc=huge:32 -Mfp relaxed -Mnovect -tp k8-64  
-Bstatic\_pgi

456.hmmer: -fast -Msmartalloc=huge:32 -Mfp relaxed -Msafeptr  
-Mipa=const -Mipa=ptr -Mipa=arg -tp k8-64 -Bstatic\_pgi

458.sjeng: -Mpfi(pass 1) -Mipa=fast(pass 2) -Mipa=inline(pass 2)  
-Mipa=noarg(pass 2) -Mpfo(pass 2) -fast  
-Msmartalloc=huge:32 -Mfp relaxed -tp k8-64 -Bstatic\_pgi

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar: basepeak = yes

483.xalancbmk: -fastsse -O4 -Mipa=fast -Mipa=inline -Mfp relaxed  
-Msmartalloc --zc\_eh -tp k8-32 -Bstatic\_pgi -lsmarheap

## Peak Other Flags

C benchmarks:

-w

C++ benchmarks:

-w -L/proj/qa/smarheap/SmartHeap\_8/lib



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint\_rate2006 = 90.2

PowerEdge 6950 (AMD Opteron 8216, 2.40 GHz)

SPECint\_rate\_base2006 = 83.0

CPU2006 license: 55

Test date: Oct-2007

Test sponsor: Dell Inc.

Hardware Availability: Dec-2006

Tested by: Dell Inc.

Software Availability: Oct-2007

The flags file that was used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/pgi710\\_flags.html](http://www.spec.org/cpu2006/flags/pgi710_flags.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/cpu2006/flags/pgi710\\_flags.xml](http://www.spec.org/cpu2006/flags/pgi710_flags.xml)

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 14:13:54 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 30 October 2007.