



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint®2006 = 21.7

IBM System p 570 (4.7 GHz, 1 core, RHEL)

SPECint_base2006 = 17.8

CPU2006 license: 11


Test date: Oct-2007

Test sponsor: IBM Corporation

Hardware Availability: Jun-2007

Tested by: IBM Corporation

Software Availability: Oct-2007



Hardware

CPU Name:	POWER6
CPU Characteristics:	
CPU MHz:	4700
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 2 cores/chip
CPU(s) orderable:	2,4,8,12,16 cores
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per core
L3 Cache:	32 MB I+D off chip per chip
Other Cache:	None
Memory:	32 GB (16x2 GB) DDR2 667 MHz
Disk Subsystem:	2x73 GB SAS 15K RPM
Other Hardware:	None

Software

Operating System:	Red Hat Enterprise Linux Advanced Platform 5.1 for IBM POWER
Compiler:	IBM XL C/C++ Advanced Edition for Linux, V9.0
Auto Parallel:	No
File System:	ext3
System State:	Multi-User
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	-IBM Post-Link Optimization for Linux on POWER, Version 5.4.0-10 -MicroQuill SmartHeap 8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System p 570 (4.7 GHz, 1 core, RHEL)

SPECint2006 = 21.7

SPECint_base2006 = 17.8

CPU2006 license: 11

Test date: Oct-2007

Test sponsor: IBM Corporation

Hardware Availability: Jun-2007

Tested by: IBM Corporation

Software Availability: Oct-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
400.perlbench	867	11.3	867	11.3	867	11.3	672	14.5	672	14.5	672	14.5
401.bzip2	678	14.2	681	14.2	676	14.3	595	16.2	597	16.2	598	16.1
403.gcc	479	16.8	479	16.8	479	16.8	391	20.6	392	20.6	391	20.6
429.mcf	259	35.2	259	35.2	259	35.2	246	37.1	246	37.1	246	37.1
445.gobmk	665	15.8	665	15.8	665	15.8	570	18.4	570	18.4	570	18.4
456.hammer	721	12.9	721	12.9	721	12.9	573	16.3	573	16.3	573	16.3
458.sjeng	873	13.9	873	13.9	874	13.9	768	15.7	768	15.8	768	15.7
462.libquantum	402	51.5	402	51.6	402	51.6	209	99.3	208	99.4	208	99.5
464.h264ref	933	23.7	933	23.7	932	23.7	725	30.5	725	30.5	725	30.5
471.omnetpp	431	14.5	431	14.5	434	14.4	404	15.5	402	15.6	402	15.5
473.astar	582	12.1	582	12.1	582	12.1	484	14.5	485	14.5	485	14.5
483.xalancbmk	381	18.1	381	18.1	381	18.1	355	19.4	356	19.4	356	19.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

kernel release 2.6.18-52.el5.

See flags file for details on following settings.

ulimit -s (stack) set to 262144.

System set to Enhanced mode when defining partition on HMC

Large pages reserved as follows by root user:

```
echo 200 > /proc/sys/vm/nr_hugepages
```

System configured with libhugetlbfs library for application access to large pages
Environment variables set before executing benchmarks.

```
export HUGETLB_VERBOSE=0
export HUGETLB_MORECORE=yes
export XLF RTEOPTS=intrinthds=1
```

Linux booted with the options:
maxcpus=1 smt-enabled=off

fdpr binary optimization tool used for
400.perlbench 401.bzip2 403.gcc 429.mcf 456.hammer 458.sjeng
462.libquantum 464.h264ref 473.astar 483.xalancbmk

Benchmarks bound to a processor using numactl on the submit command.



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 21.7

IBM System p 570 (4.7 GHz, 1 core, RHEL)

SPECint_base2006 = 17.8

CPU2006 license: 11

Test date: Oct-2007

Test sponsor: IBM Corporation

Hardware Availability: Jun-2007

Tested by: IBM Corporation

Software Availability: Oct-2007

Base Compiler Invocation

C benchmarks:

`xlc -qlanglvl=extc99`

C++ benchmarks:

`x1C`

Base Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_PPC`

462.libquantum: `-DSPEC_CPU_LINUX`

`464.h264ref: -qchars=signed`

483.xalancbmk: `-DSPEC_CPU_LINUX`

Base Optimization Flags

C benchmarks:

`-O5 -qalias=noansi -galloca -lhugetlbfs`

C++ benchmarks:

`-O5 -qrtti -lsmartheap`

Base Other Flags

C benchmarks:

`-qipa=noobject -qipa=threads`

C++ benchmarks:

`-qipa=noobject -qipa=threads`

Peak Compiler Invocation

C benchmarks:

`xlc -qlanglvl=extc99`

C++ benchmarks:

`x1C`



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System p 570 (4.7 GHz, 1 core, RHEL)

SPECint2006 = 21.7

SPECint_base2006 = 17.8

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Oct-2007

Hardware Availability: Jun-2007

Software Availability: Oct-2007

Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LINUX_PPC
    403.gcc: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
    464.h264ref: -qchars=signed
483.xalancbmk: -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qalias=noansi
    -lsmartheap

401.bzip2: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -lhugetlbfs

403.gcc: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qalloc -q64
    -lhugetlbfs

429.mcf: -Wl,-q -O5 -qnoenablevmx -lhugetlbfs

445.gobmk: -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qnoenablevmx
    -lhugetlbfs

456.hmmer: Same as 401.bzip2

458.sjeng: Same as 401.bzip2

462.libquantum: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qnoenablevmx
    -q64 -lhugetlbfs

464.h264ref: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -q64
    -lhugetlbfs
```

C++ benchmarks:

```
471.omnetpp: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qrtti -lsmartheap

473.astar: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qnoenablevmx
    -lsmartheap

483.xalancbmk: -Wl,-q -O4 -lsmartheap
```

Peak Other Flags

C benchmarks:

-qipa=noobject -qipa=threads

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 21.7

IBM System p 570 (4.7 GHz, 1 core, RHEL)

SPECint_base2006 = 17.8

CPU2006 license: 11

Test date: Oct-2007

Test sponsor: IBM Corporation

Hardware Availability: Jun-2007

Tested by: IBM Corporation

Software Availability: Oct-2007

Peak Other Flags (Continued)

C++ benchmarks:

-qipa=noobject -qipa=threads

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/lop-xl-flags.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/lop-xl-flags.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 14:29:30 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 27 November 2007.