



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint®_rate2006 = 51.3

Acer Altos R5250 (AMD Opteron 2220 SE)

SPECint_rate_base2006 = 45.6

CPU2006 license: 97


Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Jul-2007

Hardware Availability: Dec-2007

Software Availability: Jun-2007



Hardware

CPU Name: AMD Opteron 2220 SE
 CPU Characteristics:
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (16x1GB, DDR2-667 CL5 ECC Reg)
 Disk Subsystem: 1 x SATA, 160 GB
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 EM64T kernel
 Compiler: QLogic PathScale
 Compiler Suite, Release 3.0
 Auto Parallel: No
 File System: ReiserFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap 8.0 32 bit Library for Linux



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 51.3

Acer Altos R5250 (AMD Opteron 2220 SE)

SPECint_rate_base2006 = 45.6

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Jul-2007

Hardware Availability: Dec-2007

Software Availability: Jun-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	791	49.4	<u>783</u>	<u>49.9</u>	783	49.9	4	635	61.5	<u>635</u>	<u>61.6</u>	633	61.7
401.bzip2	4	1103	35.0	<u>1085</u>	<u>35.6</u>	1061	36.4	4	1075	35.9	1057	36.5	<u>1059</u>	<u>36.5</u>
403.gcc	4	1023	31.5	<u>998</u>	<u>32.3</u>	990	32.5	4	<u>772</u>	<u>41.7</u>	771	41.8	772	41.7
429.mcf	4	1016	35.9	995	36.6	<u>996</u>	<u>36.6</u>	4	779	46.8	767	47.6	<u>768</u>	<u>47.5</u>
445.gobmk	4	750	55.9	748	56.1	<u>749</u>	<u>56.1</u>	4	637	65.9	<u>636</u>	<u>65.9</u>	636	66.0
456.hmmer	4	681	54.8	676	55.2	<u>678</u>	<u>55.0</u>	4	506	73.8	<u>506</u>	<u>73.8</u>	505	73.9
458.sjeng	4	944	51.3	942	51.4	<u>943</u>	<u>51.3</u>	4	<u>865</u>	<u>55.9</u>	865	56.0	866	55.9
462.libquantum	4	1974	42.0	<u>1829</u>	<u>45.3</u>	1797	46.1	4	1785	46.4	<u>1777</u>	<u>46.6</u>	1764	47.0
464.h264ref	4	1087	81.4	1079	82.0	<u>1082</u>	<u>81.8</u>	4	1021	86.7	<u>1037</u>	<u>85.4</u>	1047	84.6
471.omnetpp	4	759	32.9	<u>740</u>	<u>33.8</u>	735	34.0	4	736	34.0	734	34.1	<u>734</u>	<u>34.1</u>
473.astar	4	803	35.0	<u>793</u>	<u>35.4</u>	792	35.5	4	803	35.0	<u>793</u>	<u>35.4</u>	792	35.5
483.xalancbmk	4	504	54.8	<u>499</u>	<u>55.3</u>	499	55.3	4	488	56.6	487	56.7	<u>487</u>	<u>56.6</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

taskset utility used to bind cores to processes

This result was measured on the Acer Altos G5450

The Altos G5450 and Altos R5250 are electronically equivalent.

Base Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC

Base Portability Flags

```

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 51.3

Acer Altos R5250 (AMD Opteron 2220 SE)

SPECint_rate_base2006 = 45.6

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Jul-2007

Hardware Availability: Dec-2007

Software Availability: Jun-2007

Base Portability Flags (Continued)

464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-Ofast -OPT:malloc_alg=1

C++ benchmarks:

-Ofast -m32 -L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap

Peak Compiler Invocation

C benchmarks:

pathcc

C++ benchmarks:

pathCC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
-LNO:opt=0

401.bzip2: -O3 -LNO:ou_prod_max=10 -OPT:Ofast -OPT:alias=disjoint

403.gcc: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -m32 -O3
-OPT:Ofast

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 51.3

Acer Altos R5250 (AMD Opteron 2220 SE)

SPECint_rate_base2006 = 45.6

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Jul-2007

Hardware Availability: Dec-2007

Software Availability: Jun-2007

Peak Optimization Flags (Continued)

429.mcf: -m32 -O3 -ipa
-L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap

445.gobmk: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-OPT:alias=disjoint -LNO:simd=0 -LNO:minvariant=off
-WOPT:retype_expr=on

456.hmmer: -O2 -OPT:alias=disjoint -OPT:malloc_alg=1 -CG:cflow=0

458.sjeng: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-IPA:plimit=50000 -IPA:pu_reorder=2

462.libquantum: -O3 -ipa -CG:local_fwd_sched=on -IPA:space=1000

464.h264ref: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-IPA:plimit=20000 -OPT:alias=disjoint -LNO:prefetch=0

C++ benchmarks:

471.omnetpp: -Ofast -CG:gcm=off -m32
-L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: -Ofast -m32 -OPT:unroll_times_max=8
-L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:45:39 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 11 December 2007.