



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint®_rate2006 = 82.1

ProLiant BL460c
(3.33 GHz, Intel Xeon processor X5260)

SPECint_rate_base2006 = 70.0

CPU2006 license: 3


Test date: Dec-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon X5260
 CPU Characteristics: 3.33 GHz, 6 MB L2 shared, 1333 MHz system bus
 CPU MHz: 3333
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 6 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2 GB PC2-5300F CL5)
 Disk Subsystem: 1x72 GB 15 K SAS
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1
 Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ Compiler for applications running on IA-32 and Intel 64, Version 10.1
 Build 20070913 Package ID: l_cc_p_10.1.008
 Auto Parallel: Yes
 File System: ext2
 System State: Multi-user run level 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.1
 binutils-2.17.50



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 82.1

ProLiant BL460c
(3.33 GHz, Intel Xeon processor X5260)

SPECint_rate_base2006 = 70.0

CPU2006 license: 3

Test date: Dec-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	<u>471</u>	<u>82.9</u>	472	82.7	468	83.5	4	390	100	394	99.3	<u>390</u>	<u>100</u>
401.bzip2	4	632	61.1	636	60.7	<u>632</u>	<u>61.1</u>	4	604	63.9	598	64.5	<u>600</u>	<u>64.3</u>
403.gcc	4	502	64.1	<u>500</u>	<u>64.4</u>	500	64.4	4	500	64.4	<u>501</u>	<u>64.2</u>	503	64.0
429.mcf	4	600	60.8	<u>601</u>	<u>60.7</u>	602	60.6	4	577	63.2	578	63.1	<u>578</u>	<u>63.2</u>
445.gobmk	4	498	84.3	<u>495</u>	<u>84.7</u>	495	84.8	4	<u>461</u>	<u>91.0</u>	461	90.9	460	91.3
456.hammer	4	531	70.3	531	70.3	<u>531</u>	<u>70.3</u>	4	309	121	<u>310</u>	<u>120</u>	310	120
458.sjeng	4	624	77.6	<u>623</u>	<u>77.6</u>	623	77.7	4	<u>563</u>	<u>86.0</u>	565	85.7	562	86.1
462.libquantum	4	<u>1538</u>	<u>53.9</u>	1538	53.9	1538	53.9	1	178	116	179	116	<u>179</u>	<u>116</u>
464.h264ref	4	<u>633</u>	<u>140</u>	634	140	633	140	4	<u>608</u>	<u>145</u>	609	145	608	146
471.omnetpp	4	<u>561</u>	<u>44.6</u>	561	44.6	561	44.6	4	526	47.5	<u>526</u>	<u>47.5</u>	526	47.5
473.astar	4	544	51.6	536	52.4	<u>544</u>	<u>51.6</u>	4	507	55.4	510	55.0	<u>509</u>	<u>55.2</u>
483.xalancbmk	4	319	86.6	<u>319</u>	<u>86.6</u>	320	86.3	4	319	86.6	<u>319</u>	<u>86.6</u>	320	86.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 64M

Platform Notes

BIOS configuration:
Power Regulator set to Static High Performance Mode
Adjacent Sector Prefetch Disabled

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 82.1

ProLiant BL460c
(3.33 GHz, Intel Xeon processor X5260)

SPECint_rate_base2006 = 70.0

CPU2006 license: 3

Test date: Dec-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Base Portability Flags (Continued)

462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/cpu2006/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 82.1

ProLiant BL460c
(3.33 GHz, Intel Xeon processor X5260)

SPECint_rate_base2006 = 70.0

CPU2006 license: 3

Test date: Dec-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
               -prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
           -no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch
                -opt-streaming-stores always -vec-guard-write
                -opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
             -ansi-alias
```

C++ benchmarks:

```
471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
              -no-prec-div -ansi-alias -opt-ra-region-strategy=block
              -Wl,-z,muldefs -L/cpu2006/SmartHeap_8.1/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
            -no-prec-div -ansi-alias -opt-ra-region-strategy=routine
            -Wl,-z,muldefs -L/cpu2006/SmartHeap_8.1/lib -lsmartheap

483.xalancbmk: basepeak = yes
```

Peak Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-int-flags.20090714.00.html>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint_rate2006 = 82.1

ProLiant BL460c
(3.33 GHz, Intel Xeon processor X5260)

SPECint_rate_base2006 = 70.0

CPU2006 license: 3

Test date: Dec-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2008

Tested by: Hewlett-Packard Company

Software Availability: Nov-2007

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/HP-Intel-ic10.1-linux-int-flags.20090714.00.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 15:14:26 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 14 January 2008.