



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint®2006 = 20.8

IBM BladeCenter LS42 (AMD Opteron 8384)

SPECint_base2006 = 17.8

CPU2006 license: 11


Test date: Oct-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: Advanced Micro Devices

Software Availability: May-2008



Hardware

CPU Name: AMD Opteron 8384
 CPU Characteristics:
 CPU MHz: 2700
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2,3,4 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core
 L3 Cache: 6 MB I+D on chip per chip
 Other Cache: None
 Memory: 32 GB (8 x 4 GB DDR2-6400 ECC)
 Disk Subsystem: 1 x 73 GB SAS, 10000 RPM
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16.60-0.21-smp
 Compiler: PGI Server Complete Version 7.2
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Run level 3 (Full multiuser with network)
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: binutils 2.18.50
 32-bit and 64-bit libhugetlbfs libraries
 SmartHeap 8.1 32-bit Library for Linux



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 20.8

IBM BladeCenter LS42 (AMD Opteron 8384)

SPECint_base2006 = 17.8

CPU2006 license: 11

Test date: Oct-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: Advanced Micro Devices

Software Availability: May-2008

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	<u>631</u>	<u>15.5</u>	631	15.5	623	15.7	<u>526</u>	<u>18.6</u>	526	18.6	529	18.5
401.bzip2	<u>741</u>	<u>13.0</u>	740	13.0	742	13.0	676	14.3	677	14.3	<u>676</u>	<u>14.3</u>
403.gcc	592	13.6	592	13.6	<u>592</u>	<u>13.6</u>	555	14.5	555	14.5	<u>555</u>	<u>14.5</u>
429.mcf	477	19.1	552	16.5	<u>477</u>	<u>19.1</u>	313	29.1	314	29.0	<u>314</u>	<u>29.0</u>
445.gobmk	751	14.0	<u>751</u>	<u>14.0</u>	751	14.0	660	15.9	661	15.9	<u>660</u>	<u>15.9</u>
456.hammer	525	17.8	529	17.7	<u>525</u>	<u>17.8</u>	300	31.1	<u>300</u>	<u>31.1</u>	300	31.1
458.sjeng	<u>824</u>	<u>14.7</u>	824	14.7	824	14.7	754	16.0	755	16.0	<u>755</u>	<u>16.0</u>
462.libquantum	282	73.4	<u>286</u>	<u>72.4</u>	295	70.3	<u>244</u>	<u>84.9</u>	229	90.6	244	84.8
464.h264ref	970	22.8	<u>967</u>	<u>22.9</u>	966	22.9	897	24.7	892	24.8	<u>893</u>	<u>24.8</u>
471.omnetpp	<u>437</u>	<u>14.3</u>	437	14.3	439	14.2	<u>437</u>	<u>14.3</u>	437	14.3	439	14.2
473.astar	<u>534</u>	<u>13.1</u>	534	13.2	535	13.1	<u>523</u>	<u>13.4</u>	523	13.4	524	13.4
483.xalancbmk	403	17.1	404	17.1	<u>403</u>	<u>17.1</u>	<u>372</u>	<u>18.6</u>	370	18.6	374	18.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
'numactl' was used to bind copies to the cores.

General Notes

The libhugetlbfs libraries were installed using the installation rpms that came with the distribution.

'ulimit -s unlimited' was used to set environment stack size
'ulimit -l 2097152' was used to set environment locked pages in memory limit

Set vm/nr_hugepages=7168 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages

Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/root/work/cpu2006v1.1/pgi72/linux_lib64:/root/work/cpu2006v1.1/pgi72/linux_lib32"
PGI_HUGE_PAGES = "7168"
NCPUS = "8"

The powersaved was disabled, set the CPU frequency to its maximum.

Base Compiler Invocation

C benchmarks:
pgcc

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 20.8

IBM BladeCenter LS42 (AMD Opteron 8384)

SPECint_base2006 = 17.8

CPU2006 license: 11

Test date: Oct-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: Advanced Micro Devices

Software Availability: May-2008

Base Compiler Invocation (Continued)

C++ benchmarks:
pgcpp

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-Mvect=cachesize:6291456 -fastsse -Msmartalloc=huge -Mloop32
-Mconcur=innermost -Mfprelaxed -Mipa=fast -Mipa=inline
-tp barcelona-64 -Bstatic_pgi

C++ benchmarks:
-Mvect=cachesize:6291456 -fastsse -Msmartalloc=huge -Mloop32
-Mfprelaxed --zc_eh -Mipa=fast -Mipa=inline:10 -tp barcelona-32
-Bstatic_pgi

Base Other Flags

C benchmarks:
-Mipa=jobs:8

C++ benchmarks:
-Mipa=jobs:8

Peak Compiler Invocation

C benchmarks:
pgcc

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 20.8

IBM BladeCenter LS42 (AMD Opteron 8384)

SPECint_base2006 = 17.8

CPU2006 license: 11

Test date: Oct-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: Advanced Micro Devices

Software Availability: May-2008

Peak Compiler Invocation (Continued)

C++ benchmarks:
pgcpp

Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=inline(pass 2)
-Mvect=cachesize:6291456 -fastsse -O4 -Msmartalloc=huge
-Mnovect -Mnounroll -Mfprelaxed -tp barcelona-64
-Bstatic_pgi

401.bzip2: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2)
-Mvect=cachesize:6291456 -fastsse -O4 -Msmartalloc=huge
-Mprefetch=t0 -Mnounroll -tp barcelona-64 -Bstatic_pgi

403.gcc: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)
-Mipa=inline(pass 2) -Mvect=cachesize:6291456 -fastsse
-Msmartalloc=huge -Mprefetch=t0 -Mnodalign -Mloop32
-Mfprelaxed -tp barcelona-32 -Bstatic_pgi

429.mcf: -Mvect=cachesize:6291456 -fastsse -Msmartalloc=huge
-Mipa=fast -Mipa=inline:1 -tp barcelona-32 -Bstatic_pgi

445.gobmk: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)
-Mvect=cachesize:6291456 -fastsse -O4 -Msmartalloc=huge
-Mnovect -Mfprelaxed -tp barcelona-64 -Bstatic_pgi

456.hmmer: -Mvect=cachesize:6291456 -fastsse -Mvect=partial
-Munroll=n:8 -Msmartalloc=huge -Msafeptr -Mprefetch=t0
-Mfprelaxed -Mipa=const -Mipa=ptr -Mipa=arg -Mipa=inline
-tp barcelona-64 -Bstatic_pgi

458.sjeng: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)
-Mipa=inline:1(pass 2) -Mipa=noarg(pass 2)
-Mvect=cachesize:6291456 -fastsse -Msmartalloc=huge
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 20.8

IBM BladeCenter LS42 (AMD Opteron 8384)

SPECint_base2006 = 17.8

CPU2006 license: 11

Test date: Oct-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: Advanced Micro Devices

Software Availability: May-2008

Peak Optimization Flags (Continued)

458.sjeng (continued):

-Mfprelaxed -tp barcelona-64 -Bstatic_pgi

462.libquantum:

-Mvect=cachesize:6291456 -fastsse -Munroll=m:8
-Msmartalloc=huge -Mprefetch=distance:8 -Mconcur=innermost
-Mconcur=noaltcode -Mfprelaxed -Mipa=fast -Mipa=noarg
-tp barcelona-64 -Bstatic_pgi

464.h264ref:

-Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2)
-Mipa=fast(pass 2) -Mipa=inline(pass 2)
-Mvect=cachesize:6291456 -fastsse -Msmartalloc=huge
-Mfprelaxed -tp barcelona-64 -Bstatic_pgi

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar:

-Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)
-Mipa=inline:6(pass 2) -Mvect=cachesize:6291456 -fastsse
-O4 -Msmartalloc=huge -Msafeptr=global -Mloop32
-Mfprelaxed --zc_eh -tp barcelona-32 -Bstatic_pgi

483.xalancbmk:

-Mvect=cachesize:6291456 --zc_eh -fastsse -O4 -Mfprelaxed
-Msmartalloc -Mipa=fast -Mipa=inline -tp barcelona-32
-Bstatic_pgi -lsmarheap

Peak Other Flags

C benchmarks (except as noted below):

-Mipa=jobs:8(pass 2)

401.bzip2: No flags used

C++ benchmarks (except as noted below):

-Mipa=jobs:8(pass 2)

483.xalancbmk: -Mipa=jobs:8 -L/proj/qa/smarheap/SmartHeap_8.1/lib

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/pgi72_linux_flags.20090713.01.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/pgi72_linux_flags.20090713.01.xml



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 20.8

IBM BladeCenter LS42 (AMD Opteron 8384)

SPECint_base2006 = 17.8

CPU2006 license: 11

Test date: Oct-2008

Test sponsor: IBM Corporation

Hardware Availability: Nov-2008

Tested by: Advanced Micro Devices

Software Availability: May-2008

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 21:19:37 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 9 December 2008.