



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Oracle Corporation SPARC Enterprise M8000

SPECfp<sup>®</sup>\_rate2006 = 786

SPECfp\_rate\_base2006 = 711

CPU2006 license: 6


Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: Nov-2010

Hardware Availability: Dec-2010

Software Availability: Sep-2010



### Hardware

CPU Name: SPARC64 VII+  
 CPU Characteristics:  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 64 cores, 16 chips, 4 cores/chip, 2 threads/core  
 CPU(s) orderable: 1 to 4 CMUs; each CMU contains 2 or 4 CPU chips  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip

Continued on next page

### Software

Operating System: Oracle Solaris 10 9/10  
 Compiler: Oracle Solaris Studio 12.2  
 Auto Parallel: Yes  
 File System: ufs  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: 32-bit  
 Other Software: None



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation  
SPARC Enterprise M8000

SPECfp\_rate2006 = 786

SPECfp\_rate\_base2006 = 711

CPU2006 license: 6  
Test sponsor: Oracle Corporation  
Tested by: Oracle Corporation

Test date: Nov-2010  
Hardware Availability: Dec-2010  
Software Availability: Sep-2010

L3 Cache: None  
Other Cache: None  
Memory: 512 GB (128 x 4 GB, 8-way interleaved)  
Disk Subsystem: 698 GB mirrored partition on  
12 x 146 GB 15K RPM SAS disks  
in each of 2 StorageTek 2530 Array  
(24 total disk, 12 in each array)  
Other Hardware: None

## Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	127	3235	533	3191	541	<u>3192</u>	<u>541</u>	127	<u>3191</u>	<u>541</u>	3192	541	3191	541		
416.gamess	127	<u>2645</u>	<u>940</u>	2632	945	2705	919	127	<u>2499</u>	<u>995</u>	2498	996	2527	984		
433.milc	127	2297	508	2298	507	<u>2297</u>	<u>507</u>	127	2297	508	2298	507	<u>2297</u>	<u>507</u>		
434.zeusmp	127	<u>1441</u>	<u>802</u>	1440	802	1444	801	127	1441	802	<u>1431</u>	<u>808</u>	1430	808		
435.gromacs	127	900	1010	888	1020	<u>893</u>	<u>1020</u>	127	840	1080	<u>831</u>	<u>1090</u>	829	1090		
436.cactusADM	127	<u>1426</u>	<u>1060</u>	1425	1070	1430	1060	63	633	1190	<u>632</u>	<u>1190</u>	628	1200		
437.leslie3d	127	2881	414	<u>2880</u>	<u>415</u>	2879	415	63	<u>1399</u>	<u>423</u>	1399	423	1399	423		
444.namd	127	981	1040	942	1080	<u>975</u>	<u>1050</u>	127	844	1210	<u>844</u>	<u>1210</u>	844	1210		
447.dealII	127	<u>912</u>	<u>1590</u>	911	1590	912	1590	127	<u>896</u>	<u>1620</u>	890	1630	910	1600		
450.soplex	127	<u>2958</u>	<u>358</u>	2954	359	2960	358	64	1392	384	<u>1377</u>	<u>388</u>	1375	388		
453.povray	127	596	1130	600	1130	<u>597</u>	<u>1130</u>	127	<u>429</u>	<u>1580</u>	429	1580	428	1580		
454.calculix	127	<u>769</u>	<u>1360</u>	765	1370	772	1360	127	<u>704</u>	<u>1490</u>	703	1490	704	1490		
459.GemsFDTD	127	<u>4141</u>	<u>325</u>	4153	324	4141	325	127	<u>4141</u>	<u>325</u>	4153	324	4141	325		
465.tonto	127	<u>1214</u>	<u>1030</u>	1204	1040	1218	1030	127	1158	1080	<u>1160</u>	<u>1080</u>	1170	1070		
470.lbm	127	5210	335	<u>5210</u>	<u>335</u>	5210	335	1	21.5	640	21.5	638	<u>21.5</u>	<u>639</u>		
481.wrf	127	<u>2174</u>	<u>653</u>	2177	652	2169	654	127	2131	666	2128	667	<u>2131</u>	<u>666</u>		
482.sphinx3	127	5049	490	<u>5049</u>	<u>490</u>	5042	491	64	2415	517	2423	515	<u>2418</u>	<u>516</u>		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

Oracle Solaris Studio 12.2 is distributed with mandatory OS patches  
118683-05 119963-20 120753-08  
Oracle Solaris Studio 12.2 and patches are available at  
<http://oracle.com/goto/solarisstudio>

The Apache C++ Standard Library V4.2.1 was installed from  
<http://stdcxx.apache.org/download.html> using:  
alias gmake=specmake  
gmake BUILDTYPE=8d CONFIG=sunpro.config



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation  
SPARC Enterprise M8000

SPECfp\_rate2006 = 786  
SPECfp\_rate\_base2006 = 711

CPU2006 license: 6  
Test sponsor: Oracle Corporation  
Tested by: Oracle Corporation

Test date: Nov-2010  
Hardware Availability: Dec-2010  
Software Availability: Sep-2010

## Submit Notes

Processes were assigned to specific processors using 'pbind' commands. The config file option 'submit' was used, along with a list of processors in the 'BIND' variable, to generate the pbind commands. (For details, please see the config file.)

## Operating System Notes

ulimit -s 131072 was used to limit the space consumed by the stack (and therefore make more space available to the heap).

```
/etc/system parameters
autoup=600
    Causes pages older than the listed number of seconds to
    be written by fsflush.
tune_t_fsflushr=10
    Controls how many seconds elapse between runs of the
    page flush daemon, fsflush.
lpg_alloc_prefer=1
    Indicates that extra effort should be taken to ensure
    that pages are created in the nearby lgroup (NUMA location).
The "webconsole" service was turned off using
svcadm disable webconsole
The system had 75 GB of swap space.
```

## Platform Notes

Memory is 8-way interleaved by filling all slots with the same capacity DIMMs.

This result is measured on a SPARC Enterprise M8000 server from Oracle. The SPARC Enterprise M8000 server from Oracle and from Fujitsu are electrically equivalent.

## General Notes

Environment variables set by runspec before the start of the run:  
OMP\_NUM\_THREADS = "128"  
SUNW\_MP\_PROCBIND = "127 126 125 124 123 122 121 120 119 118 117 116  
115 114 113 112 111 110 109 108 107 106 105 104 103 102 101 100 99  
98 97 96 95 94 93 92 91 90 89 88 87 86 85 84 83 82 81 80 79 78 77  
76 75 74 73 72 71 70 69 68 67 66 65 64 63 62 61 60 59 58 57 56 55  
54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33  
32 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11  
10 9 8 7 6 5 4 3 2 1 0"  
SUNW\_MP\_THR\_IDLE = "SPIN"

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation  
SPARC Enterprise M8000

SPECfp\_rate2006 = 786  
SPECfp\_rate\_base2006 = 711

CPU2006 license: 6  
Test sponsor: Oracle Corporation  
Tested by: Oracle Corporation

Test date: Nov-2010  
Hardware Availability: Dec-2010  
Software Availability: Sep-2010

## General Notes (Continued)

447.dealII (peak): "apache\_stdccx\_4\_2\_1" src.alt was used.  
447.dealII (base): "apache\_stdccx\_4\_2\_1" src.alt was used.

## Base Compiler Invocation

C benchmarks:  
cc

C++ benchmarks:  
CC

Fortran benchmarks:  
f90

Benchmarks using both Fortran and C:  
cc f90

## Base Optimization Flags

C benchmarks:  
-fast -fma=fused -xipo=2 -xpagesize=4M -xalias\_level=std  
-xprefetch\_auto\_type=indirect\_array\_access -xprefetch\_level=3  
-fsimple=1

C++ benchmarks:  
-fast -fma=fused -xipo=2 -xpagesize=4M -xalias\_level=compatible  
-xdepend -xprefetch=latx:0.5 -library=no%Cstd  
-I/export/home/apache/stdccx-4.2.1/include  
-I/export/home/apache/stdccx-4.2.1/build/include  
-L/export/home/apache/stdccx-4.2.1/build/lib  
-R/export/home/apache/stdccx-4.2.1/build/lib -lstd8d

Fortran benchmarks:  
-fast -fma=fused -xipo=2 -xpagesize=4M

Benchmarks using both Fortran and C:  
-fast(cc) -fast(f90) -fma=fused -xipo=2 -xpagesize=4M  
-xalias\_level=std -xprefetch\_auto\_type=indirect\_array\_access  
-xprefetch\_level=3 -fsimple=1

## Base Other Flags

C benchmarks:  
-xjobs=32 -V -#

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation  
SPARC Enterprise M8000

SPECfp\_rate2006 = 786  
SPECfp\_rate\_base2006 = 711

CPU2006 license: 6  
Test sponsor: Oracle Corporation  
Tested by: Oracle Corporation

Test date: Nov-2010  
Hardware Availability: Dec-2010  
Software Availability: Sep-2010

## Base Other Flags (Continued)

C++ benchmarks:  
-xjobs=32 -verbose=diags,version

Fortran benchmarks:  
-xjobs=32 -V -v

Benchmarks using both Fortran and C:  
-xjobs=32 -V -# -v

## Peak Compiler Invocation

C benchmarks:  
cc

C++ benchmarks:  
CC

Fortran benchmarks:  
f90

Benchmarks using both Fortran and C:  
cc f90

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: -fast -xpagesize=4M -fma=fused -xipo=2 -xprefetch\_level=3  
-xvector -xarch=generic -xautopar -xreduction

482.sphinx3: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
-fma=fused -xipo=2 -xinline= -xalias\_level=strong  
-xprefetch\_level=2 -lfast -l12amm

C++ benchmarks:

444.namd: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
-xalias\_level=any -xdepend -library=stlport4 -fma=fused  
-xipo=2 -xchip=generic -xunroll=2

447.dealIII: -fast -xpagesize=4M -xalias\_level=compatible -xdepend  
-library=no%Cstd -I/export/home/apache/stdcxx-4.2.1/include  
-I/export/home/apache/stdcxx-4.2.1/build/include -fma=fused

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation  
SPARC Enterprise M8000

SPECfp\_rate2006 = 786  
SPECfp\_rate\_base2006 = 711

CPU2006 license: 6  
Test sponsor: Oracle Corporation  
Tested by: Oracle Corporation

Test date: Nov-2010  
Hardware Availability: Dec-2010  
Software Availability: Sep-2010

## Peak Optimization Flags (Continued)

447.dealIII (continued):

```
-xipo=2 -xprefetch=latx:0.5
-L/export/home/apache/stdcxx-4.2.1/build/lib
-R/export/home/apache/stdcxx-4.2.1/build/lib -lstd8d
```

450.soplex: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
-xalias\_level=compatible -xdepend -library=stlport4  
-fma=fused -xipo=2 -xrestrict -xprefetch=no -ll2amm

453.povray: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
-xalias\_level=compatible -xdepend -fma=fused -xipo=2  
-xlinkopt=2 -xprefetch=no -xunroll=4 -xO4 -lfast

Fortran benchmarks:

410.bwaves: -fast -xpagesize=4M -fma=fused -xipo=2

416.gamess: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
-fma=fused -xipo=2 -xprefetch=no%auto -xO3

434.zeusmp: -fast -xpagesize=4M -fma=fused -xipo=2 -xprefetch\_level=1  
-ll2amm -xunroll=5

437.leslie3d: -fast -xpagesize=4M -M /usr/lib/ld/map.bssalign  
-xprefetch=no

459.GemsFDTD: basepeak = yes

465.tonto: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M  
-xipo=2 -xprefetch=no -lfast -ll2amm

Benchmarks using both Fortran and C:

435.gromacs: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)  
-xpagesize=4M -fma=fused -xtarget=generic -xinline=  
-fsimple=0 -xlinkopt -xvector -xdepend

436.cactusADM: -fast(cc) -fast(f90) -xpagesize=4M -fma=fused -xipo=2

454.calculix: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)  
-xpagesize=4M -fma=fused -xipo=2 -xvector  
-xprefetch=latx:3 -xalias\_level=std

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation  
SPARC Enterprise M8000

SPECfp\_rate2006 = 786

SPECfp\_rate\_base2006 = 711

CPU2006 license: 6

Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: Nov-2010

Hardware Availability: Dec-2010

Software Availability: Sep-2010

## Peak Optimization Flags (Continued)

```
481.wrf: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)
-xpagesize=4M -fma=fused -xipo=2 -xprefetch_level=3
-xprefetch_auto_type=indirect_array_access -l12amm
```

## Peak Other Flags

C benchmarks:

```
-xjobs=32 -V -#
```

C++ benchmarks:

```
-xjobs=32 -verbose=diags,version
```

Fortran benchmarks:

```
-xjobs=32 -V -v
```

Benchmarks using both Fortran and C:

```
-xjobs=32 -V -# -v
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.2-SPARC.20101221.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.2-SPARC.20101221.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 13:44:53 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 21 December 2010.