



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp[®]2006 = 32.5

ASUSTek M4A89GTD PRO/USB3 (Phenom II X6 1090T)

SPECfp_base2006 = 31.2

CPU2006 license: 13


Test date: Jul-2011

Test sponsor: Intel Corporation

Hardware Availability: Feb-2011

Tested by: Intel Corporation

Software Availability: Apr-2011



Hardware

CPU Name: AMD Phenom II X6 1090T
 CPU Characteristics: AMD Turbo CORE technology up to 3.6 GHz
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 6 cores, 1 chip, 6 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core

Continued on next page

Software

Operating System: Windows 7 Ultimate (64-bit)
 Compiler: Intel C++ Compiler XE for Intel 64
 Version 12.0.3.176 Build 20110309
 Intel Visual Fortran Compiler XE for Intel 64
 Version 12.0.3.176 Build 20110309
 Microsoft Visual Studio 2008 Professional SP1
 (for libraries)
 Auto Parallel: Yes
 File System: NTFS

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 32.5

ASUSTek M4A89GTD PRO/USB3 (Phenom II X6 1090T)

SPECfp_base2006 = 31.2

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2011

Hardware Availability: Feb-2011

Software Availability: Apr-2011

L3 Cache: 6 MB I+D on chip per chip
Other Cache: None
Memory: 8 GB (2 x 4 GB 2Rx4 PC3-10600U-9)
Disk Subsystem: 1 TB Seagate SATA, 7200 RPM
Other Hardware: None

System State: Default
Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	253	53.7	250	54.3	248	54.8	253	53.7	250	54.3	248	54.8
416.gamess	880	22.3	880	22.3	879	22.3	720	27.2	720	27.2	720	27.2
433.milc	342	26.8	344	26.7	286	32.1	342	26.8	344	26.7	286	32.1
434.zeusmp	165	55.1	165	55.2	162	56.3	165	55.1	165	55.2	162	56.3
435.gromacs	348	20.5	348	20.5	348	20.5	348	20.5	348	20.5	348	20.5
436.cactusADM	140	85.3	140	85.4	140	85.6	138	86.4	140	85.7	140	85.7
437.leslie3d	237	39.6	237	39.6	233	40.3	237	39.6	237	39.6	233	40.3
444.namd	425	18.9	425	18.9	424	18.9	420	19.1	420	19.1	420	19.1
447.dealII	502	22.8	504	22.7	500	22.9	502	22.8	504	22.7	500	22.9
450.soplex	556	15.0	557	15.0	527	15.8	556	15.0	557	15.0	527	15.8
453.povray	200	26.6	201	26.5	200	26.5	166	32.1	166	32.0	166	32.1
454.calculix	305	27.0	305	27.0	303	27.2	305	27.0	305	27.0	303	27.2
459.GemsFDTD	372	28.6	371	28.6	366	29.0	351	30.2	355	29.9	355	29.9
465.tonto	512	19.2	512	19.2	507	19.4	395	24.9	398	24.7	398	24.7
470.lbm	171	80.3	171	80.5	166	83.0	171	80.3	171	80.5	166	83.0
481.wrf	349	32.0	347	32.2	341	32.7	349	32.0	347	32.2	341	32.7
482.sphinx3	639	30.5	635	30.7	635	30.7	639	30.5	635	30.7	635	30.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter

Base Compiler Invocation

C benchmarks:
icl -Qvc9 -Qstd=c99

C++ benchmarks:
icl -Qvc9

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 32.5

ASUSTek M4A89GTD PRO/USB3 (Phenom II X6 1090T)

SPECfp_base2006 = 31.2

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Jul-2011
Hardware Availability: Feb-2011
Software Availability: Apr-2011

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc9 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64 -names:lowercase
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000

C++ benchmarks:
/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
-Qcxx-features -Qauto-ilp32 -Qprec-div- /F1000000000 shlw64M.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:
/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
/F1000000000

Benchmarks using both Fortran and C:
/arch:SSE3 -Qipo -O3 -Qparallel -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 32.5

ASUSTek M4A89GTD PRO/USB3 (Phenom II X6 1090T)

SPECfp_base2006 = 31.2

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Jul-2011
Hardware Availability: Feb-2011
Software Availability: Apr-2011

Peak Compiler Invocation

C benchmarks:
icl -Qvc9 -Qstd=c99
C++ benchmarks:
icl -Qvc9
Fortran benchmarks:
ifort
Benchmarks using both Fortran and C:
icl -Qvc9 -Qstd=c99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:
433.milc: basepeak = yes
470.lbm: basepeak = yes
482.sphinx3: basepeak = yes
C++ benchmarks:
444.namd: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
sh1W64M.lib -link /FORCE:MULTIPLE
447.dealII: basepeak = yes
450.soplex: basepeak = yes
453.povray: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias -Qauto-ilp32
/F1000000000 sh1W64M.lib -link /FORCE:MULTIPLE
Fortran benchmarks:
410.bwaves: basepeak = yes
416.gamess: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias
-Qscalar-rep- /F1000000000

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp2006 = 32.5

ASUSTek M4A89GTD PRO/USB3 (Phenom II X6 1090T)

SPECfp_base2006 = 31.2

CPU2006 license: 13

Test date: Jul-2011

Test sponsor: Intel Corporation

Hardware Availability: Feb-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

Peak Optimization Flags (Continued)

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Qopt-prefetch -Qparallel
/F1000000000

465.tonto: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc
/F1000000000

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qunroll2
-Qauto-ilp32 /F1000000000

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revC.html>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revC.xml>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 22:26:36 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 20 September 2011.