



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

SPECint®\_rate2006 = 208

Intel DH87MC Motherboard (Intel Core i7-4770)

SPECint\_rate\_base2006 = 200

CPU2006 license: 13


Test date: Jul-2014

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Oct-2013



### Hardware

CPU Name: Intel Core i7-4770  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.90 GHz  
 CPU MHz: 3400  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 8 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 8 GB (2 x 4 GB 2Rx4 PC3-12800U-11)  
 Disk Subsystem: 1 TB Seagate SATA HDD, 7200 RPM  
 Other Hardware: None

### Software

Operating System: Microsoft Windows 8.1 Pro  
 6.3.9600 N/A Build 9600  
 Compiler: C/C++: Version 14.0.1.139 of Intel C++ Studio XE for Windows;  
 Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1  
 Auto Parallel: No  
 File System: NTFS  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap Library Version 10.0 from <http://www.microquill.com/>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint\_rate2006 = 208

Intel DH87MC Motherboard (Intel Core i7-4770)

SPECint\_rate\_base2006 = 200

CPU2006 license: 13

Test date: Jul-2014

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	484	162	<u>479</u>	<u>163</u>	477	164	8	401	195	402	194	<u>402</u>	<u>194</u>
401.bzip2	8	732	106	739	105	<u>736</u>	<u>105</u>	8	719	107	723	107	<u>721</u>	<u>107</u>
403.gcc	8	439	147	434	148	<u>437</u>	<u>147</u>	8	428	150	<u>423</u>	<u>152</u>	414	155
429.mcf	8	402	182	<u>432</u>	<u>169</u>	440	166	8	402	182	<u>432</u>	<u>169</u>	440	166
445.gobmk	8	<u>556</u>	<u>151</u>	558	150	556	151	8	532	158	530	158	<u>531</u>	<u>158</u>
456.hammer	8	<u>239</u>	<u>313</u>	241	310	238	314	8	217	344	223	334	<u>217</u>	<u>343</u>
458.sjeng	8	610	158	613	158	<u>611</u>	<u>158</u>	8	606	160	<u>605</u>	<u>160</u>	604	160
462.libquantum	8	85.2	1950	85.5	1940	<u>85.3</u>	<u>1940</u>	8	82.3	2010	82.7	2000	<u>82.5</u>	<u>2010</u>
464.h264ref	8	694	255	692	256	<u>694</u>	<u>255</u>	8	694	255	692	256	<u>694</u>	<u>255</u>
471.omnetpp	8	<u>493</u>	<u>102</u>	494	102	490	102	8	461	109	<u>459</u>	<u>109</u>	458	110
473.astar	8	<u>497</u>	<u>113</u>	501	112	493	114	8	497	113	498	113	<u>497</u>	<u>113</u>
483.xalancbmk	8	251	220	<u>252</u>	<u>219</u>	253	218	8	251	220	<u>252</u>	<u>219</u>	253	218

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

To compile these binaries, the Intel Compiler 14.0 was set up to generate 32-bit binaries with the command:  
"ipsxe-comp-vars.bat ia32 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

## Submit Notes

Processes were bound to specific processors using the start command with the /affinity switch. The config file option 'submit' was used to generate the affinity mask for each process.

## Platform Notes

Sysinfo program C:\SPEC14.0\Docs\sysinfo  
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c  
running on Clt7C05070D8262 Sat Jul 26 01:33:08 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Trying 'systeminfo'  
OS Name : Microsoft Windows 8.1 Pro  
OS Version : 6.3.9600 N/A Build 9600  
System Manufacturer: INTEL\_  
System Model : DH87MC\_  
Processor(s) : 1 Processor(s) Installed.

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint\_rate2006 = 208

Intel DH87MC Motherboard (Intel Core i7-4770)

SPECint\_rate\_base2006 = 200

CPU2006 license: 13

Test date: Jul-2014

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

## Platform Notes (Continued)

[01]: Intel64 Family 6 Model 60 Stepping 3 GenuineIntel ~3401 Mhz  
BIOS Version : Intel Corp. MCH8710H.86A.0047.2013.0606.1508, 6/6/2013  
Total Physical Memory: 7,862 MB

Trying 'wmic cpu get /value'

DeviceID : CPU0  
L2CacheSize : 1024  
L3CacheSize : 8192  
MaxClockSpeed : 3401  
Name : Intel(R) Core(TM) i7-4770 CPU @ 3.40GHz  
NumberOfCores : 4  
NumberOfLogicalProcessors: 8

(End of data from sysinfo program)

## Component Notes

Tested systems can be used with Shin-G ATX case,  
PC Power and Cooling 1200W power supply

## General Notes

Binaries compiled on a system with 1x Intel Core i7-860 CPU  
+ 8GB memory using Windows 7 Enterprise 64-bit

## Base Compiler Invocation

C benchmarks:

icl -Qvc10 -Qstd=c99

C++ benchmarks:

icl -Qvc10

## Base Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32  
464.h264ref: -DWIN32 -DSPEC\_CPU\_NO\_INTTYPES  
483.xalancbmk: -Qoption,cpp,--no\_wchar\_t\_keyword

## Base Optimization Flags

C benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint\_rate2006 = 208

Intel DH87MC Motherboard (Intel Core i7-4770)

SPECint\_rate\_base2006 = 200

CPU2006 license: 13

Test date: Jul-2014

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

## Base Optimization Flags (Continued)

C++ benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features  
/F512000000 shlw32M.lib -link /FORCE:MULTIPLE

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icl -Qvc10 -Qstd=c99

456.hmmr: C:\Program Files (x86)\Intel\Composer XE 2013 SP1/bin/intel64/icl.exe

458.sjeng: C:\Program Files (x86)\Intel\Composer XE 2013 SP1/bin/intel64/icl.exe

462.libquantum: C:\Program Files (x86)\Intel\Composer XE 2013 SP1/bin/intel64/icl.exe  
-Qstd=c99

C++ benchmarks (except as noted below):

icl -Qvc10

473.astar: C:\Program Files (x86)\Intel\Composer XE 2013 SP1/bin/intel64/icl.exe

## Peak Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32  
456.hmmr: -DSPEC\_CPU\_P64  
458.sjeng: -DSPEC\_CPU\_P64  
462.libquantum: -DSPEC\_CPU\_P64  
464.h264ref: -DWIN32 -DSPEC\_CPU\_NO\_INTTYPES  
473.astar: -DSPEC\_CPU\_P64  
483.xalancbmk: -Qoption,cpp,--no\_wchar\_t\_keyword

## Peak Optimization Flags

C benchmarks:

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint\_rate2006 = 208

Intel DH87MC Motherboard (Intel Core i7-4770)

SPECint\_rate\_base2006 = 200

CPU2006 license: 13

Test date: Jul-2014

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

## Peak Optimization Flags (Continued)

400.perlbench: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
/F512000000 shlw32M.lib -link /FORCE:MULTIPLE

401.bzip2: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias  
/F512000000

403.gcc: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

429.mcf: basepeak = yes

445.gobmk: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O2 -Qprec-div- -Qansi-alias /F512000000

456.hmmer: -Qauto-ilp32 -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1)  
-Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch  
/F512000000

458.sjeng: -Qauto-ilp32 -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1)  
-Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4  
/F512000000

462.libquantum: -Qauto-ilp32 -QxCORE-AVX2 -Qipo -O3 -Qprec-div-  
-Qopt-prefetch /F512000000

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias  
-Qopt-ra-region-strategy=block /F512000000 shlw32M.lib  
-link /FORCE:MULTIPLE

473.astar: -Qauto-ilp32 -QxCORE-AVX2 -Qipo -O3 -Qprec-div-  
-Qopt-prefetch /F512000000 shlw64M.lib  
-link /FORCE:MULTIPLE

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint\_rate2006 = 208

Intel DH87MC Motherboard (Intel Core i7-4770)

SPECint\_rate\_base2006 = 200

CPU2006 license: 13

Test date: Jul-2014

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

## Peak Other Flags (Continued)

```
456.hmmr: -link -LIBPATH:C:\Program Files (x86)\Intel\Composer XE 2013 SP1/compiler/lib/intel64
          -link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 10.0/VC/lib/AMD64
          -link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 10.0/VC/lib
          -link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64
```

```
458.sjeng: -link -LIBPATH:C:\Program Files (x86)\Intel\Composer XE 2013 SP1/compiler/lib/intel64
           -link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 10.0/VC/lib/AMD64
           -link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 10.0/VC/lib
           -link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64
```

```
462.libquantum: -link -LIBPATH:C:\Program Files (x86)\Intel\Composer XE 2013 SP1/compiler/lib/intel64
                -link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 10.0/VC/lib/AMD64
                -link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 10.0/VC/lib
                -link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64
```

C++ benchmarks:

```
473.astar: -link -LIBPATH:C:\Program Files (x86)\Intel\Composer XE 2013 SP1/compiler/lib/intel64
           -link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 10.0/VC/lib/AMD64
           -link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 10.0/VC/lib
           -link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Tue Sep 9 10:50:26 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 12 August 2014.