



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 252

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECfp_rate_base2006 = 248

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2014

Hardware Availability: Sep-2013

Software Availability: Oct-2013



SPECfp_rate_base2006 = 248

SPECfp_rate2006 = 252

Hardware

CPU Name: Intel Core i7-4960X
 CPU Characteristics: Intel Turbo Boost Technology up to 4.00 GHz
 CPU MHz: 3600
 FPU: Integrated
 CPU(s) enabled: 6 cores, 1 chip, 6 cores/chip, 2 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Software

Operating System: Microsoft Windows 8.1 Pro 6.3.9600 N/A Build 9600
 Compiler: C/C++: Version 14.0.1.139 of Intel C++ Studio XE for Windows;
 Fortran: Version 14.0.1.139 of Intel Fortran Studio XE for Windows;
 Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
 Auto Parallel: No

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 252

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECfp_rate_base2006 = 248

CPU2006 license: 13

Test date: Sep-2014

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

L3 Cache: 15 MB I+D on chip per chip
 Other Cache: None
 Memory: 16 GB (4 x 4 GB 2Rx4 PC3-14900U-13)
 Disk Subsystem: 480 GB Intel SSD 530 Series
 Other Hardware: None

File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 10.0 from
<http://www.microquill.com/>

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	12	731	223	<u>730</u>	<u>223</u>	729	223	12	731	223	<u>730</u>	<u>223</u>	729	223
416.gamess	12	972	241	970	242	<u>971</u>	<u>242</u>	12	972	241	970	242	<u>971</u>	<u>242</u>
433.milc	12	<u>486</u>	<u>227</u>	486	227	487	227	12	<u>486</u>	<u>227</u>	486	227	487	227
434.zeusmp	12	359	304	<u>360</u>	<u>304</u>	362	301	12	359	304	<u>360</u>	<u>304</u>	362	301
435.gromacs	12	280	306	<u>279</u>	<u>307</u>	277	310	12	280	306	<u>279</u>	<u>307</u>	277	310
436.cactusADM	12	<u>566</u>	<u>253</u>	564	254	567	253	12	<u>566</u>	<u>253</u>	564	254	567	253
437.leslie3d	12	747	151	<u>747</u>	<u>151</u>	749	151	12	747	151	<u>747</u>	<u>151</u>	749	151
444.namd	12	498	193	<u>499</u>	<u>193</u>	501	192	12	<u>490</u>	<u>197</u>	490	197	487	198
447.dealII	12	371	370	361	380	<u>363</u>	<u>379</u>	12	371	370	361	380	<u>363</u>	<u>379</u>
450.soplex	12	<u>607</u>	<u>164</u>	619	162	607	164	6	297	169	<u>298</u>	<u>168</u>	299	167
453.povray	12	191	334	<u>193</u>	<u>331</u>	193	331	12	<u>162</u>	<u>394</u>	164	390	162	395
454.calculix	12	275	360	274	361	<u>275</u>	<u>360</u>	12	275	360	274	361	<u>275</u>	<u>360</u>
459.GemsFDTD	12	917	139	<u>917</u>	<u>139</u>	916	139	12	917	139	<u>917</u>	<u>139</u>	916	139
465.tonto	12	<u>473</u>	<u>250</u>	469	252	474	250	12	449	263	<u>448</u>	<u>264</u>	444	266
470.lbm	12	599	275	600	275	<u>600</u>	<u>275</u>	12	599	275	600	275	<u>600</u>	<u>275</u>
481.wrf	12	492	272	<u>492</u>	<u>272</u>	493	271	12	492	272	<u>492</u>	<u>272</u>	493	271
482.sphinx3	12	747	313	<u>756</u>	<u>310</u>	757	308	12	747	313	<u>756</u>	<u>310</u>	757	308

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 14.0 was set up to generate 64-bit binaries with the command:

"ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

Submit Notes

Processes were bound to specific processors using the start command with the /affinity switch. The config file option 'submit' was used to generate the affinity mask for each process.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 252

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECfp_rate_base2006 = 248

CPU2006 license: 13

Test date: Sep-2014

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

Platform Notes

```
Sysinfo program C:\SPEC14.0\Docs\sysinfo
$Rev: 6775 $ $Date::: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
running on Clt74D02B2C81C9 Sat Sep 13 05:00:52 2014
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name      : Microsoft Windows 8.1 Pro
OS Version   : 6.3.9600 N/A Build 9600
System Manufacturer: System manufacturer
System Model  : System Product Name
Processor(s) : 1 Processor(s) Installed.
[01]: Intel64 Family 6 Model 62 Stepping 4 GenuineIntel ~3601 Mhz
BIOS Version  : American Megatrends Inc. 4701, 5/7/2014
Total Physical Memory: 16,325 MB
```

```
Trying 'wmic cpu get /value'
DeviceID     : CPU0
L2CacheSize  : 256
L3CacheSize  : 15360
MaxClockSpeed: 3601
Name         : Intel(R) Core(TM) i7-4960X CPU @ 3.60GHz
NumberOfCores: 6
NumberOfLogicalProcessors: 12
```

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

Binaries compiled on a system with 1x Intel Core i7-860 CPU
+ 8GB memory using Windows 7 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 252

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECfp_rate_base2006 = 248

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2014

Hardware Availability: Sep-2013

Software Availability: Oct-2013

Base Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc10 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 /names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
-Qoption_cpp,--ms_incompat_treatment_of_commas_in_macros
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_NEED_INVHYP -DNEED_INVHYP
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER /names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F10000000000 -link /FORCE:MULTIPLE

C++ benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qcxx-features -Qauto-ilp32 /F10000000000 shlw64M.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
/F10000000000 -link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F10000000000 -link /FORCE:MULTIPLE



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 252

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECfp_rate_base2006 = 248

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2014

Hardware Availability: Sep-2013

Software Availability: Oct-2013

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc10 -Qstd=c99 ifort
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
433.milc: basepeak = yes
```

```
470.lbm: basepeak = yes
```

```
482.sphinx3: basepeak = yes
```

C++ benchmarks:

```
444.namd: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo  
          -O3 -Qprec-div- -Oa -Qauto-ilp32 /F10000000000 shlw64M.lib  
          -link /FORCE:MULTIPLE
```

```
447.dealII: basepeak = yes
```

```
450.soplex: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo  
          -O3 -Qauto-ilp32 /F10000000000 shlw64M.lib  
          -link /FORCE:MULTIPLE
```

```
453.povray: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo  
           -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32 /F10000000000  
           shlw64M.lib           -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
410.bwaves: basepeak = yes
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 252

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECfp_rate_base2006 = 248

CPU2006 license: 13

Test date: Sep-2014

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

Peak Optimization Flags (Continued)

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000
-link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Wed Nov 5 10:22:51 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 4 November 2014.