



# SPEC® CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS RS300-E10(P11C-C/4L) Server System  
(3.30 GHz, Intel Xeon E-2136)

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

CPU2017 License: 9016


Test Date: Feb-2019

Test Sponsor: ASUSTeK Computer Inc.

Hardware Availability: Sep-2018

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2018



Hardware		Software	
CPU Name:	Intel Xeon E-2136	OS:	SUSE Linux Enterprise Server 12 (x86_64) SP3
Max MHz.:	4500		Kernel 4.4.120-94.17-default
Nominal:	3300	Compiler:	C/C++: Version 19.0.1.144 of Intel C/C++ Compiler for Linux;
Enabled:	6 cores, 1 chip, 2 threads/core		Fortran: Version 19.0.1.144 of Intel Fortran Compiler for Linux
Orderable:	1 chip	Parallel:	No
Cache L1:	32 KB I + 32 KB D on chip per core	Firmware:	Version 0303 released Aug-2018
L2:	256 KB I+D on chip per core	File System:	btrfs
L3:	12 MB I+D on chip per chip	System State:	Run level 3 (multi-user)
Other:	None	Base Pointers:	64-bit
Memory:	64 GB (4 x 16 GB 2Rx8 PC4-2666V-E)	Peak Pointers:	64-bit
Storage:	1 x 500 GB SATA HDD, 7200RPM	Other:	None
Other:	None		



# SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS RS300-E10(P11C-C/4L) Server System  
(3.30 GHz, Intel Xeon E-2136)

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

CPU2017 License: 9016

Test Date: Feb-2019

Test Sponsor: ASUSTeK Computer Inc.

Hardware Availability: Sep-2018

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2018

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.bwaves_r	12	1746	68.9	<b>1746</b>	<b>68.9</b>	1747	68.9	12	1746	68.9	<b>1746</b>	<b>68.9</b>	1747	68.9
507.cactuBSSN_r	12	<b>410</b>	<b>37.0</b>	406	37.4	414	36.7	12	<b>410</b>	<b>37.0</b>	406	37.4	414	36.7
508.namd_r	12	310	36.8	314	36.3	<b>311</b>	<b>36.7</b>	12	310	36.7	309	37.0	<b>310</b>	<b>36.8</b>
510.parest_r	12	1825	17.2	1822	17.2	<b>1824</b>	<b>17.2</b>	12	<b>1822</b>	<b>17.2</b>	1816	17.3	1825	17.2
511.povray_r	12	487	57.5	<b>486</b>	<b>57.7</b>	485	57.8	12	419	66.9	<b>416</b>	<b>67.3</b>	414	67.7
519.lbm_r	12	761	16.6	762	16.6	<b>762</b>	<b>16.6</b>	12	763	16.6	<b>762</b>	<b>16.6</b>	762	16.6
521.wrf_r	12	833	32.3	<b>842</b>	<b>31.9</b>	847	31.7	12	<b>824</b>	<b>32.6</b>	824	32.6	823	32.7
526.blender_r	12	<b>360</b>	<b>50.8</b>	360	50.8	359	50.9	12	<b>360</b>	<b>50.8</b>	360	50.8	359	50.9
527.cam4_r	12	442	47.4	449	46.8	<b>443</b>	<b>47.3</b>	12	442	47.4	449	46.8	<b>443</b>	<b>47.3</b>
538.imagick_r	12	249	120	<b>249</b>	<b>120</b>	249	120	12	<b>249</b>	<b>120</b>	249	120	249	120
544.nab_r	12	253	79.9	247	81.7	<b>252</b>	<b>80.0</b>	12	253	79.9	247	81.7	<b>252</b>	<b>80.0</b>
549.fotonik3d_r	12	2048	22.8	<b>2048</b>	<b>22.8</b>	2048	22.8	12	<b>2048</b>	<b>22.8</b>	2048	22.8	2049	22.8
554.roms_r	12	1308	14.6	1300	14.7	<b>1306</b>	<b>14.6</b>	12	1289	14.8	<b>1289</b>	<b>14.8</b>	1289	14.8

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## General Notes

Environment variables set by runcpu before the start of the run:

```
LD_LIBRARY_PATH = "/spec2017_2019u1/lib/ia32:/spec2017_2019u1/lib/intel64:  
/spec2017_2019u1/je5.0.1-32:/spec2017_2019u1/je5.0.1-64"
```

Binaries compiled on a system with 1x Intel Core i7-6700K CPU + 32GB RAM memory using Redhat Enterprise Linux 7.5

Transparent Huge Pages enabled by default

Prior to runcpu invocation

Filesystem page cache synced and cleared with:

```
sync; echo 3> /proc/sys/vm/drop_caches
```

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

(Continued on next page)



# SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS RS300-E10(P11C-C/4L) Server System  
(3.30 GHz, Intel Xeon E-2136)

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

CPU2017 License: 9016

Test Date: Feb-2019

Test Sponsor: ASUSTeK Computer Inc.

Hardware Availability: Sep-2018

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2018

## General Notes (Continued)

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

## Platform Notes

BIOS Configuration:

VT-d = Disabled

AES = Disabled

Hardware Prefetcher = Disabled

Adjacent Cache Line Prefetch = Disabled

Race to Halt (RTH) = Disabled

Sysinfo program /spec2017\_2019u1/bin/sysinfo

Rev: r5974 of 2018-05-19 9bcde8f2999c33d61f64985e45859ea9  
running on linux-pmm5 Mon Feb 18 18:25:48 2019

SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see

<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : Intel(R) Xeon(R) E-2136 CPU @ 3.30GHz
  1 "physical id"s (chips)
  12 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following
excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
  cpu cores : 6
  siblings   : 12
  physical 0: cores 0 1 2 3 4 5
```

From lscpu:

```
Architecture:           x86_64
CPU op-mode(s):        32-bit, 64-bit
Byte Order:            Little Endian
CPU(s):                12
On-line CPU(s) list:  0-11
Thread(s) per core:   2
Core(s) per socket:   6
Socket(s):             1
NUMA node(s):          1
Vendor ID:             GenuineIntel
CPU family:            6
Model:                 158
Model name:            Intel(R) Xeon(R) E-2136 CPU @ 3.30GHz
Stepping:               10
CPU MHz:                4468.796
CPU max MHz:            4500.0000
```

(Continued on next page)



# SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS RS300-E10(P11C-C/4L) Server System  
(3.30 GHz, Intel Xeon E-2136)

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

CPU2017 License: 9016

Test Date: Feb-2019

Test Sponsor: ASUSTeK Computer Inc.

Hardware Availability: Sep-2018

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2018

## Platform Notes (Continued)

```
CPU min MHz: 800.0000
BogoMIPS: 6623.95
Virtualization: VT-x
L1d cache: 32K
L1i cache: 32K
L2 cache: 256K
L3 cache: 12288K
NUMA node0 CPU(s): 0-11
Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov
pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp
lm constant_tsc art arch_perfmon pebs bts rep_good nopl xtopology nonstop_tsc
aperfmperf eagerfpu pni pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg
fma cx16 xtpr pdcm pcid sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer xsave
avx f16c rdrand lahf_lm abm 3dnowprefetch ida arat epb invpcid_single pln pts dtherm
hwp hwp_notify hwp_act_window hwp_epp intel_pt rsb_ctxsw spec_ctrl stibp retpoline
kaiser tpr_shadow vnmi flexpriority ept vpid fsgsbase tsc_adjust bmi1 hle avx2 smep
bmi2 erms invpcid rtm mpx rdseed adx smap clflushopt xsaveopt xsavec xgetbv1
```

```
/proc/cpuinfo cache data
cache size : 12288 KB
```

From numactl --hardware    WARNING: a numactl 'node' might or might not correspond to a physical chip.

```
available: 1 nodes (0)
node 0 cpus: 0 1 2 3 4 5 6 7 8 9 10 11
node 0 size: 64313 MB
node 0 free: 62879 MB
node distances:
node 0
0: 10
```

From /proc/meminfo

```
MemTotal: 65857424 kB
HugePages_Total: 0
Hugepagesize: 2048 kB
```

From /etc/\*release\* /etc/\*version\*

```
SuSE-release:
SUSE Linux Enterprise Server 12 (x86_64)
VERSION = 12
PATCHLEVEL = 3
# This file is deprecated and will be removed in a future service pack or release.
# Please check /etc/os-release for details about this release.
os-release:
NAME="SLES"
VERSION="12-SP3"
VERSION_ID="12.3"
```

(Continued on next page)



# SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS RS300-E10(P11C-C/4L) Server System  
(3.30 GHz, Intel Xeon E-2136)

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

CPU2017 License: 9016

Test Date: Feb-2019

Test Sponsor: ASUSTeK Computer Inc.

Hardware Availability: Sep-2018

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2018

## Platform Notes (Continued)

```
PRETTY_NAME="SUSE Linux Enterprise Server 12 SP3"
ID="sles"
ANSI_COLOR="0;32"
CPE_NAME="cpe:/o:suse:sles:12:sp3"
```

uname -a:

```
Linux linux-pmm5 4.4.120-94.17-default #1 SMP Wed Mar 14 17:23:00 UTC 2018 (cf3a7bb)
x86_64 x86_64 x86_64 GNU/Linux
```

Kernel self-reported vulnerability status:

```
CVE-2017-5754 (Meltdown): Mitigation: PTI
CVE-2017-5753 (Spectre variant 1): Mitigation: __user pointer sanitization
CVE-2017-5715 (Spectre variant 2): Mitigation: IBRS+IBPB
```

run-level 3 Feb 18 17:59

```
SPEC is set to: /spec2017_2019u1
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda2        btrfs  445G  116G  329G  27%  /
```

Additional information from dmidecode follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS American Megatrends Inc. 0303 08/07/2018

Memory:

```
4x Samsung M391A2K43BB1-CTD 16 GB 2 rank 2667, configured at 2666
```

(End of data from sysinfo program)

## Compiler Version Notes

```
=====
CC 519.lbm_r(base) 538.imagick_r(base, peak) 544.nab_r(base, peak)
-----
```

```
icc (ICC) 19.0.1.144 20181018
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.
-----
```

```
=====
CC 519.lbm_r(peak)
-----
```

```
icc (ICC) 19.0.1.144 20181018
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.
-----
```

(Continued on next page)



# SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS RS300-E10(P11C-C/4L) Server System  
(3.30 GHz, Intel Xeon E-2136)

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

CPU2017 License: 9016

Test Date: Feb-2019

Test Sponsor: ASUSTeK Computer Inc.

Hardware Availability: Sep-2018

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2018

## Compiler Version Notes (Continued)

=====  
CXXC 508.namd\_r(base) 510.parest\_r(base, peak)

-----  
icpc (ICC) 19.0.1.144 20181018  
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====  
CXXC 508.namd\_r(peak)

-----  
icpc (ICC) 19.0.1.144 20181018  
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====  
CC 511.povray\_r(base) 526.blender\_r(base, peak)

-----  
icpc (ICC) 19.0.1.144 20181018  
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.  
icc (ICC) 19.0.1.144 20181018  
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====  
CC 511.povray\_r(peak)

-----  
icpc (ICC) 19.0.1.144 20181018  
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.  
icc (ICC) 19.0.1.144 20181018  
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====  
FC 507.cactusBSSN\_r(base, peak)

-----  
icpc (ICC) 19.0.1.144 20181018  
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.  
icc (ICC) 19.0.1.144 20181018  
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.  
ifort (IFORT) 19.0.1.144 20181018  
Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====  
FC 503.bwaves\_r(base, peak) 549.fotonik3d\_r(base, peak) 554.roms\_r(base)

(Continued on next page)



# SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS RS300-E10(P11C-C/4L) Server System  
(3.30 GHz, Intel Xeon E-2136)

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

CPU2017 License: 9016

Test Date: Feb-2019

Test Sponsor: ASUSTeK Computer Inc.

Hardware Availability: Sep-2018

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2018

## Compiler Version Notes (Continued)

ifort (IFORT) 19.0.1.144 20181018

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

FC 554.roms\_r(peak)

ifort (IFORT) 19.0.1.144 20181018

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

CC 521.wrf\_r(base) 527.cam4\_r(base, peak)

ifort (IFORT) 19.0.1.144 20181018

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

icc (ICC) 19.0.1.144 20181018

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

CC 521.wrf\_r(peak)

ifort (IFORT) 19.0.1.144 20181018

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

icc (ICC) 19.0.1.144 20181018

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

## Base Compiler Invocation

C benchmarks:

icc -m64 -std=c11

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

ifort -m64 icc -m64 -std=c11

Benchmarks using both C and C++:

icpc -m64 icc -m64 -std=c11

(Continued on next page)



# SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS RS300-E10(P11C-C/4L) Server System  
(3.30 GHz, Intel Xeon E-2136)

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

CPU2017 License: 9016

Test Date: Feb-2019

Test Sponsor: ASUSTeK Computer Inc.

Hardware Availability: Sep-2018

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2018

## Base Compiler Invocation (Continued)

Benchmarks using Fortran, C, and C++:

```
icpc -m64icc -m64 -std=c11 ifort -m64
```

## Base Portability Flags

```
503.bwaves_r: -DSPEC_LP64
507.cactusBSSN_r: -DSPEC_LP64
508.namd_r: -DSPEC_LP64
510.parest_r: -DSPEC_LP64
511.povray_r: -DSPEC_LP64
519.lbm_r: -DSPEC_LP64
521.wrf_r: -DSPEC_LP64 -DSPEC_CASE_FLAG -convert big_endian
526.blender_r: -DSPEC_LP64 -DSPEC_LINUX -funsigned-char
527.cam4_r: -DSPEC_LP64 -DSPEC_CASE_FLAG
538.imagick_r: -DSPEC_LP64
544.nab_r: -DSPEC_LP64
549.fotonik3d_r: -DSPEC_LP64
554.roms_r: -DSPEC_LP64
```

## Base Optimization Flags

C benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3
```

C++ benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3
```

Fortran benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3 -auto -nostandard-realloc-lhs
```

Benchmarks using both Fortran and C:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3 -auto -nostandard-realloc-lhs
```

Benchmarks using both C and C++:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3
```

(Continued on next page)



# SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS RS300-E10(P11C-C/4L) Server System  
(3.30 GHz, Intel Xeon E-2136)

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

CPU2017 License: 9016

Test Date: Feb-2019

Test Sponsor: ASUSTeK Computer Inc.

Hardware Availability: Sep-2018

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2018

## Base Optimization Flags (Continued)

Benchmarks using Fortran, C, and C++:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3 -auto -nostandard-realloc-lhs
```

## Peak Compiler Invocation

C benchmarks:

```
icc -m64 -std=c11
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
ifort -m64 icc -m64 -std=c11
```

Benchmarks using both C and C++:

```
icpc -m64 icc -m64 -std=c11
```

Benchmarks using Fortran, C, and C++:

```
icpc -m64 icc -m64 -std=c11 ifort -m64
```

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
519.lbm_r: -prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3  
-no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3
```

```
538.imagick_r: -xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch  
-ffinite-math-only -qopt-mem-layout-trans=3
```

(Continued on next page)



# SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS RS300-E10(P11C-C/4L) Server System  
(3.30 GHz, Intel Xeon E-2136)

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

CPU2017 License: 9016

Test Date: Feb-2019

Test Sponsor: ASUSTeK Computer Inc.

Hardware Availability: Sep-2018

Tested by: ASUSTeK Computer Inc.

Software Availability: Nov-2018

## Peak Optimization Flags (Continued)

544.nab\_r: basepeak = yes

C++ benchmarks:

508.namd\_r: -prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3  
-no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3

510.parest\_r: -xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch  
-ffinite-math-only -qopt-mem-layout-trans=3

Fortran benchmarks:

503.bwaves\_r: basepeak = yes

549.fotonik3d\_r: -xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch  
-ffinite-math-only -qopt-mem-layout-trans=3 -auto  
-nostandard-realloc-lhs

554.roms\_r: -prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3  
-no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3 -auto -nostandard-realloc-lhs

Benchmarks using both Fortran and C:

521.wrf\_r: -prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3  
-no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3 -auto -nostandard-realloc-lhs

527.cam4\_r: basepeak = yes

Benchmarks using both C and C++:

511.povray\_r: -prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3  
-no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3

526.blender\_r: basepeak = yes

Benchmarks using Fortran, C, and C++:

507.cactuBSSN\_r: basepeak = yes



# SPEC CPU2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

ASUS RS300-E10(P11C-C/4L) Server System  
(3.30 GHz, Intel Xeon E-2136)

**SPECrate2017\_fp\_base = 38.3**

**SPECrate2017\_fp\_peak = 38.9**

**CPU2017 License:** 9016

**Test Date:** Feb-2019

**Test Sponsor:** ASUSTeK Computer Inc.

**Hardware Availability:** Sep-2018

**Tested by:** ASUSTeK Computer Inc.

**Software Availability:** Nov-2018

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/ASUSTekPlatform-Settings-p11-V2.0-revA.html>  
<http://www.spec.org/cpu2017/flags/Intel-ic18.0-official-linux64.2017-12-21.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/ASUSTekPlatform-Settings-p11-V2.0-revA.xml>  
<http://www.spec.org/cpu2017/flags/Intel-ic18.0-official-linux64.2017-12-21.xml>

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU2017 v1.0.5 on 2019-02-18 05:25:47-0500.

Report generated on 2019-04-16 17:15:17 by CPU2017 PDF formatter v6067.

Originally published on 2019-04-16.