



SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International

SPECmpiM_peak2007 = Not Run

Intel Xeon Phi 7210, 1.30 GHz,
SMT off, Turbo off, MCDRAM Cache

SPECmpiM_base2007 = 7.33

MPI2007 license: 3440


Test sponsor: Indiana University

Tested by: Junjie Li

Test date: Sep-2016

Hardware Availability: Aug-2016

Software Availability: Apr-2016



Results Table

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
104.milc	64	206	7.60	<u>207</u>	<u>7.56</u>	207	7.55									
107.leslie3d	64	475	11.0	<u>478</u>	<u>10.9</u>	479	10.9									
113.GemsFDTD	64	595	10.6	<u>597</u>	<u>10.6</u>	599	10.5									
115.fds4	64	411	4.74	<u>411</u>	<u>4.75</u>	411	4.75									
121.pop2	64	<u>649</u>	<u>6.36</u>	652	6.33	642	6.43									
122.tachyon	64	909	3.08	908	3.08	<u>908</u>	<u>3.08</u>									
126.lammps	64	807	3.61	804	3.63	<u>804</u>	<u>3.62</u>									
127.wrf2	64	550	14.2	<u>551</u>	<u>14.1</u>	556	14.0									
128.GAPgeofem	64	<u>286</u>	<u>7.23</u>	285	7.25	286	7.22									
129.tera_tf	64	788	3.51	787	3.52	<u>788</u>	<u>3.51</u>									

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International

SPECmpiM_peak2007 = Not Run

Intel Xeon Phi 7210, 1.30 GHz,
SMT off, Turbo off, MCDRAM Cache

SPECmpiM_base2007 = 7.33

MPI2007 license: 3440

Test date: Sep-2016

Test sponsor: Indiana University

Hardware Availability: Aug-2016

Tested by: Junjie Li

Software Availability: Apr-2016

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	64	177	21.6	180	21.2	176	21.7							
132.zeusmp2	64	359	8.63	359	8.64	360	8.62							
137.lu	64	409	9.00	408	9.00	409	8.99							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System: Homogeneous
 Compute Node: KNL
 File Server Node: KNL
 Head Node: KNL
 Total Compute Nodes: 1
 Total Chips: 1
 Total Cores: 64
 Total Threads: 64
 Total Memory: 96 GB
 Base Ranks Run: 64
 Minimum Peak Ranks: --
 Maximum Peak Ranks: --

Software Summary

C Compiler: Intel C++ Composer XE 2016 for Linux, Version 16.0.3.210 Build 20160415
 C++ Compiler: Intel C++ Composer XE 2016 for Linux, Version 16.0.3.210 Build 20160415
 Fortran Compiler: Intel Fortran Composer XE 2016 for Linux, Version 16.0.3.210 Build 20160415
 Base Pointers: 64-bit
 Peak Pointers: 64-bit
 MPI Library: Intel MPI Library for Linux 5.1.3 Build 20160120
 Other MPI Info: None
 Pre-processors: No
 Other Software: None

Node Description: KNL

Hardware

Number of nodes: 1
 Uses of the node: head, compute, fileserver
 Vendor: Colfax International
 Model: None
 CPU Name: Intel Xeon Phi 7210
 CPU(s) orderable: 1 chip
 Chips enabled: 1
 Cores enabled: 64
 Cores per chip: 64
 Threads per core: 1
 CPU Characteristics: Intel Turbo Boost Technology off, Simultaneous Multithreading (SMT) off
 CPU MHz: 1300
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per two cores
 L3 Cache: None
 Other Cache: None
 Memory: 96 GB (6 x 16 GB 2Rx8 PC4-2400T-REB-11, ECC)
 Disk Subsystem: Intel S3510 SSD 800GB, SATA3
 Other Hardware: None
 Adapter: 0
 Number of Adapters: 0
 Slot Type: 0
 Data Rate: 0

Software

Adapter: 0
 Adapter Driver: 0
 Adapter Firmware: --
 Operating System: CentOS Linux Release 7.2.1511
 Local File System: Linux/ext4
 Shared File System: None
 System State: Multi-User
 Other Software: None

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International

SPECmpiM_peak2007 = Not Run

Intel Xeon Phi 7210, 1.30 GHz,
SMT off, Turbo off, MCDRAM Cache

SPECmpiM_base2007 = 7.33

MPI2007 license: 3440

Test date: Sep-2016

Test sponsor: Indiana University

Hardware Availability: Aug-2016

Tested by: Junjie Li

Software Availability: Apr-2016

Node Description: KNL

Ports Used: 0
Interconnect Type: 0

Submit Notes

The config file option 'submit' was used.

General Notes

130.socorro (base): "nullify_ptrs" src.alt was used.

MPI startup command:
mpirun command was used to start MPI jobs.

BIOS settings:
Intel Simultaneous Multithreading (SMT): off
Intel Turbo Boost Technology (Turbo) : off
Cluster Mode: quadrant
Memory Mode: cache

Base Compiler Invocation

C benchmarks:
mpiicc

C++ benchmarks:

126.lammps: mpiicpc

Fortran benchmarks:
mpiifort

Benchmarks using both Fortran and C:
mpiicc mpiifort

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG
126.lammps: -DMPICH_IGNORE_CXX_SEEK
127.wrf2: -DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX
130.socorro: -assume nostd_intent_in



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International

SPECmpiM_peak2007 = Not Run

Intel Xeon Phi 7210, 1.30 GHz,
SMT off, Turbo off, MCDRAM Cache

SPECmpiM_base2007 = 7.33

MPI2007 license: 3440

Test sponsor: Indiana University

Tested by: Junjie Li

Test date: Sep-2016

Hardware Availability: Aug-2016

Software Availability: Apr-2016

Base Optimization Flags

C benchmarks:

`-O3 -xMIC-AVX512 -no-prec-div -fp-model fast=2 -ipo -fma`

C++ benchmarks:

`126.lammps: -O3 -xMIC-AVX512 -no-prec-div -fp-model fast=2 -ipo -fma`

Fortran benchmarks:

`-O3 -xMIC-AVX512 -no-prec-div -fp-model fast=2 -ipo -fma`

Benchmarks using both Fortran and C:

`-O3 -xMIC-AVX512 -no-prec-div -fp-model fast=2 -ipo -fma`

The flags files that were used to format this result can be browsed at

http://www.spec.org/mpi2007/flags/EM64T_Intel_flags.html

<http://www.spec.org/mpi2007/flags/colfax-knl.html>

You can also download the XML flags sources by saving the following links:

http://www.spec.org/mpi2007/flags/EM64T_Intel_flags.xml

<http://www.spec.org/mpi2007/flags/colfax-knl.xml>

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.

Report generated on Wed Jan 11 12:44:11 2017 by SPEC MPI2007 PS/PDF formatter v1463.

Originally published on 11 January 2017.