



# OMPM2001 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System p5 550 (1900 MHz, 4 CPU)

SPECompMpeak2001 = 15392  
SPECompMbase2001 = 14878

SPEC license #HPG0005 | Tested by: IBM | Test site: Austin, TX | Test date: Sep-2005 | Hardware Avail: Oct-2005 | Software Avail: Oct-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
310.wupwise_m	6000	348	17264	348	17264
312.swim_m	6000	409	14665	402	14925
314.mgrid_m	7300	910	8025	910	8025
316.applu_m	4000	207	19290	187	21437
318.galgel_m	5100	198	25699	196	26067
320.earthquake_m	2600	199	13067	160	16234
324.apsi_m	3400	251	13559	251	13559
326.gafort_m	8700	548	15867	548	15867
328.fma3d_m	4600	590	7798	590	7798
330.art_m	6400	171	37347	171	37347
332.ammp_m	7000	730	9589	716	9776

### Hardware

CPU: POWER5+  
 CPU MHz: 1900  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (SMT on)  
 CPU(s) orderable: 2,4  
 Primary Cache: 64KBI+32KBD (on chip)  
 Secondary Cache: 1920KB unified (on chip)  
 L3 Cache: 36MB unified (off-chip)/DCM, 2 DCM/SUT  
 Other Cache: None  
 Memory: 16x2GB  
 Disk Subsystem: 2x36GB SCSI, 15K RPM  
 Other Hardware: None

### Software

OpenMP Threads: 8  
 Parallel: OpenMP  
 Operating System: AIX 5L V5.3  
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX  
 XL Fortran Enterprise Edition Version 10.1 for AIX  
 Other Software: ESSL 4.2.0.2  
 File System: AIX/JFS2  
 System State: Multi-user

## Notes/Tuning Information

Tested by IBM

### Portability Flags & Environment Variables

-qfixed used in: 310.wupwise\_m, 312.swim\_m, 314.mgrid\_m, 316.applu\_m, 324.apsi\_m  
 -qfixed=80 used in: 318.galgel\_m  
 -qsuffix=f=f90 used in: 318.galgel\_m, 326.gafort\_m, 328.fma3d\_m

### Base Flags

C: -qpdf1/pdf2  
 -q64 -O5 -blpdata -qalign=natural -qhot=arraypad -Q -qsmp=omp  
 EXTRA\_LDFLAGS=-q64  
 FORTRAN: -O5 -qipa=noobject -qmaxmem=-1 -qsmp=omp  
 EXTRA\_LDFLAGS=-bmaxdata:0x80000000

### Base & Peak User Environment:

OMP\_NUM\_THREADS=8  
 OMP\_DYNAMIC=FALSE  
 XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:SCHEDULE=STATIC:STARTPROC=0:STRIDE=1  
 MALLOCMULTIHEAP=1

### Peak Flags:

-qsmp=omp used in all cases  
 310.wupwise\_m: basepeak=1



# OMPM2001 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System p5 550 (1900 MHz, 4 CPU)

SPECompMpeak2001 = 15392  
SPECompMbase2001 = 14878

SPEC license #HPG0005 | Tested by: IBM | Test site: Austin, TX | Test date: Sep-2005 | Hardware Avail: Oct-2005 | Software Avail: Oct-2005

## Notes/Tuning Information (Continued)

```

312.swim_m:      -O5 -blpdata -lmass
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
314.mgrid_m:    basepeak=1
316.applu_m:    -O5 -blpdata -lmass
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
318.galgel_m:   -O3 -qhot -qarch=pwr4 -qtune=pwr4 -blpdata
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
320.quake_m:    -O5 -lesslsm
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
325.apsi_m:     basepeak=1
326.gafort_m:   basepeak=1
328.fma3d_m:    basepeak=1
330.art_m:      basepeak=1
332.ammp_m:     -qpdf1/pdf2
                  -O5 -blpdata -qfdpr -qalign=natural
                  fdpr -q -O3

```

### Alternate sources:

Add critical region around update of linked list in parallel loop.  
 Approved src.alt available as ompm-purdue1-20040324.tar.gz  
 Used for 330.art\_m, base and peak.

### Peak sources:

SPEC OMPL2001 source for 32bit systems modified for SPEC OMPM2001 used  
 with 312.swim\_m, 316.applu\_m, 320.quake\_m.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

DCM: Acronym for Acronym for "Dual-Chip Module" (one dual-core processor chip + one L3-cache chip)

ESSL: Engineering and Scientific Subroutine Library

SUT: Acronym for "System Under Test"

C: IBM XL C for AIX invoked as xlc\_r

Fortran 90: IBM XL Fortran for AIX invoked as xlf90\_r

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=800 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -r
export MEMORY_AFFINITY=MCM

```

The default number of executing threads is set as follows:

```
export OMP_NUM_THREADS=8
```

Use flags-description file IBM-20051013-AIX.txt.