



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 550 (2100 MHz, 4 CPU)

SPECompMpeak2001 = 19983
SPECompMbase2001 = 15355

SPEC license #HPG0005 | Tested by: IBM Austin | Test site: Austin, TX | Test date: Jul-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio
310.wupwise_m	6000	299	20049	299	20049
312.swim_m	6000	391	15358	309	19444
314.mgrid_m	7300	845	8643	330	22102
316.applu_m	4000	182	21931	147	27276
318.galgel_m	5100	184	27694	149	34261
320.earthquake_m	2600	194	13406	111	23431
324.apsi_m	3400	271	12559	217	15676
326.gafort_m	8700	507	17167	493	17651
328.fma3d_m	4600	707	6508	504	9129
330.art_m	6400	168	38184	151	42327
332.ammp_m	7000	726	9637	696	10058

Hardware

CPU: POWER5+
 CPU MHz: 2100
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (SMT on)
 CPU(s) orderable: 2,4 cores
 Primary Cache: 64 KB I + 32 KB D on chip per core
 Secondary Cache: 1920 KB I+D on chip per chip
 L3 Cache: 36 MB I+D off chip per chip, 2 chips per SUT
 Other Cache: None
 Memory: 32 GB (8x4 GB)
 Disk Subsystem: 2x73GB SCSI, 15K RPM
 Other Hardware: None

Software

OpenMP Threads: 8
 Parallel: OpenMP
 Operating System: AIX 5L V5.3
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX
 XL Fortran Enterprise Edition Version 10.1 for AIX
 Other Software: ESSL 4.2.0.4
 File System: AIX/JFS2
 System State: Multi-user

Notes/Tuning Information

Portability Flags & Environment Variables

-qfixed used in: 310.wupwise_m, 312.swim_m, 314.mgrid_m, 316.applu_m, 324.apsi_m
 -qfixed=80 used in: 318.galgel_m
 -qsuffix=f=f90 used in: 318.galgel_m, 326.gafort_m, 328.fma3d_m

Base Flags

C: -qpdf1/pdf2
 -q64 -O5 -blpdata -qalign=natural -qhot=arraypad -Q -qsmp=omp -qipa=threads=4
 FORTRAN: -O5 -qipa=noobject -qipa=partition=large -qmaxmem=-1 -qsmp=omp -qipa=threads=4
 -bmaxdata:0xD0000000/dsa

Base & Peak User Environment:

MEMORY_AFFINITY=MCM
 OMP_DYNAMIC=FALSE
 XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:SCHEDULE=STATIC:STARTPROC=0:STRIDE=1
 XLFRTIOPTS=intrinthds=1
 MALLOCMULTIHEAP=1
 OMP_NUM_THREADS=8

Peak Flags:

-qsmp=omp used in all cases
 310.wupwise_m: basepeak=1
 312.swim_m: -qpdf1/pdf2



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 550 (2100 MHz, 4 CPU)

SPECompMpeak2001 = 19983
SPECompMbase2001 = 15355

SPEC license #HPG0005 Tested by: IBM Austin Test site: Austin, TX Test date: Jul-2006 Hardware AvailAug-2006 Software AvailAug-2006

Notes/Tuning Information (Continued)

```

-q64 -bdatapsize:64K -O4
OMP_NUM_THREADS=4
314.mgrid_m: XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:SCHEDULE=STATIC:STARTPROC=0:STRIDE=2
-q64 -bdatapsize:64K -O5 -qsave
OMP_NUM_THREADS=4
316.applu_m: XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:SCHEDULE=STATIC:STARTPROC=0:STRIDE=2
-qpdf1/pdf2
318.galgel_m: -q64 -btextpsize:64K -bdatapsize:64K -bstackpsize:64K -O4 -qfdpr
-O5 -qarch=pwr3 -qtune=pwr3 -qessl
EXTRA_LDFLAGS=-bmaxdata:0x80000000 -btextpsize:64K -bdatapsize:64K -bstackpsize:64K -lmass -lesslsm
OMP_NUM_THREADS=4
320.earthquake_m: XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:SCHEDULE=STATIC:STARTPROC=0:STRIDE=2
-q64 -btextpsize:64K -bdatapsize:64K -bstackpsize:64K -O5 -qsave
OMP_NUM_THREADS=4
324.apsi_m: XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:SCHEDULE=STATIC:STARTPROC=0:STRIDE=2
-O5 -qalign=struct=natural -bdatapsize:64K -bstackpsize:64K
-bmaxdata:0x80000000
326.gafort_m: -btextpsize:64K -bdatapsize:64K -bstackpsize:64K -lmass -O5 -qhot=arraypad -Q
EXTRA_LDFLAGS=-bmaxdata:0x80000000
328.fma3d_m: -btextpsize:64K -bdatapsize:64K -bstackpsize:64K -lhm -O5 -qhot=arraypad -qipa=noobject -qmaxmem=-1
EXTRA_LDFLAGS=-bmaxdata:0x80000000
330.art_m: -qpdf1/pdf2
-O5 -qfdpr -q64 -btextpsize:64K -bdatapsize:64K -lesslsm
fdpr -q -O3
EXTRA_CFLAGS= -DINTS_PER_CACHELINE=32 -DDBLS_PER_CACHELINE=16
332.ammp_m: -qpdf1/pdf2
-O5 -qipa=partition=large -qmaxmem=-1 -q64 -btextpsize:64K -bdatapsize:64K

```

Peak sources:

SPEC OMPL2001 source for 32bit systems modified for SPEC OMPM2001 used with 312.swim_m, 316.applu_m, 320.earthquake_m, 326.gafort_m.

The installed OS level is AIX 5L for POWER version 5.3 with the 5300-04 Recommended Maintenance package. The installed C/C++ compiler is XL C/C++ Enterprise Edition Version 8.0 for AIX with the August 2006 PTF. The installed Fortran copiler is XL Fortran Enterprise Edition Version 10.1 with the August 2006 AIX PTF.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

SUT: Acronym for "System Under Test"

ESSL: Engineering and Scientific Subroutine Library

PTF: IBM identifier for "Program Fix Level"

C: IBM XL C for AIX invoked as xlc_r

Fortran 90: IBM XL Fortran for AIX invoked as xlf_r

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=1024 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
bosboot -aD
shutdown -rF
export MEMORY_AFFINITY=MCM

```