

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers: PRIMEPOWER 850
Zeus Technology Ltd.: Zeus WebServer 4.0r1

SPECweb99 = 8500

Test Date: Jan-2002
Tester: Fujitsu Siemens

Hardware Avail: Feb-2002 OS Avail: Oct-2001 HTTP Software Avail: Oct-2001 Sup. Software Avail: NA SPEC license #: 22

Hardware

Vendor: Fujitsu Siemens Computers
Model: PRIMEPOWER 850
Processor: 675 MHz SPARC64
Processors: 8 cores, 8 chips, 1 core/chip
Primary Cache: 128 KBI+128 KBD on chip
Secondary Cache: 8MB(I+D) off chip
Other Cache: None
Memory: 64GB
Disk Subsystem: 21 x 17GB
Disk Controllers: Dual Channel Ultra SCSI
Other Hardware: 2 x PCI Box D:GP70M-BG60

Software

Operating System: Solaris 8 7/01
File System: VxFS (for non-root disks)
Other Software: NCA

HTTP Software

Vendor: Zeus Technology Ltd.
HTTP Software: Zeus WebServer 4.0r1
API: Zeus PEPP 0.6 ISAPI
Server Cache: SNCA
Log Mode: SNCA Binary CLF

Test Sponsor

Test Date: Jan-2002
Tested By: Fujitsu Siemens
SPEC License: 22

Network

of Controllers: 12
Network Controllers: Gigabit Ethernet X1141A-U
of Nets: 12
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/sec
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 63
Model: PRIMEPOWER 100N
Processor: 500 MHz UltraSPARC IIe
of Processors: 1
Memory: 256 MB
Network Controller: Fast Ethernet X1093A-U
Operating System: Solaris 8 7/01
Compiler: GNU cc 2.8

Notes/Tuning Information

Operating System Notes

Operating System settings in /etc/system

__General settings:

__set sq_max_size=0 (unlimited messages allowed on each IP queue)
__set segmap_percent=90 (def: 12, Size of kernel segmap segment)
__set rlim_fd_max=350000 (def: 1024 file descriptors)
__set rlim_fd_cur=350000 (def: max (256,rlim_fd_max))
__set autoup=60 (def: 30, seconds before dirty page buffers are sync'd)
__set maxphys=65536 (def: 131072, maximal size of physical I/O requests)
__set maxpgio=128 (def: 40, maximal number of page I/O requests that can be queued)

__Specific modules:

__set ge:ge_intr_mode=1 (bypass normal communication layer queuing)
__set ge:ge_nos_tmds = 8192 (def: 512, transmit descriptors)
__set ge:ge_tx_fastdvma_min = 95 (def: 1024, min packet size to use fast dvm a interface)
__set ge:ge_tx_bcopy_max = 96 (def: 256, Maximum packet size to use copy of buffer)
__set ge:ge_nos_txdvma = 8192 (def: 512, transmit descriptors)
__set pcipsy:pci_stream_buf_enable = 0 (disable PCI cache streaming)
__set nca:nca_conn_req_max_q=10240 (def: 256, Max number of TCP conns to listen to)
__set nca:nca_conn_req_max_q0=10240 (def: 1024, Max number of 3 way handshakes open)
__set nca:nca_ppmax=5200000 (def: 25% of physical memory, Max amount of physical memory (in pages) used by NCA)
__set nca:nca_vpmax=5200000 (def: 25% of virtual memory, Max amount of virtual memory (in pages) used by NCA)
__set nca:nca_conn_hash_size=393209 (def: 383, hash table size)
__set nca:ncaurishash_sz = 289669 (def: 8053, URI hash table size)
__set nca:nca vnodehash_sz = 289669 (def: 12281, Controls the vnode hash table size in the NCA module)

__Settings in NCA control files (/etc/nca)

__nca.if: ge0 ge1 ge2 ge3 ge4 ge5 ge6 ge7 ge8 ge9 ge10 ge11
__ncalogd.conf: status=enabled, logd_file_size=1000000000
__ncalogd.conf: logd/path_name=/logs/log0 ... /logs/log12

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Operating System Notes (Continued)

— Disk usage:

- __1 disk (internal): OS, Paging, Zeus, and /export/home
- __3 disks (striped): /logs
- __1 disk: /web99 except file_set (r/w portion of docroot, e.g. post.log)
- __15 disks (striped): /web99/file_set (r/o portion of docroot)
- __File Systems, Striping with Veritas Volume Manager

Tuning disclosure: Fujitsu-Siemens-20011126.txt

HTTP Software Notes

Zeus 4.0r1 global.cfg performance parameters

__Refer to: <http://support.zeus.com/faq/entries/tuning.html>

—
tuning!modules!stats!enabled no
tuning!accelerator!nca!enabled yes
tuning!num_children 12
tuning!num_cgid 12
tuning!cache_files 419999
tuning!cache_max_bytes 0
tuning!cache_small_file 4096
tuning!cache_large_file 1048576
tuning!cache_stat_expire 31536000
tuning!cache_flush_interval 31536000
tuning!cache_cooling_time 0
tuning!sendfile yes
tuning!listen_queue_size 8192
tuning!so_wbuff_size 1048576
tuning!so_rbuff_size 0
tuning!modules!cgi!cleansize 0
tuning!cbuff_size 65536
tuning!sendfile_minsize 1
tuning!sendfile_maxsize 1048576
tuning!sendfile_reservefd 299993
tuning!bind_any no
tuning!softservers no

— Other Zeus 4.0r1 global.cfg parameters

—
gid root
uid root
controlport 9080
controlallow 127.0.0.1

— Other Zeus 4.0r1 virtual_server performance parameters (%zeushome%/web-4.0r1/runningsites/websvr)

__bindaddr gsvr0,gsvr1,gsvr2,gsvr3,gsvr4,gsvr5,gsvr6,gsvr7,gsvr8,gsvr9,gsvr10,gsvr11
__modules!cgi!enabled yes
__modules!isapi!enabled yes
__modules!log!enabled no

HTTP API Notes

Zeus PEPP 0.6 ISAPI used for dynamic content

Archived in Fujitsu-Siemens-20011126-API.tar.gz

Compiled with Sun Forte 6.2

./Configure --sendfile=no --locking=semop

Compilation options:

CCFLAGS="-I\$INCLUDES -xarch=v8plus -Kpic -dalign -fns -fsimple=2 -ftrap=%none -xlibmil -xO5 -DCHECK_CONFIG"

LDFLAGS="-z muldefs -G"

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Network Notes

1 x Cisco Catalyst 6500 Series Switch

Client Notes

Network Tuning parameters (/usr/bin/ndd):

ndd -set /dev/tcp tcp_smallest_anon_port 2048 (def: 32768)

ndd -set /dev/tcp tcp_time_wait_interval 60000 (def: 240000 ms = 4 mins.)

Client code generated with "Configure OPTIMIZE="-O2 -Wall"; export OPTIMIZE

and with ./configure --enable-posix-threads --enable-gethostbyname_r --enable-pthread_scope_system
--enable-rlimit --enable-nanosleep --enable-safe-usleep=no

ge0: 4 clients, using NIC 33 MHz

ge1: 5 clients, using NIC 66 MHz

ge2: 4 clients, using NIC 33 MHz

ge3: 5 clients, using NIC 66 MHz

ge4: 6 clients, using NIC 66 MHz

ge5: 6 clients, using NIC 66 MHz

ge6: 6 clients, using NIC 66 MHz

ge7: 7 clients, using NIC 66 MHz

ge8: 5 clients, using NIC 66 MHz

ge9: 5 clients, using NIC 66 MHz

ge10: 5 clients, using NIC 66 MHz

ge11: 5 clients, using NIC 66 MHz

Used Prime Client system separate from the 63 Load Generators

__PRIMEPOWER 400, 4 x 500MHz SPARC64, Solaris 8 7/01