

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

IBM: IBM eServer pSeries 660 Model 6H0 (750MHz)
Zeus Technology Ltd.: Zeus 4.0

SPECweb99 = 5480

Test Date: Mar-2002
Tester: IBM

Hardware Avail: Apr-2002 OS Avail: Apr-2002 HTTP Software Avail: Oct-2001 Sup. Software Avail: Apr-2002 SPEC license #: 11

Hardware

Vendor: IBM
Model: IBM eServer pSeries 660 Model 6H0 (750MHz)
Processor: 750MHz RS64 IV
Processors: 4 cores, 4 chips, 1 core/chip
Primary Cache: 128KBI+128KBD on chip
Secondary Cache: 8MB(I+D) off chip
Other Cache: None
Memory: 32 GB
Disk Subsystem: 1x9.1GB 16Bit SCSI Disk
12x18.2 SSA Disk(fast-write enabled)
Disk Controllers: Wide/Ultra-2 SCSI I/O Controller,
IBM SSA 160 SerialDisk Adapter
Other Hardware: 5 x Alteon ACESwitch 180

Software

Operating System: AIX 5L V5.1(64bit)
File System: JFS
Other Software: None

HTTP Software

Vendor: Zeus Technology Ltd.
HTTP Software: Zeus 4.0
API: ISAPI
Server Cache: FRCA (Fast Response Cache Accelerator)
Log Mode: Binary CLF for Zeus, CLF for FRCA

Test Sponsor

Test Date: Mar-2002
Tested By: IBM
SPEC License: 11

Network

of Controllers: 8
Network Controllers: 8 IBM Gigabit Ethernet-SX PCI Adapter
of Nets: 8
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/sec
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 24
Model: IBM eServer pSeries 640 Model B80
Processor: 375 MHz POWER3-II
of Processors: 4
Memory: 4096MB
Network Controller: 1 IBM Gigabit Ethernet-SX PCI Adapter
Operating System: AIX 4.3.3
Compiler: IBM VAC 5.0.1

Notes/Tuning Information

SUT Notes

APAR IY28102 was applied to AIX 5L V5.1
bosdebug -H (enables secondary thread on the processor)
bindintcpu [interrupt level] [cpu] (Interrupt affinity - bind 8 Ethernet interrupts to 4 cpu's(2 interrupt to 1 cpu))
maxpgahead=32(the maximum number of pages to be read ahead,default=8)
minperm=5%(the point below which the page-stealer will steal file of computational pages,default=20%)
maxperm=95%(the point above which the page stealing algorithm steals only file page,default=80%)
4 different logs for 4 zeus instances (1 log per zeus instance) for dynamic requests
frca-log.N (once the frca-log.N reaches 1GB, a new frca-log.N+1 is generated) for static requests
Disk layout: 1 disk for OS, 1 disk for webserver, 10 disks striped for file_set, 1 disks for web logfile)
Set Gigabit Ethernet driver attribute copy_bytes=256 (copy packet into contiguous buffer on transmit if this many or less bytes, default=2048)
Set Gigabit Ethernet driver attribute large_send=yes (turn on large_send capability of TCPIP, default=no)
fractrl pconintr 100 (frca set to allow 100% cpu time on interrupt, default=90)
fractrl revaltimeout 100000 (set frca revalidation timeout to 100,000 seconds, default=300 seconds)
no(network option) tuning:
no -o tcp_sendspace=131072(default socket send buffer size, default=16384)
no -o tcp_recvspace=65536(default socket receive buffer size, default=16384)
no -o send_file duration=100000(cached send_file expiration time, default=300)
no -o somaxconn=10240(max listen backlog, default=1024)
no -o nbc_max_cache=409600(max file size for network buffer cache, default=131072)
no -o nbc_pseg=800000(max file entries in private segment,default=0)
no -o tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds, default=1)
no -o tcp_newreno=0 (disables the modification to TCP's Fast Recovery algorithm as described in RFC 2582, default=1)

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTP API Notes

Zeus PEPP-06 SPECweb99 toolkit used for dynamic content
Compiled with IBM VAC 5.0.1
post.log in /weblog directory instead of doc_root
./Configure --sendfile=no --locking=semop

Client Notes

APAR IY17356 was applied to AIX 4.3.3
no (network option) tuning:
no -o delayack=3(delay ack for connection setup and shutdown,default=0)
no -o delayackports={80}(delay ack ports,default={ })
no -o tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds,default=1)
no -o tcp_sendspace=65536(default socket send buffer size, default=16384)
no -o tcp_recvspace=65536(default socket receive buffer size, default=16384)

Other Notes

Starts 4 unique instances of Zeus sharing a common docroot
The 2 child iprocesses of each Zeus instance bind to two unique IP address
Zeus 4.0 global.cfg (one per instance)
tuning!bind_any no
tuning!cache_files 100003
tuning!cache_large_file 9216
tuning!cache_small_file 4096
tuning!cache_stat_expire 180000
tuning!cache_flush_interval 180000
tuning!cache_max_bytes 0
tuning!num_children 2
tuning!keepalive yes
tuning!keepalive_timeout 1000
tuning!keepalive_max -1
tuning!listen_queue_size 9216
tuning!cbuff_size 1048576
tuning!multiple_accept yes
tuning!sendfile yes
tuning!sendfile_maxsize 1048576
tuning!sendfile_minsize 4096
tuning!sendfile_reservefd 31991
tuning!so_nagle_off no
tuning!so_rbuff_size 32768
tuning!softservers no
tuning!unique_bind yes
tuning!use_poll no
tuning!cache_cooling_time 0
tuning!modules!cgi!cleansize 0
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
tuning!accelerator!frca!enabled yes
tuning!accelerator!frca!log!enabled yes
tuning!accelerator!frca!log!filename /weblog/log/frca-log
tuning!accelerator!frca!log!format CLF
tuning!accelerator!frca!maxsize 1048576
tuning!accelerator!frca!minsize 100
Zeus_Site_Configuration (one per instance):
modules!cgi!enabled yes
modules!isapi!enabled yes
bindaddr ip_addr1, ip_addr2
Tuning Disclosure: IBM-20011019.txt
Dynamic API: IBM-20011019_2-API.tar.gz