

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices: Tyan S2882/Opteron 252
Zeus: Zeus V4.2r4 (64-bit)

SPECweb99_SSL =2800

Test Date: Jan-2005
Tester: Advanced Micro Devices

Hardware Avail: Feb-2005 OS Avail: Aug-2004 HTTPS Software Avail: Nov-2003 Sup. Software Avail: Nov-2003 SPEC license #: 49

Hardware

Vendor: Advanced Micro Devices
Model: Tyan S2882/Opteron 252
Processor: AMD Opteron 252, 2.6 GHz
Processors: 2 cores, 2 chips, 1 core/chip
Primary Cache: 64KBI + 64KBD
Secondary Cache: 1MB on chip
Other Cache: none
Memory: 16GB DDR400
Disk Subsystem: 3 73GB 15KRPM SCSI drives
Disk Controllers: LSI 22320-R U320 SCSI adapter
Other Hardware: 2 Dell PowerConnect 5224 gigabit switches

Software

Operating System: SuSE Linux Enterprise Server 9
File System: ext2
Other Software: none

HTTPS Software

Vendor: Zeus
HTTPS Software: Zeus V4.2r4 (64-bit)
API: Zeus PEPP 0.9pre1 ISAPI for Dynamic content
Server Cache: None
Log Mode: binary Common Log Format

Test Sponsor

Test Date: Jan-2005
Tested By: Advanced Micro Devices
SPEC License: 49

Network

of Controllers: 2
Network Controllers: Intel Pro/1000 MT Server Adapter
of Nets: 2
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 10
Model: RackSaver RS-1100
Processor: AMD Athlon MP 2800+
of Processors: 2
Memory: 1024MB
Network Controller: Intel Pro/1000 MT Server Adapter
Operating System: Windows 2000 Professional
Compiler: Microsoft Visual C++ 6.0

Notes/Tuning Information

SUT Notes

- 1 U320 15K 73GB SCSI disk for OS
- 1 U320 15K 73GB SCSI disk for log
- 1 U320 15K 73GB SCSI disk for html/fileset

Operating System Notes

- One NIC irq bound per CPU
- irqbalancer disabled for the duration of the test
- ulimit -n 72720, sets number of open files, default 1024
- Each NIC's TX queue length set to 40000 via ifconfig, default 1000
- log, & html/fileset partitions mounted with 'noatime, nodiratime', no inode access time updating

Tuning Parameters:

- net.ipv4.ip_forward = 0
- net.ipv4.conf.all.rp_filter = 1, enables source route verification, default 0
- net.ipv4.tcp_timestamps = 0, turns TCP timestamp support off, default 1
- net.ipv4.tcp_max_tw_buckets = 2000000, sets TCP time-wait buckets pool size, default 180000
- net.core.rmem_max = 10000000, maximum receive socket buffer size, default 65535
- net.core.rmem_default = 10000000, default receive socket buffer size, default 65535
- net.core.wmem_max = 10000000, maximum send socket buffer size, default 65535
- net.core.wmem_default = 10000000, default send socket buffer size, default 65535
- net.core.optmem_max = 10000000, default 10240
- net.ipv4.tcp_rmem = 3000000 3000000 30000000, maximum TCP read-buffer space allocatable, default 4096 87380 174760
- net.ipv4.tcp_wmem = 30000000 30000000 30000000, maximum TCP write-buffer space allocatable, default 4096 16384 131072
- net.ipv4.tcp_mem = 30000000 30000000 30000000, maximum TCP buffer space, default 31744 32256 32768
- fs.file-max = 291879, maximum number of open files, default 1024

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTPS Software Notes

Zeus Configuration:
tuning!bind_any no
tuning!unique_bind yes
tuning!cache_cooling_time 0
tuning!cache_files 282011
tuning!cache_flush_interval 180000
tuning!cache_small_file 90000
tuning!cache_large_file 1048576
tuning!cache_max_bytes 12884901888
tuning!cache_stat_expire 180000
tuning!cbuff_size 65536
tuning!clientfirst_optimise yes
tuning!keepalive yes
tuning!keepalive_max -1
tuning!keepalive_timeout 3600
tuning!listen_queue_size 8192
tuning!maxaccept 2048
tuning!modules!cgi!cleansize 0
tuning!sendfile no
tuning!sendfile_maxsize 0
tuning!sendfile_minsize 0
tuning!so_wbuff_size 1048576
tuning!softservers no
tuning!ssl_diskcache no
tuning!ssl_sessioncache_size 6037
tuning!ssl_cbuff_size 32840
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no

HTTP API Notes

Zeus PEPP configured with command: ./Configure --ssl=yes
Zeus PEPP compiled with default gcc (v3.3.3)

Client Notes

Client tuning via registry:
Tcip\Parameters\MaxUserPort=0xffff, sets maximum open ports to 65534
Tcip\Parameters\TcpTimedWaitDelay=60, sets TIME_WAIT parameter to 60 seconds (non-RFC 1122), default 240
Tcip\Parameters\MaxFreeTcbs=100000, sets maximum number of TIME_WAIT tcbs to 100,000
Tcip\Parameters\TcpWindowSize=65535, sets TCP receive window size, default 8192

Other Notes

Dynamic API: HP-20020724-API.tgz
Server kernel config: Default SLES9 (2.6.5-7.97-smp)
SUT requires a Tyan S2882 motherboard, an eATX 3 hard drive
capable case with a minimum 420 watt power supply.