SPEC ACCEL™ OMP Result

Copyright 2015-2023 Standard Performance Evaluation Corporation

Supermicro
Intel Xeon Platinum 8490H
SuperServer SYS-221H-TN24R

SPECaccel_omp_peak = 13.9

SPECaccel_omp_base = 13.9

ACCEL license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Jan-2023
Hardware Availability: Jan-2023
Software Availability: Aug-2022



Hardware

CPU Name:	Intel Xeon Platinum 8490H
CPU Characteristics:	Intel Turbo Boost Technology up to 3.50 GHz
CPU MHz:	1900
CPU MHz Maximum:	3500
FPU:	Integrated
CPU(s) enabled:	120 cores, 2 chips, 60 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 48 KB D on chip per core
Secondary Cache:	2 MB I+D on chip per core
L3 Cache:	115200 KB I+D on chip per chip
Other Cache:	None

Continued on next page

Accelerator

Accel Model Name:	Intel Xeon Platinum 8490H
Accel Vendor:	Intel
Accel Name:	Intel Xeon Platinum 8490H
Type of Accel:	CPU
Accel Connection:	N/A
Does Accel Use ECC:	Yes
Accel Description:	2 x Intel Xeon Platinum 8490H
Accel Driver:	N/A

SPEC ACCEL OMP Result

Copyright 2015-2023 Standard Performance Evaluation Corporation

Supermicro
Intel Xeon Platinum 8490H
SuperServer SYS-221H-TN24R

SPECaccel_omp_peak = 13.9

SPECaccel_omp_base = 13.9

ACCEL license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Jan-2023
Hardware Availability: Jan-2023
Software Availability: Aug-2022

Hardware (Continued)

Memory: 1 TB (16 x 64 GB 2Rx4 PC5-4800B-R)
Disk Subsystem: 1 x 1.92 TB M.2 NVME SSD
Other Hardware: None

Software

Operating System: Ubuntu 22.04.1 LTS 5.15.0-58-generic
Compiler: C/C++/Fortran: Version 2023.0.0.20221208 of Intel oneAPI DPC++/C++
File System: ext4
System State: Run-level 5 (multi-user)
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.postencil	11.5	9.47	**11.8**	**9.24**	17.0	6.42	11.5	9.47	**11.8**	**9.24**	17.0	6.42
504.polbm	**11.3**	**10.8**	13.6	8.96	11.2	10.8	**11.3**	**10.8**	13.6	8.96	11.2	10.8
514.pomriq	36.6	17.0	36.8	16.9	**36.7**	**16.9**	36.6	17.0	36.8	16.9	**36.7**	**16.9**
550.pmd	**9.44**	**25.5**	9.36	25.8	9.45	25.5	**9.44**	**25.5**	9.36	25.8	9.45	25.5
551.ppalm	**125**	**4.35**	126	4.33	124	4.40	**125**	**4.35**	126	4.33	124	4.40
552.pep	**21.6**	**10.7**	21.6	10.7	21.6	10.7	**21.6**	**10.7**	21.6	10.7	21.6	10.7
553.pclvrleaf	61.0	18.8	61.9	18.5	**61.3**	**18.7**	61.0	18.8	61.9	18.5	**61.3**	**18.7**
554.pcg	26.2	12.7	**26.1**	**12.8**	26.1	12.8	26.2	12.7	**26.1**	**12.8**	26.1	12.8
555.pseismic	**52.1**	**5.41**	53.1	5.31	49.9	5.65	**52.1**	**5.41**	53.1	5.31	49.9	5.65
556.psp	21.0	38.9	20.3	40.4	**20.5**	**40.0**	21.0	38.9	20.3	40.4	**20.5**	**40.0**
557.pcsp	21.9	39.3	22.2	38.8	**22.1**	**38.9**	21.9	39.3	22.2	38.8	**22.1**	**38.9**
559.pmniGhost	79.5	4.99	**71.0**	**5.59**	69.0	5.76	79.5	4.99	**71.0**	**5.59**	69.0	5.76
560.pilbdc	**59.4**	**11.0**	59.8	10.9	58.6	11.1	**59.4**	**11.0**	59.8	10.9	58.6	11.1
563.pswim	15.3	10.4	**13.5**	**11.8**	10.0	15.9	15.3	10.4	**13.5**	**11.8**	10.0	15.9
570.pbt	16.5	47.3	**16.3**	**47.9**	16.3	48.0	16.5	47.3	**16.3**	**47.9**	16.3	48.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program /home/accel/Docs/sysinfo
$Rev: 6965 $ $Date:: 2015-04-21 #$ c05a7f14b1b1765e3fe1df68447e8a35
running on lab Sat Jan 21 03:36:06 2023

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
```

Continued on next page

Platform Notes (Continued)

```
  http://www.spec.org/accel/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) Platinum 8490H
      2 "physical id"s (chips)
      240 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 60
      siblings  : 120
      physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
      22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46
      47 48 49 50 51 52 53 54 55 56 57 58 59
      physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
      22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46
      47 48 49 50 51 52 53 54 55 56 57 58 59
   cache size : 115200 KB

From /proc/meminfo
   MemTotal:       1056094820 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

/usr/bin/lsb_release -d
   Ubuntu 22.04.1 LTS

From /etc/*release* /etc/*version*
   debian_version: bookworm/sid
   os-release:
      PRETTY_NAME="Ubuntu 22.04.1 LTS"
      NAME="Ubuntu"
      VERSION_ID="22.04"
      VERSION="22.04.1 LTS (Jammy Jellyfish)"
      VERSION_CODENAME=jammy
      ID=ubuntu
      ID_LIKE=debian
      HOME_URL="https://www.ubuntu.com/"

uname -a:
   Linux lab 5.15.0-58-generic #64-Ubuntu SMP Thu Jan 5 11:43:13 UTC 2023 x86_64
   x86_64 x86_64 GNU/Linux

run-level 5 Jan 21 02:22

SPEC is set to: /home/accel
   Filesystem     Type  Size  Used Avail Use% Mounted on
   /dev/nvme0n1p2 ext4  1.8T   27G  1.7T   2% /
Additional information from dmidecode:
```

Continued on next page

Platform Notes (Continued)

```
     Warning: Use caution when you interpret this section. The 'dmidecode' program
     reads system data which is "intended to allow hardware to be accurately
     determined", but the intent may not be met, as there are frequent changes to
     hardware, firmware, and the "DMTF SMBIOS" standard.

    BIOS Supermicro X13DEM 1.1 01/20/2023
    Memory:
     16x Micron Technology MTC40F2046S1RC48BA1 64 GB 2 rank 4800 MT/s


  (End of data from sysinfo program)
```

General Notes

```
------------------------------------------------------------------------
BIOS Setting:
    Power Performance Tuning = BIOS Controls EPB
    ENERGY_PERF_BIAS_CFG Mode = Extreme Performance
    LLC Dead Line Alloc = Auto
    NUMA = Disabled
    UMA-Based Clustering = Disable (All2All)
------------------------------------------------------------------------
Spectre and Meltdown
    NA: The test sponsor attests, as of date of publication, the CVE-2017-5754 (Meltdown)
    is mitigated in the system as tested and documented.
    Yes: The test sponsor attests, as of date of publication, the CVE-2017-5753 (Spectre variant 1)
    is mitigated in the system as tested and documented.
    Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
    is mitigated in the system as tested and documented.
------------------------------------------------------------------------
OS tunning:
    Stack size set to unlimited using "ulimit -s unlimited"
```

Base Compiler Invocation

C benchmarks:
icc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

503.postencil: -DSPEC_USE_INNER_SIMD
504.polbm: -DSPEC_USE_INNER_SIMD
514.pomriq: -DSPEC_USE_INNER_SIMD
550.pmd: -DSPEC_USE_INNER_SIMD
551.ppalm: -DSPEC_USE_INNER_SIMD
552.pep: -DSPEC_USE_INNER_SIMD
553.pclvrleaf: -DSPEC_USE_INNER_SIMD
554.pcg: -DSPEC_USE_INNER_SIMD
555.pseismic: -DSPEC_USE_INNER_SIMD
556.psp: -DSPEC_USE_INNER_SIMD
557.pcsp: -DSPEC_USE_INNER_SIMD
559.pmniGhost: -DSPEC_USE_INNER_SIMD -nofor-main
560.pilbdc: -DSPEC_USE_INNER_SIMD
563.pswim: -DSPEC_USE_INNER_SIMD
570.pbt: -DSPEC_USE_INNER_SIMD

Base Optimization Flags

C benchmarks:
-qopenmp -qopenmp-offload=host -Ofast -xCORE-AVX512
-qopt-zmm-usage=high -fimf-precision=low:exp,sin,cos,sincos,log
-no-prec-sqrt -qopt-multiple-gather-scatter-by-shuffles

Fortran benchmarks:
-qopenmp -qopenmp-offload=host -Ofast -xCORE-AVX512
-qopt-zmm-usage=high -fimf-precision=low:exp,sin,cos,sincos,log
-no-prec-sqrt -qopt-multiple-gather-scatter-by-shuffles

Benchmarks using both Fortran and C:
-qopenmp -qopenmp-offload=host -Ofast -xCORE-AVX512
-qopt-zmm-usage=high -fimf-precision=low:exp,sin,cos,sincos,log
-no-prec-sqrt -qopt-multiple-gather-scatter-by-shuffles

Peak Optimization Flags

C benchmarks:

503.postencil: basepeak = yes

504.polbm: basepeak = yes

514.pomriq: basepeak = yes

Continued on next page

Peak Optimization Flags (Continued)

552.pep: basepeak = yes

554.pcg: basepeak = yes

557.pcsp: basepeak = yes

570.pbt: basepeak = yes

Fortran benchmarks:

550.pmd: basepeak = yes

551.ppalm: basepeak = yes

555.pseismic: basepeak = yes

556.psp: basepeak = yes

560.pilbdc: basepeak = yes

563.pswim: basepeak = yes

Benchmarks using both Fortran and C:

553.pclvrleaf: basepeak = yes

559.pmniGhost: basepeak = yes

The flags files that were used to format this result can be browsed at
https://www.spec.org/accel/flags/Intel-compiler.20230208.html
https://www.spec.org/accel/flags/Supermicro-Platform-Settings-V1.2-SPR-revC.html

You can also download the XML flags sources by saving the following links:
https://www.spec.org/accel/flags/Intel-compiler.20230208.xml
https://www.spec.org/accel/flags/Supermicro-Platform-Settings-V1.2-SPR-revC.xml

SPEC ACCEL is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC ACCEL v1.4.
Report generated on Wed Feb 8 14:38:17 2023 by SPEC ACCEL PS/PDF formatter v1290.
Originally published on 8 February 2023.