



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**SGI**  
**SGI Origin 300 32X 500MHz R14k**

**SPECint\_rate2000 = 136**  
**SPECint\_rate\_base2000 = 129**

SPEC license #: 4 Tested by: SGI Test date: Dec-2001 Hardware Avail: Dec-2001 Software Avail: Nov-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	32	520	100.0	32	500	104
175.vpr	32	370	140	32	355	147
176.gcc	32	312	131	32	310	132
181.mcf	32	643	104	32	643	104
186.crafty	32	250	149	32	247	150
197.parser	32	573	117	32	548	122
252.eon	32	299	161	32	281	172
253.perlbnk	32	605	110	32	604	111
254.gap	32	566	72.1	32	430	95.0
255.vortex	32	356	198	32	313	225
256.bzip2	32	441	126	32	410	136
300.twolf	32	580	192	32	580	192

### Hardware

CPU: R14000  
 CPU MHz: 500  
 FPU: Integrated  
 CPU(s) enabled: 32 cores, 32 chips, 1 core/chip  
 CPU(s) orderable: 2-32  
 Parallel: No  
 Primary Cache: 32KBI + 32KBD on chip  
 Secondary Cache: 2MB(I+D) off chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 32 GB  
 Disk Subsystem: 1 x 18 GB SCSI, 2 x 18 GB SCSI (striped)  
 Other Hardware: None

### Software

Operating System: IRIX 6.5.14f  
 Compiler: MIPSpro 7.3.1.2m C, C++  
 SCSL 1.4 Math Library  
 File System: xfs  
 System State: Single-user

## Notes/Tuning Information

Baseline optimization flags (C and C++ use same flags):

PASS1 : -Ofast=ip27 -IPA:use\_intrinsic -fb\_create /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)  
 PASS2 : -Ofast=ip27 -IPA:use\_intrinsic -fb\_opt /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

Portability Flags:

176.gcc: -Dalloca=\_\_builtin\_alloca -DMIPS -DHOST\_WORDS\_BIG\_ENDIAN  
 186.crafty: -DSGI  
 252.eon: -lm  
 253.perlbnk: -DSPEC\_CPU2000\_SGI -DI\_FCNTL  
 254.gap: -DSYS\_IS\_USG -DSYS\_HAS\_TIME\_PROTO -DSYS\_HAS\_SIGNAL\_PROTO -DSYS\_HAS\_IOCTL\_PROTO  
 -DSYS\_HAS\_ANSI -DSYS\_HAS\_CALLOC\_PROTO  
 300.twolf: -DHAVE\_SIGNED\_CHAR

Peak optimization flags:

note: all occurrences of (FEEDBACK) below means compiled with a two-step process:

PASS1 = -fb\_create /tmp/SPEC2000/FBDIR\_peak/\$(EXEBASE)  
 PASS2 = -fb\_opt /tmp/SPEC2000/FBDIR\_peak/\$(EXEBASE)  
 164.gzip: -Ofast=ip27 -IPA:space=500:plimit=500 -lmalloc (FEEDBACK)  
 175.vpr: -Ofast=ip27 -IPA:space=300:plimit=10000:callee\_limit=5000:linear=on  
 . -LNO:prefetch Ahead=2 -INLINE:aggressive=on  
 . -OPT:Olimit=0:alias=disjoint:alias=restrict -CG:ld\_latency=10 -lmalloc (FEEDBACK)  
 181.mcf: basepeak=yes



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Origin 300 32X 500MHz R14k

SPECint\_rate2000 = 136

SPECint\_rate\_base2000 = 129

SPEC license #: 4 Tested by: SGI Test date: Dec-2001 Hardware Avail: Dec-2001 Software Avail: Nov-2001

## Notes/Tuning Information (Continued)

```

176.gcc: -Ofast=ip27 -CG:ld_latency=4 (FEEDBACK)
186.crafty: -Ofast=ip27 -LNO:prefetch=0 -OPT:goto=off -CG:ld_latency=4 -lmalloc (FEEDBACK)
197.parser: -Ofast=ip27 -IPA:min_hot=14 (FEEDBACK)
252.eon: -Ofast=ip27 -LNO:prefetch=0 -LANG:exceptions=off -CG:ld_latency=4 -lmalloc -lm
      (FEEDBACK)
253.perlbnk: -Ofast=ip27 -IPA:use_intrinsic -Wl,-x (FEEDBACK)
254.gap: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4
      -OPT:alias=restrict:alias=disjoint -IPA:min_hot=7 -CG:ld_latency=8 -lmalloc (FEEDBACK)
255.vortex: -Ofast=ip27 -IPA:use_intrinsic
      -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4 -LNO:opt=0 -CG:ld_latency=5
      -IPA:min_hot=14 -TENV:X=4 -IPA:space=500:plimit=3600 -OPT:goto=off (FEEDBACK)
256.bzip2: -Ofast=ip27 -IPA:min_hot=5:space=500:plimit=2900 -INLINE:aggressive=on (FEEDBACK)
300.twolf: basepeak=yes

```

The following O/S parameters were set:

```

setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
system -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
system -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
system -i ; r12k_bdiag = 0x4000000 ;
limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):

```

rm -rf /tmp/SPEC2000 ; mkdir /tmp/SPEC2000 ; cd /tmp/SPEC2000 ; mkdir FBDIR_base ; mkdir FBDIR_peak
The first disk mentioned in the Disk Subsystem is the system disk. A striped
XFS filesystem was created using the rest of the disks and the benchmark was
run on this.

```

Jobs are submitted using dplace. Contents of the placement file submit.pf:

```

memories 1 in topology physical near $NODE
threads 1
run thread 0 on memory 0 using cpu $CPU

```