



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer DS25 68/1000

SPECint_rate2000 = 7.86
SPECint_rate_base2000 = 7.17

SPEC license #: 2 | Tested by: HP | Test date: Jul-2002 | Hardware Avail: Aug-2002 | Software Avail: Oct-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	1	303	5.35	1	299	5.43
175.vpr	1	262	6.19	1	260	6.24
176.gcc	1	157	8.11	1	141	9.02
181.mcf	1	319	6.55	1	242	8.63
186.crafty	1	123	9.46	1	123	9.46
197.parser	1	431	4.84	1	345	6.05
252.eon	1	164	9.20	1	159	9.46
253.perlbnk	1	311	6.70	1	287	7.27
254.gap	1	239	5.35	1	204	6.27
255.vortex	1	223	9.88	1	199	11.1
256.bzip2	1	225	7.72	1	212	8.23
300.twolf	1	380	9.15	1	372	9.37

Hardware

CPU: Alpha 21264C
 CPU MHz: 1000
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1 to 2
 Parallel: No
 Primary Cache: 64KB(I)+64KB(D) on chip
 Secondary Cache: 8MB off chip per CPU
 L3 Cache: None
 Other Cache: None
 Memory: 8GB
 Disk Subsystem: 18.2GB SCSI
 Other Hardware: None

Software

Operating System: Tru64 UNIX V5.1A
 Compiler: Compaq C V6.4-215-46B70
 Program Analysis Tools V2.0
 Spike V5.2 DTK (1.471.2.2 46B5P)
 Compaq C++ V6.3-010-46B2F
 File System: AdvFS
 System State: Multi-user

Notes/Tuning Information

Baseline C : cc -arch ev6 -fast +CFB ONESTEP
 C++: cxx -arch ev6 -O2 ONESTEP

Peak:

All but 252.eon: cc -g3 -arch ev6 ONESTEP
 164.zip: -fast -O4 -non_shared +CFB
 175.vpr: -fast -O4 -assume restricted_pointers +CFB
 176.gcc: -fast -O4 -xtaso_short -all -ldensemalloc -none
 +CFB +IFB
 181.mcf: -fast -xtaso_short +CFB +IFB +PFB
 186.crafty: same as base
 197.parser: -fast -O4 -xtaso_short -non_shared +CFB
 252.eon: cxx -arch ev6 -O2 -all -ldensemalloc -none
 253.perlbnk: -fast -non_shared +CFB +IFB
 254.gap: -fast -O4 -non_shared +CFB +IFB +PFB
 255.vortex: -fast -non_shared +CFB +IFB
 256.bzip2: -fast -O4 -non_shared +CFB
 300.twolf: -fast -O4 -assume restricted_pointers -all
 -ldensemalloc -none +CFB +IFB



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer DS25 68/1000

SPECint_rate2000 = 7.86
SPECint_rate_base2000 = 7.17

SPEC license #: 2 | Tested by: HP | Test date: Jul-2002 | Hardware Avail: Aug-2002 | Software Avail: Oct-2001

Notes/Tuning Information (Continued)

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```
mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*
```

and these flags are added to the first and second compiles:

```
PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use -prof_dir /tmp/pp
```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```
mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}
```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```
rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}
```

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DALPHA
perlbnk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP64
gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL_PROTO
-DSPEC_CPU2000_LP64

Spike, and the Program Analysis Tools, are part of the Developers' Tool Kit Supplement, <http://www.tru64unix.compaq.com/dtk/>. The features used in this SPEC submission will be available at the web site as a production release in October, 2001. The C compiler for this SPEC submission has been available at the same location, as a production release, since August, 2001.