



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER1500 (2160MHz)

SPECfp_rate2000 = 300
SPECfp_rate_base2000 = 260

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: May-2005 | Hardware Avail: Jun-2005 | Software Avail: Sep-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	16	139	213	16	129	230
171.swim	16	419	137	16	119	481
172.mgrid	16	263	127	16	257	130
173.applu	16	168	232	16	143	273
177.mesa	16	123	212	16	102	255
178.galgel	16	64.6	834	16	54.7	984
179.art	16	12.6	3840	16	12.1	3980
183.quake	16	101	238	16	100	241
187.facerec	16	104	338	16	103	341
188.amp	16	165	247	16	154	265
189.lucas	16	282	132	16	270	137
191.fma3d	16	295	132	16	295	132
200.sixtrack	16	155	132	16	155	132
301.apsi	16	204	237	16	204	237

Hardware

CPU: SPARC64 V
CPU MHz: 2160
FPU: Integrated
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
CPU(s) orderable: 1 to 32 (increments of 1)
Parallel: None
Primary Cache: 128KBI + 128KBD on chip
Secondary Cache: 4MB(I+D) on chip
L3 Cache: None
Other Cache: None
Memory: 65536MB
Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)
Other Hardware: None

Software

Operating System: Solaris 9 9/04
Compiler: (Fortran)
Fujitsu Parallelnavi 2.3 with patch 913221-03
Sun Studio 9
Sun Performance Library 9
(C)
Sun Studio 9
File System: ufs
System State: multi user

Notes/Tuning Information

```
FDO: (for Parallelnavi 2.3)
fdo_pre0=rm -rf `pwd`/*.f.d
PASS1=-Kpg
PASS2=-Kpu
FDO: (for Sun Studio 9)
fdo_pre0=rm -rf ./feedback.profile ./SunWS_cache
PASS1=-xprofile=collect:./feedback
PASS2=-xprofile=use:./feedback
```

```
Floating point base flags:
(using Fortran compiler of Sun Studio 9)
-fast -xtarget=ultra3cu -xipo=2 ONESTEP=yes FDO
(using C compiler of Sun Studio 9)
-fast -xtarget=ultra3 -xipo=2 ONESTEP=yes FDO
```

Floating point peak flags:



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER1500 (2160MHz)

SPECfp_rate2000 = 300

SPECfp_rate_base2000 = 260

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: May-2005 | Hardware Avail: Jun-2005 | Software Avail: Sep-2004

Notes/Tuning Information (Continued)

(using Fortran compiler of Parallelnavi 2.3)

168.wupwise: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=1 -Qoption iropt -Ainline:inc=800:cp=1 ONESTEP=yes FDO
172.mgrid: -Kfast_GP2=3,GREG_SYSTEM -O3 -Kcommonpad=180,alignc=64
189.lucas: -Kfast_GP2=3 -O5 -x dir=./ -Kunroll=2 FDO

(using Fortran compiler of Sun Studio 9)

171.swim: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xpad=common:1700 -Qoption iropt -Ainline:cs=700,-Atile:skewp:b10
173.applu: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -Qoption cg -Qlp=1-av=192-t=4-fa=1-fl=0
-Qoption iropt -Aujam:inner=g ONESTEP=yes FDO
178.galgel: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
RM_SOURCES=lapak.f90 ONESTEP=yes FDO
187.facerec: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xprefetch=latx:1.6 ONESTEP=yes FDO
191.fma3d: basepeak=yes
200.sixtrack: basepeak=yes
301.apsi: basepeak=yes

(using C compiler of Sun Studio 9)

177.mesa: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xchip=ultra2 -xalias_level=strong -xipo=2 -xrestrict
ONESTEP=yes FDO
179.art: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 ONESTEP=yes FDO
183.earthquake: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=strong -W2,-whole -Wc,-Qms_pipe-pref,
-Qlp=1-av=512-t=6-fa=1-fl=1 ONESTEP=yes FDO
188.ammp: -fast -xalias_level=std -xipo=2 ONESTEP=yes FDO

Portability:

178.galgel: -e -fixed

System Tunables:

(for /etc/system)

```
set consistent_coloring=1
set tune_t_fsflushr=86400
set autoup=86400
set memscrub_period_sec=172800
```

Shell Environments:

```
Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1
```

Processes were bound to CPUs using "submit=pbind".

Extended Interleave Mode enabled.

4 CPUs each on 4 system boards. Unused CPUs have physically removed.

Sun Studio 9, posted at URL <http://www.sun.com/software/products/studio/previous/9/index.xml> was used for this submission.



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER1500 (2160MHz)

SPECfp_rate2000 =	300
SPECfp_rate_base2000 =	260

SPEC license #:	19	Tested by:	Fujitsu Limited	Test date:	May-2005	Hardware Avail:	Jun-2005	Software Avail:	Sep-2004
-----------------	----	------------	-----------------	------------	----------	-----------------	----------	-----------------	----------

Notes/Tuning Information (Continued)