



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL45p (AMD Opteron (TM) 854)

SPECfp\_rate2000 = 52.4  
SPECfp\_rate\_base2000 = 47.5

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	56.9	65.2	2	48.6	76.3
171.swim	2	117	61.4	2	114	63.1
172.mgrid	2	96.1	43.5	2	91.2	45.8
173.applu	2	96.1	50.7	2	82.9	58.8
177.mesa	2	63.9	50.8	2	60.4	53.8
178.galgel	2	86.0	78.3	2	77.0	87.4
179.art	2	96.9	62.2	2	68.6	87.9
183.quake	2	76.2	39.6	2	68.7	43.9
187.facerec	2	71.1	62.0	2	68.5	64.3
188.amp	2	138	37.1	2	127	40.0
189.lucas	2	92.4	50.2	2	92.9	49.9
191.fma3d	2	127	38.4	2	119	41.0
200.sixtrack	2	135	18.9	2	114	22.3
301.apsi	2	147	41.1	2	143	42.2

### Hardware

CPU: AMD Opteron (TM) 854  
CPU MHz: 2800  
FPU: Integrated  
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip  
CPU(s) orderable: 1, 2, 4  
Parallel: No  
Primary Cache: 64KBI + 64KBD on chip  
Secondary Cache: 1024KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x2048MB PC3200 CL3.0  
Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI  
Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 9 (x86\_64) SP 1  
SuSE kernel 2.6.5-7.139-smp  
Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.1  
AMD Core Math Library 2.5.1  
File System: Linux/ext2  
System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on
Portability flags:
 178.galgel: -fixedform
Peak tuning:
 168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
              -OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3
              -IPA:linear=on:plimit=50000:callee_limit=5000 -INLINE:aggressive=on
 171.swim:
 172.mgrid: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 -m3dnow
              -Ofast -CG:gcm=off -OPT:IEEE_a=3:unroll_size=200
              -LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2 -WOPT:mem_opnds=on:aggstr=0
 173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
              -LNO:fusion=2:fission=2:full_unroll_size=10000
 177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
              -WOPT:mem_opnds=on +FDO
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL45p (AMD Opteron (TM) 854)

SPECfp\_rate2000 = 52.4  
SPECfp\_rate\_base2000 = 47.5

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

## Notes/Tuning Information (Continued)

```

178.galgel: -Ofast -OPT:fast_complex=on RM_SOURCES=lapak.f90 +ACML
179.art: -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32 +FDO
183.quake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec: -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0 -LNO:fusion=2
            -IPA:plimit=1500 +FDO
188.ammp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
            -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
            -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:Olimit=6000:early_intrinsics=on -fno-math-errno
            -CG:load_exe=1 +FDO
301.apsi: -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```

BIOS Configuration Notes  
Node Interleaving is Disabled

Other Configuration Notes  
Taskset utility used to bind process to CPU(s)