



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**  
CELSIUS V830, Opteron (TM) 256, Linux 64-bit

SPECfp\_rate2000 = **54.9**  
SPECfp\_rate\_base2000 = **50.2**

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Mar-2006 | Software Avail: Dec-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	54.1	68.6	2	48.2	76.9
171.swim	2	123	58.7	2	118	61.1
172.mgrid	2	94.6	44.2	2	87.8	47.6
173.applu	2	93.0	52.4	2	81.6	59.7
177.mesa	2	57.6	56.4	2	53.6	60.6
178.galgel	2	81.9	82.1	2	73.5	91.5
179.art	2	93.7	64.4	2	67.5	89.4
183.equake	2	74.3	40.6	2	67.0	45.0
187.facerec	2	66.8	66.0	2	67.9	64.9
188.amp	2	127	40.2	2	119	43.0
189.lucas	2	92.4	50.2	2	82.6	56.2
191.fma3d	2	114	42.6	2	114	42.8
200.sixtrack	2	109	23.5	2	104	24.6
301.apsi	2	139	43.3	2	130	46.3

### Hardware

CPU: AMD Opteron 256  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip)  
 Secondary Cache: 1024KB(I+D) (on chip)  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8 x 512 MB PC3200 CL3-3-3 DDR SDRAM  
 Disk Subsystem: SCSI U320  
 Other Hardware: None

### Software

Operating System: SLES 9 with SP3 (AMD64) - kernel 2.6.5-7.244-smp  
 Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.3 (for C and Fortran)  
 AMD Core Mathematical Library (ACML), Version 3.0.0  
 File System: Linux/ReiserFS  
 System State: Multi-User SuSE Run Level 3

## Notes/Tuning Information

Portability flags:  
 178.galgel: -fixedform

Feedback Optimization:  
 +FDO: PASS1=-fb\_create fbdata PASS2=-fb\_opt fbdata

AMD Core Math Library  
 +ACML means -L<acml-install-dir>/pathscale64/lib -lacml,  
 which causes linking with AMD Core Math Library

Baseline Optimization Flags:  
 C programs: -Ofast -WOPT:mem\_opnds=on +FDO  
 Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast\_complex=on +FDO

Peak Tuning Flags:  
 168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3  
 -OPT:unroll\_times\_max=8:unroll\_size=128:IEEE\_NaN\_Inf=off:ro=3



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers  
CELSIUS V830, Opteron (TM) 256, Linux 64-bit

SPECfp\_rate2000 = 54.9  
SPECfp\_rate\_base2000 = 50.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Mar-2006 | Software Avail: Dec-2005

## Notes/Tuning Information (Continued)

```

-IPA:linear=on:plimit=50000:callee_limit=5000
-INLINE:aggressive=on
171.swim: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 -m3dnow
172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE_a=3:unroll_size=200
          -LNO:fusion=2:fission=1:blocking=off:prefetch_ahead=2
          -WOPT:mem_opnds=on:aggstr=0
173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
          -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
          +FDO
177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -WOPT:mem_opnds=on +FDO
178.galgel: -Ofast -OPT:fast_complex=on +ACML +FDO
179.art: -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.quake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec: -Ofast -LNO:fusion=2
            -OPT:fast_complex=on:IEEE_NaN_Inf=off:unroll_size=0 +FDO
188.ammp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
          -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256
          -WOPT:mem_opnds=on +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
          -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:Olimit=6000:early_intrinsics=on
            -fno-math-errno -CG:load_exe=1 +FDO
301.apsi: -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```

BIOS default settings with  
Node memory interleave disabled, SRAT enabled  
taskset has been used to bind processes to CPUs

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>