



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(2.13 GHz, Intel(R) Core(TM) 2 processor E6400)

SPECfp_rate2000 = 40.0

SPECfp_rate_base2000 = 40.0

SPEC license #: 13 Tested by: Intel Corporation Test date: Jul-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	50.5	73.5	2	50.5	73.5
171.swim	2	187	38.4	2	187	38.4
172.mgrid	2	144	29.0	2	144	29.0
173.applu	2	149	32.7	2	149	32.7
177.mesa	2	70.4	46.1	2	70.4	46.1
178.galgel	2	99.2	67.9	2	97.9	68.7
179.art	2	85.8	70.3	2	85.8	70.3
183.quake	2	61.4	49.1	2	62.0	48.7
187.facerec	2	97.0	45.5	2	97.0	45.4
188.amp	2	205	24.9	2	204	25.0
189.lucas	2	122	37.9	2	122	37.9
191.fma3d	2	144	33.9	2	144	33.9
200.sixtrack	2	134	19.1	2	135	18.9
301.apsi	2	181	33.3	2	181	33.3

Hardware

CPU: Intel(R) Core(TM) 2 processor E6400(2.13 GHz, 1066 MHz bus)
CPU MHz: 2133
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32KBI + 32KBD per core
Secondary Cache: 4MB(I+D) shared, per chip
L3 Cache: None
Other Cache: None
Memory: 2 GB (2 1GB Corsair TWIN2X2048-8500C5 DDR2 1066 CL5-5-5 DIMMs)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware: ATI Radeon X1900 XTX PCI express graphics card

Software

Operating System: Windows XP Professional SP2
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_FC_P_9.1.020
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from http://www.microquill.com/
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo +FDO shlW32M.lib
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
188.amp: -fast -Oa +FDO shlW32M.lib
189.lucas: -fast -Qprefetch- +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(2.13 GHz, Intel(R) Core(TM) 2 processor E6400)

SPECfp_rate2000 = 40.0

SPECfp_rate_base2000 = 40.0

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 07/2006

<http://www.intel.com/products/motherboard/dg965wh/index.htm>

The system bus runs at 1066 MHz