



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS M450 (Intel Core 2 Duo processor E6300)

SPECint2000 = **1928**
SPECint_base2000 = **1919**

SPEC license #: 22 Tested by: Fujitsu Siemens Computers Test date: Aug-2006 Hardware Avail: Aug-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	121	1161	121	1161				
175.vpr	1400	101	1381	99.3	1410				
176.gcc	1100	48.9	2248	48.9	2248				
181.mcf	1800	70.7	2547	70.6	2551				
186.crafty	1000	59.1	1693	58.4	1713				
197.parser	1800	120	1506	119	1512				
252.eon	1300	53.3	2441	53.3	2441				
253.perlbmk	1800	78.7	2287	78.7	2288				
254.gap	1100	55.1	1995	54.1	2034				
255.vortex	1900	57.8	3287	57.8	3287				
256.bzip2	1500	109	1378	109	1374				
300.twolf	3000	142	2119	142	2119				

Hardware

CPU: Intel Core 2 Duo processor E6300
 CPU MHz: 1866
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 2048KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x 1GB PC2-5300 5-5-5 2Rank SDRAM
 Disk Subsystem: 1 x 160GB SATA 7200 RPM
 Other Hardware: None

Software

Operating System: Windows XP Professional, Service Pack 2
 Compiler: Intel(R) C++ Compiler for 32-bit app., Version 9.1,
 - Build 20060519Z Package ID: W_CC_P_9.1.025
 Microsoft Visual Studio .NET 2003 (for libraries)
 MicroQuill SmartHeap Library, Version 8 (shlW32M.lib)
 File System: FAT32
 System State: Default

Notes/Tuning Information

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Feedback optimization:

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:

for C programs:
 -fast +FDO shlW32M.lib
 for C++ program 252.eon:
 -fast -Qcxx_features +FDO

Peak Tuning Flags:

164.gzip: -fast +FDO
 175.vpr: -fast +FDO
 176.gcc: basepeak=yes
 181.mcf: -fast +FDO shlW32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS M450 (Intel Core 2 Duo processor E6300)

SPECint2000 = 1928
SPECint_base2000 = 1919

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

186.crafty: -fast +FDO
197.parser: -fast +FDO
252.eon: -fast -Qcxx_features +FDO
253.perlbnk: -fast +FDO shlW32M.lib
254.gap: -fast +FDO
255.vortex -fast +FDO shlW32M.lib
256.bzip2: -fast +FDO
300.twolf: -fast +FDO shlW32M.lib

Extra Libraries:

shlW32M.lib = Microquill SmartHeap Library 8
see www.microquill.com

The system bus runs at 1066 MHz

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>