



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec LX211 (Intel Xeon 5120 processor, 1.86GHz)

SPECint_rate2000 = 77.8

SPECint_rate_base2000 = 77.8

SPEC license #: 9001 | Tested by: Itautec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	4	124	52.2	4	124	52.2
175.vpr	4	116	55.9	4	116	55.9
176.gcc	4	59.1	86.3	4	59.1	86.3
181.mcf	4	125	66.7	4	125	66.7
186.crafy	4	57.9	80.1	4	57.9	80.1
197.parser	4	135	61.9	4	135	61.9
252.eon	4	53.6	113	4	53.6	113
253.perlbnk	4	87.4	95.5	4	87.4	95.5
254.gap	4	70.4	72.5	4	70.4	72.5
255.vortex	4	66.3	133	4	66.3	133
256.bzip2	4	121	57.4	4	121	57.4
300.twolf	4	141	99.0	4	141	99.0

Hardware

CPU: Intel Xeon 5120 processor (1.86 GHz, 4MB L2, 1066 MHz system bus)
CPU MHz: 1860
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4096KB(I+D) on chip, per chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2GB + 2x2GB DDRII-RAM PC2-5300F (CAS 5-5-5)ECC
Disk Subsystem: 1 x 120GB Serial ATA 7200 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio 2005 (for libraries),
MicroQuill SmartHeap for SMP Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

```
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
```

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

```
for C programs: -fast -QxP +FDO shlsMPMt.lib
for C++ programs: -fast -Qcxx_features +FDO
```

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>