



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon processor E5320, 1.86 GHz

SPECfp_rate2000 = 79.0

SPECfp_rate_base2000 = 79.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2006 | Hardware Avail: Nov-2006 | Software Avail: Aug-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	150	99.1	8	150	99.1
171.swim	8	691	41.7	8	691	41.7
172.mgrid	8	430	38.8	8	430	38.8
173.applu	8	460	42.4	8	460	42.4
177.mesa	8	77.2	168	8	77.2	168
178.galgel	8	110	244	8	110	244
179.art	8	113	214	8	113	214
183.quake	8	333	36.2	8	333	36.2
187.facerec	8	175	101	8	175	101
188.amp	8	166	123	8	166	123
189.lucas	8	388	47.8	8	388	47.8
191.fma3d	8	369	52.8	8	369	52.8
200.sixtrack	8	155	65.7	8	155	65.7
301.apsi	8	292	82.5	8	292	82.5

Hardware

CPU: Intel Xeon processor E5320 (1.86 GHz, 2x4MB L2, 1066 MHz system bus)
 CPU MHz: 1866
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x1GB DDR2-RAM PC2-4200F (CAS 4-4-4)
 Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)
 Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10
 Kernel 2.6.16.21-0.8-smp on an x86_64
 Compiler: Intel C++ and Fortran Compiler 9.1 for EM64T
 Build 20060816 (for 64-bit applications)
 File System: ext2
 System State: Multi-user runlevel 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
 PASS1: -prof_gen PASS2: -prof_use

Optimization flags
 ONESTEP=yes set for all benchmarks

Portability flags
 -DSPEC_CPU2000_LP64 applied to all benchmarks
 178.galgel: -FI for fixed-format Fortran

Base tuning flags
 for Fortran and C programs: -fast +FDO

Peak tuning flags
 same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon processor E5320, 1.86 GHz

SPECfp_rate2000 = 79.0

SPECfp_rate_base2000 = 79.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2006 | Hardware Avail: Nov-2006 | Software Avail: Aug-2006

Notes/Tuning Information (Continued)

The system bus runs at 1066 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

BIOS Configuration:

Hardware Prefetch = disable, Adjacent Sector Prefetch = disable

This result was measured on the PRIMERGY RX300 S3. The PRIMERGY TX300 S3 and the PRIMERGY RX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>