SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 840 (Intel Xeon X3220, 2.40 GHz)

SPECint®_rate2006 = 44.2

SPECint_rate_base2006 = 43.0

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Jan-2007
Hardware Availability: Jan-2007
Software Availability: Oct-2006



Hardware

CPU Name:	Intel Xeon X3220
CPU Characteristics:	1066MHz system bus
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	4 GB (4x1 GB 667MHz ECC DDR2 SDRAM)
Disk Subsystem:	1 x 73GB SAS 10000 RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 x64 Enterprise Edition
Compiler:	Intel C++ Compiler 9.1 for IA32 (20061103Z) Microsoft Visual Studio 2005 (8.0.50727.42)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library 8.0

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 840 (Intel Xeon X3220, 2.40 GHz)

SPECint_rate2006 = 44.2

SPECint_rate_base2006 = 43.0

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Jan-2007
Hardware Availability: Jan-2007
Software Availability: Oct-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	579	67.5	599	65.2	**599**	**65.3**	4	546	71.6	544	71.8	**545**	**71.7**
401.bzip2	4	**961**	**40.2**	956	40.4	968	39.9	4	**961**	**40.2**	956	40.4	968	39.9
403.gcc	4	1484	21.7	1497	21.5	**1486**	**21.7**	4	**1488**	**21.6**	1497	21.5	1486	21.7
429.mcf	4	810	45.0	811	45.0	**810**	**45.0**	4	812	44.9	**811**	**45.0**	810	45.0
445.gobmk	4	685	61.2	**686**	**61.2**	688	61.0	4	613	68.5	615	68.2	**613**	**68.4**
456.hmmer	4	930	40.1	**930**	**40.1**	930	40.1	4	930	40.1	**930**	**40.1**	930	40.1
458.sjeng	4	829	58.4	**829**	**58.4**	829	58.4	4	**755**	**64.1**	755	64.1	755	64.1
462.libquantum	4	3849	21.5	3846	21.5	**3848**	**21.5**	4	**3859**	**21.5**	3857	21.5	3877	21.4
464.h264ref	4	890	99.4	891	99.4	**890**	**99.4**	4	869	102	**870**	**102**	870	102
471.omnetpp	4	902	27.7	**902**	**27.7**	902	27.7	4	875	28.6	876	28.5	**876**	**28.5**
473.astar	4	825	34.0	**823**	**34.1**	821	34.2	4	**832**	**33.8**	832	33.7	831	33.8
483.xalancbmk	4	**510**	**54.1**	510	54.1	511	54.1	4	**513**	**53.8**	514	53.7	513	53.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Adjacent Sector Prefetch disabled in BIOS, default enabled
32-bit binaries were built on Windows XP Professional x64 Edition
```

Base Compiler Invocation

C benchmarks:

```
icl -Qc99
```

C++ benchmarks:

```
icl
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlW32M.lib           -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
```
-fast -Qcxx_features /F512000000 shlW32M.lib
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
```
icl -Qc99
```

C++ benchmarks:
```
icl
```

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Peak Optimization Flags

C benchmarks:

400.perlbench: `ONESTEP -Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast /F512000000 shlW32M.lib -link /FORCE:MULTIPLE`

401.bzip2: `basepeak = yes`

403.gcc: `Same as 400.perlbench`

429.mcf: `ONESTEP -fast /F512000000 shlW32M.lib -link /FORCE:MULTIPLE`

445.gobmk: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast /F512000000 shlW32M.lib -link /FORCE:MULTIPLE`

Continued on next page

Peak Optimization Flags (Continued)

456.hmmer: `basepeak = yes`

458.sjeng: `Same as 400.perlbench`

462.libquantum: `Same as 400.perlbench`

464.h264ref: `Same as 400.perlbench`

C++ benchmarks:

471.omnetpp: `ONESTEP -Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast -Qcxx_features /F512000000 shlW32M.lib -link /FORCE:MULTIPLE`

473.astar: `Same as 471.omnetpp`

483.xalancbmk: `ONESTEP -fast -Qcxx_features /F512000000 shlW32M.lib -link /FORCE:MULTIPLE`

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.20090715.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.20090715.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:57:42 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 7 February 2007.