



# SPEC® CINT2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

## Acer Incorporated

**SPECint®\_rate2006 = 45.0**

Acer Altos R720 (Intel Xeon X5355, 2.66GHz)

**SPECint\_rate\_base2006 = 43.5**

CPU2006 license: 97


Test date: Jan-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2006

Tested by: Acer Incorporated

Software Availability: Nov-2006



### Hardware

CPU Name: Intel Xeon X5355  
 CPU Characteristics: 1333MHz system bus  
 CPU MHz: 2666  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)  
 Disk Subsystem: 1 x 73GB 10000RPM SAS HDD  
 Other Hardware: None

### Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790), Service Pack 1  
 Compiler: Intel C++ Compiler for IA32 version 9.1  
 Package ID W\_CC\_C\_9.1.028 Build 20060706Z  
 Microsoft Visual Studio 2003 .Net (libr. & linker)  
 Auto Parallel: No  
 File System: NTFS  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: 32-bit  
 Other Software: MicroQuill Smart Heap Library, Version 7.4



# SPEC CINT2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint\_rate2006 = 45.0

Acer Altos R720 (Intel Xeon X5355, 2.66GHz)

SPECint\_rate\_base2006 = 43.5

CPU2006 license: 97

Test date: Jan-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2006

Tested by: Acer Incorporated

Software Availability: Nov-2006

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	<u>535</u>	<u>73.0</u>	536	73.0	535	73.1	4	492	79.4	490	79.7	<u>492</u>	<u>79.5</u>
401.bzip2	4	970	39.8	<u>968</u>	<u>39.9</u>	967	39.9	4	950	40.6	<u>948</u>	<u>40.7</u>	947	40.8
403.gcc	4	<u>1670</u>	<u>19.3</u>	1657	19.4	1673	19.2	4	1668	19.3	1681	19.2	<u>1670</u>	<u>19.3</u>
429.mcf	4	<u>929</u>	<u>39.3</u>	930	39.2	927	39.4	4	944	38.6	943	38.7	<u>943</u>	<u>38.7</u>
445.gobmk	4	636	65.9	634	66.1	<u>636</u>	<u>66.0</u>	4	<u>564</u>	<u>74.4</u>	563	74.5	564	74.4
456.hammer	4	<u>839</u>	<u>44.5</u>	839	44.5	839	44.5	4	<u>819</u>	<u>45.6</u>	819	45.6	819	45.6
458.sjeng	4	770	62.9	770	62.8	<u>770</u>	<u>62.9</u>	4	707	68.4	707	68.5	<u>707</u>	<u>68.4</u>
462.libquantum	4	4288	19.3	<u>4288</u>	<u>19.3</u>	4289	19.3	4	4276	19.4	<u>4281</u>	<u>19.4</u>	4282	19.4
464.h264ref	4	<u>837</u>	<u>106</u>	837	106	838	106	4	808	110	807	110	<u>807</u>	<u>110</u>
471.omnetpp	4	888	28.2	<u>888</u>	<u>28.2</u>	888	28.1	4	853	29.3	<u>853</u>	<u>29.3</u>	854	29.3
473.astar	4	785	35.8	785	35.8	<u>785</u>	<u>35.8</u>	4	797	35.2	796	35.3	<u>796</u>	<u>35.3</u>
483.xalancbmk	4	500	55.2	499	55.3	<u>500</u>	<u>55.2</u>	4	489	56.4	489	56.5	<u>489</u>	<u>56.5</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

This result was measured on the Acer Altos R520.  
The Altos R720 and Altos R520 are electronically equivalent.

## Compiler Invocation

C benchmarks:  
icl -Qvc7.1 -Qc99  
C++ benchmarks:  
icl -Qvc7.1

## Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32  
464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32  
473.astar: -DSPEC\_CPU\_LITTLE\_ENDIAN



# SPEC CINT2006 Result

Copyright ©2007 Standard Performance Evaluation Corporation

**Acer Incorporated**

**SPECint\_rate2006 = 45.0**

**Acer Altos R720 (Intel Xeon X5355, 2.66GHz)**

**SPECint\_rate\_base2006 = 43.5**

**CPU2006 license:** 97

**Test sponsor:** Acer Incorporated

**Tested by:** Acer Incorporated

**Test date:** Jan-2007

**Hardware Availability:** Nov-2006

**Software Availability:** Nov-2006

## Base Optimization Flags

C benchmarks:

`-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

C++ benchmarks:

`-fast -Qcxx_features /F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE`

## Peak Optimization Flags

C benchmarks:

`-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE`

C++ benchmarks:

`-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features  
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

## Other Flags

C benchmarks:

`403.gcc: -Dalloca=_alloca`

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Acer-CPU2006-ic91-flags-file-20070101.xml.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Acer-CPU2006-ic91-flags-file-20070101.xml.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Sat Dec 15 23:53:33 2007 by SPEC CPU2006 PS/PDF formatter v5614.