SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL360 G5
(1.86 GHz, Intel Xeon processor E5320)

SPECint®_rate2006 = 61.0

SPECint_rate_base2006 = 59.2

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Feb-2007
Hardware Availability: Jan-2007
Software Availability: Nov-2006



Hardware

CPU Name:	Intel Xeon E5320
CPU Characteristics:	1.86 GHz, 2x4 MB L2 shared, 1066 MHz system bus
CPU MHz:	1860
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8x2 GB PC2-5300 CL5)
Disk Subsystem:	2x72 GB 10k SAS
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise x64 Edition SP1
Compiler:	Intel C++ Compiler for 32-bit applications, Version 9.1, Build 20061103Z Package ID: W_CC_C_9.1.033 Microsoft Visual Studio .NET 2003 (v7.1.3088, for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library 8.0

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL360 G5
(1.86 GHz, Intel Xeon processor E5320)

SPECint_rate2006 = 61.0

SPECint_rate_base2006 = 59.2

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Feb-2007
Hardware Availability: Jan-2007
Software Availability: Nov-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	751	104	752	104	**751**	**104**	8	690	113	**689**	**114**	688	114
401.bzip2	8	**1321**	**58.4**	1320	58.5	1321	58.4	8	1300	59.4	**1298**	**59.5**	1297	59.5
403.gcc	8	**2460**	**26.2**	2513	25.6	2365	27.2	8	2537	25.4	**2510**	**25.7**	2461	26.2
429.mcf	8	1471	49.6	1475	49.5	**1473**	**49.5**	8	1471	49.6	1475	49.5	**1473**	**49.5**
445.gobmk	8	888	94.5	**888**	**94.5**	889	94.4	8	792	106	790	106	**791**	**106**
456.hmmer	8	1200	62.2	**1200**	**62.2**	1200	62.2	8	1168	63.9	1168	63.9	**1168**	**63.9**
458.sjeng	8	**1070**	**90.4**	1071	90.4	1070	90.5	8	984	98.3	**984**	**98.3**	984	98.3
462.libquantum	8	**7093**	**23.4**	7094	23.4	7092	23.4	8	7090	23.4	**7094**	**23.4**	7095	23.4
464.h264ref	8	1163	152	**1163**	**152**	1164	152	8	1140	155	**1139**	**155**	1139	155
471.omnetpp	8	1418	35.3	1418	35.3	**1418**	**35.3**	8	1402	35.7	**1402**	**35.7**	1401	35.7
473.astar	8	1169	48.1	**1169**	**48.0**	1172	47.9	8	**1174**	**47.9**	1174	47.8	1172	47.9
483.xalancbmk	8	758	72.8	**759**	**72.7**	760	72.7	8	**742**	**74.4**	742	74.4	742	74.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Power Regulator set to Static High Performance Mode in BIOS.
Adjacent Sector Prefetch disabled in BIOS.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99

C++ benchmarks:
icl -Qvc7.1

Peak Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Peak Optimization Flags

C benchmarks:

400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000
shlw32m.lib -link /FORCE:MULTIPLE

401.bzip2: Same as 400.perlbench

403.gcc: Same as 400.perlbench

429.mcf: basepeak = yes

445.gobmk: Same as 400.perlbench

456.hmmer: Same as 400.perlbench

458.sjeng: Same as 400.perlbench

Continued on next page

Peak Optimization Flags (Continued)

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:37:14 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 March 2007.