SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 1950 (Intel Xeon processor E5335, 2.00 GHz)

SPECint®_rate2006 = Not Run

SPECint_rate_base2006 = 69.0

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Mar-2007
Hardware Availability: Dec-2006
Software Availability: Nov-2006



Hardware

CPU Name:	Intel Xeon E5335
CPU Characteristics:	1333 MHz Bus Speed
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8 x 2 GB 667MHz CL5 DDR2 FB-DIMM SDRAM)
Disk Subsystem:	1 x 73 GB SAS 15k RPM
Other Hardware:	None

Software

Operating System:	Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler:	Intel C++ Compiler 9.1 for IA32 (20061103Z) Microsoft Visual Studio 2005
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	Not Applicable
Other Software:	MicroQuill SmartHeap Library 8.0

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 1950 (Intel Xeon processor E5335, 2.00 GHz)

SPECint_rate2006 = Not Run

SPECint_rate_base2006 = 69.0

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Mar-2007
Hardware Availability: Dec-2006
Software Availability: Nov-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	**710**	**110**	710	110	709	110							
401.bzip2	8	1225	63.0	**1225**	**63.0**	1223	63.1							
403.gcc	8	**1928**	**33.4**	1925	33.5	2017	31.9							
429.mcf	8	**1118**	**65.3**	1120	65.1	1118	65.3							
445.gobmk	8	832	101	**833**	**101**	833	101							
456.hmmer	8	**1153**	**64.7**	1153	64.7	1153	64.7							
458.sjeng	8	**996**	**97.2**	995	97.2	996	97.2							
462.libquantum	8	5725	29.0	5733	28.9	**5731**	**28.9**							
464.h264ref	8	**1081**	**164**	1081	164	1081	164							
471.omnetpp	8	937	53.4	936	53.4	**937**	**53.4**							
473.astar	8	968	58.0	969	57.9	**969**	**58.0**							
483.xalancbmk	8	661	83.5	**662**	**83.4**	662	83.4							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Hardware Prefetcher disabled in BIOS
Adjacent Cache Line Prefetch disabled in BIOS
```

Base Compiler Invocation

C benchmarks:

```
icl -Qc99
```

C++ benchmarks:

```
icl
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlW32M.lib           -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
```
-fast -Qcxx_features /F512000000 shlW32M.lib
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:57:17 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 17 April 2007.