SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

Fujitsu SPARC Enterprise M4000

SPECfp®2006 = 11.5

SPECfp_base2006 = 10.6

CPU2006 license: 19
Test sponsor: Fujitsu Limited
Tested by: Fujitsu Limited

Test date: Mar-2007
Hardware Availability: May-2007
Software Availability: May-2007



Hardware

CPU Name:	SPARC64 VI
CPU Characteristics:	
CPU MHz:	2150
FPU:	Integrated
CPU(s) enabled:	8 cores, 4 chips, 2 cores/chip, 2 threads/core
CPU(s) orderable:	1 or 2 CPUM; each CPUM contains 2 CPU chips
Primary Cache:	128 KB I + 128 KB D on chip per core
Secondary Cache:	5 MB I+D on chip per chip

Continued on next page

Software

Operating System:	Solaris 10 11/06
Compiler:	Sun Studio 12 (Early Access)
Auto Parallel:	No
File System:	ufs
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	None

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited

Fujitsu SPARC Enterprise M4000

SPECfp2006 = 11.5

SPECfp_base2006 = 10.6

CPU2006 license: 19
Test sponsor: Fujitsu Limited
Tested by: Fujitsu Limited

Test date: Mar-2007
Hardware Availability: May-2007
Software Availability: May-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (16 x 1 GB, see notes for details)
Disk Subsystem: 73 GB 10,000 RPM Fujitsu MAY2073RC SAS
Other Hardware: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	**683**	**19.9**	683	19.9	683	19.9	658	20.7	658	20.7	**658**	**20.7**
416.gamess	2009	9.74	2010	9.74	**2010**	**9.74**	2009	9.74	2010	9.74	**2010**	**9.74**
433.milc	1242	7.39	**1242**	**7.39**	1242	7.39	1091	8.42	1090	8.42	**1090**	**8.42**
434.zeusmp	**1324**	**6.87**	1324	6.87	1324	6.87	**1324**	**6.87**	1324	6.87	1324	6.87
435.gromacs	723	9.88	**723**	**9.88**	723	9.88	685	10.4	685	10.4	**685**	**10.4**
436.cactusADM	782	15.3	**782**	**15.3**	782	15.3	782	15.3	**782**	**15.3**	782	15.3
437.leslie3d	**778**	**12.1**	779	12.1	778	12.1	687	13.7	**687**	**13.7**	687	13.7
444.namd	842	9.52	842	9.52	**842**	**9.52**	842	9.52	842	9.52	**842**	**9.52**
447.dealII	955	12.0	**955**	**12.0**	956	12.0	**836**	**13.7**	836	13.7	836	13.7
450.soplex	978	8.53	**979**	**8.52**	979	8.52	978	8.53	**979**	**8.52**	979	8.52
453.povray	**597**	**8.92**	597	8.91	596	8.92	**414**	**12.8**	416	12.8	414	12.8
454.calculix	757	10.9	757	10.9	**757**	**10.9**	719	11.5	**719**	**11.5**	720	11.5
459.GemsFDTD	1123	9.45	**1123**	**9.45**	1123	9.45	1123	9.45	**1123**	**9.45**	1123	9.45
465.tonto	925	10.6	**926**	**10.6**	927	10.6	**820**	**12.0**	820	12.0	820	12.0
470.lbm	**937**	**14.7**	937	14.7	937	14.7	891	15.4	891	15.4	**891**	**15.4**
481.wrf	912	12.3	**911**	**12.3**	911	12.3	904	12.4	904	12.4	**904**	**12.4**
482.sphinx3	**2314**	**8.42**	2308	8.44	2317	8.41	1710	11.4	1703	11.4	**1704**	**11.4**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
 Shell Environment:
      Stack size set to unlimited via "ulimit -s unlimited"
      MPSSHEAP=4MB
      MPSSSTACK=4MB
      MADV=access_lwp
      LD_PRELOAD=mpss.so.1:madv.so.1

The run was bound to processor #27 using the "psrset" command
    psrset -c processor id...: creates a set
    psrset -e set_id command:  runs command on a set


 System Tunables:
```

Continued on next page

Operating System Notes (Continued)

```
(/etc/system parameters)
   maxphys=4194304
      Defines the maximum size of I/O requests, in bytes.
   maxpgio=1024
      Defines the maximum number of page I/O requests that can
      be queued by the paging system.
   tune_t_fsflushr=1
      Controls how many seconds elapse between runs of the
      page flush daemon, fsflush.
   autoup=60
      Causes pages older than the listed number of seconds to
      be written by fsflush.
   bufhwm=3000
      Memory byte limit for caching I/O buffers
   segmap_percent=1
      Set maximum percent memory for file system cache
```

Platform Notes

```
"CPUM" = CPU Module; each module holds two CPU chips.

Memory was 8-way interleaved by filling same capacity
DIMMs in every other slot.

This result was measured on a Fujitsu SPARC Enterprise
M4000 Server.  Note that the Fujitsu SPARC Enterprise
M4000 and Sun SPARC Enterprise M4000 are electrically
equivalent.
```

Base Compiler Invocation

C benchmarks:
```
/opt/SUNWspro12_EA070303/bin/cc
```

C++ benchmarks:
```
/opt/SUNWspro12_EA070303/bin/CC
```

Fortran benchmarks:
```
/opt/SUNWspro12_EA070303/bin/f90
```

Benchmarks using both Fortran and C:
```
/opt/SUNWspro12_EA070303/bin/cc /opt/SUNWspro12_EA070303/bin/f90
```

Base Optimization Flags

C benchmarks:
```
-fast -xipo=2 -xtarget=sparc64vi -xarch=sparcfmaf -fma=fused
-Wc,-fma=fused -xprefetch_level=2
```

C++ benchmarks:
```
-library=stlport4 -fast -xipo=2 -xtarget=sparc64vi -xarch=sparcfmaf
-fma=fused -Qoption cg -fma=fused
```

Fortran benchmarks:
```
-fast -xipo=2 -xtarget=sparc64vi -xarch=sparcfmaf -fma=fused
-Qoption cg -fma=fused -xprefetch_level=2
```

Benchmarks using both Fortran and C:
```
-fast(cc) -fast(f90) -xipo=2 -xtarget=sparc64vi -xarch=sparcfmaf
-fma=fused -Wc,-fma=fused -xprefetch_level=2 -Qoption cg -fma=fused
```

Peak Compiler Invocation

C benchmarks:
```
/opt/SUNWspro12_EA070303/bin/cc
```

C++ benchmarks:
```
/opt/SUNWspro12_EA070303/bin/CC
```

Fortran benchmarks:
```
/opt/SUNWspro12_EA070303/bin/f90
```

Benchmarks using both Fortran and C:
```
/opt/SUNWspro12_EA070303/bin/cc /opt/SUNWspro12_EA070303/bin/f90
```

Peak Optimization Flags

C benchmarks:

433.milc:
```
-fast -xipo=2 -xtarget=sparc64vi -xarch=sparcfmaf
-fma=fused -Wc,-fma=fused -xalias_level=strong
-xprefetch_level=2 -xprefetch_auto_type=indirect_array_access
-fsimple=0
```

470.lbm:
```
-xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xtarget=sparc64vi -xarch=v8plusb -xprefetch_level=2
-fma=fused -Wc,-fma=fused
```

482.sphinx3:
```
-xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xtarget=sparc64vi -xarch=sparcfmaf -fma=fused
```

Continued on next page

Peak Optimization Flags (Continued)

482.sphinx3 (continued):
-Wc,-fma=fused

C++ benchmarks:

444.namd: basepeak = yes

447.dealII: -library=stlport4 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xtarget=sparc64vi -xarch=sparcfmaf -fma=fused
-Qoption cg -fma=fused -xdepend -xalias_level=compatible
-xrestrict

450.soplex: basepeak = yes

453.povray: -library=stlport4 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xtarget=sparc64vi -xarch=sparcfmaf -fma=fused
-Qoption cg -fma=fused -xdepend -xalias_level=compatible

Fortran benchmarks:

410.bwaves: -fast -xipo=2 -xtarget=sparc64vi -xarch=v8plusb
-xchip=ultra3cu -xprefetch_level=2 -xprefetch=latx:3.0
-fma=fused -Qoption cg -fma=fused

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: -fast -xipo=2 -xtarget=sparc64vi -xarch=sparcfmaf
-fma=fused -Qoption cg -fma=fused -xprefetch_level=2
-xprefetch=latx:8.0

459.GemsFDTD: basepeak = yes

465.tonto: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xtarget=sparc64vi -xarch=v8plusa -fma=fused
-Qoption cg -fma=fused -lfast

Benchmarks using both Fortran and C:

435.gromacs: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)
-xipo=2 -xtarget=sparc64vi -xarch=sparcfmaf -fma=fused
-Wc,-fma=fused -Qoption cg -fma=fused

436.cactusADM: basepeak = yes

Continued on next page

Peak Optimization Flags (Continued)

454.calculix: `-fast`(cc) `-fast`(f90) `-xipo=2 -xtarget=sparc64vi -xarch=sparcfmaf -fma=fused -Wc,-fma=fused -Qoption cg -fma=fused`

481.wrf: `-xprofile=collect:./feedback`(pass 1) `-xprofile=use:./feedback`(pass 2) `-fast`(cc) `-fast`(f90) `-xipo=2 -xtarget=sparc64vi -xarch=sparcfmaf -fma=fused -Wc,-fma=fused -Qoption cg -fma=fused -xprefetch_level=2`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12.20090714.02.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12.20090714.02.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:13:04 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 3 May 2007.