SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T880 (2.60 GHz, Intel Xeon 7110M)

SPECint®2006 = 8.19

SPECint_base2006 = 7.75

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Apr-2007
Hardware Availability: Sep-2006
Software Availability: Nov-2006



Hardware

CPU Name:	Intel Xeon 7110M
CPU Characteristics:	2.6 GHz, 800 MHz bus
CPU MHz:	2600
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 2 cores/chip
CPU(s) orderable:	1,2,4 chips
Primary Cache:	12 K micro-ops I + 16 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	4 MB I+D on chip per chip
Other Cache:	None
Memory:	32 GB (16x2 GB) DDR2 400 PC2-3200R-333
Disk Subsystem:	2x36 GB SAS 15000 RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise X64 Edition
Compiler:	Intel C++ Compiler for IA32 version 9.1 Package ID W_CC_C_9.1.033 Build no 20061103Z Microsoft Visual Studio .NET 2003 (lib & linker)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library 8.0 (shlW32M.lib)

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T880 (2.60 GHz, Intel Xeon 7110M)

SPECint2006 = 8.19

SPECint_base2006 = 7.75

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Apr-2007
Hardware Availability: Sep-2006
Software Availability: Nov-2006

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	1059	9.22	1060	9.21	**1060**	**9.22**	980	9.97	**980**	**9.97**	981	9.95
401.bzip2	1404	6.87	**1406**	**6.86**	1406	6.86	1352	7.14	1352	7.14	**1352**	**7.14**
403.gcc	1323	6.09	**1328**	**6.06**	1329	6.06	**1294**	**6.22**	1294	6.22	1295	6.22
429.mcf	**975**	**9.36**	975	9.36	975	9.35	**975**	**9.36**	975	9.36	975	9.35
445.gobmk	1469	7.14	1468	7.15	**1468**	**7.14**	**1390**	**7.55**	1390	7.55	1390	7.55
456.hmmer	**1659**	**5.62**	1659	5.62	1659	5.62	1613	5.78	1613	5.78	**1613**	**5.78**
458.sjeng	2026	5.97	2026	5.97	**2026**	**5.97**	**1785**	**6.78**	1785	6.78	1785	6.78
462.libquantum	1973	10.5	**1973**	**10.5**	1973	10.5	**1996**	**10.4**	1996	10.4	1996	10.4
464.h264ref	1500	14.7	1501	14.7	**1501**	**14.7**	1429	15.5	**1429**	**15.5**	1430	15.5
471.omnetpp	**1050**	**5.95**	1050	5.95	1050	5.95	**952**	**6.57**	952	6.57	952	6.57
473.astar	1186	5.92	**1186**	**5.92**	1186	5.92	1123	6.25	1123	6.25	**1123**	**6.25**
483.xalancbmk	695	9.93	695	9.93	**695**	**9.93**	615	11.2	**615**	**11.2**	615	11.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Other Configuration Notes
/NUMPROC=1 flag was added to boot.ini to invoke
uniprocessor environment
Hyper-Threading technology was disabled in the Bios.

The NovaScale T880 and the NovaScale R480 models are
electronically equivalent.
The results have been measured on a NovaScale R480 model.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:
`-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

C++ benchmarks:
`-fast -Qcxx_features /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
`icl -Qvc7.1 -Qc99`

C++ benchmarks:
`icl -Qvc7.1`

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Peak Optimization Flags

C benchmarks:

400.perlbench: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

401.bzip2: `Same as 400.perlbench`

Continued on next page

Peak Optimization Flags (Continued)

403.gcc: Same as 400.perlbench

429.mcf: basepeak = yes

445.gobmk: Same as 400.perlbench

456.hmmer: Same as 400.perlbench

458.sjeng: Same as 400.perlbench

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/flags.20090714.00.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/flags.20090714.00.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:46:04 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 May 2007.