



SPEC® CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint®_rate2006 = 30.8

PRIMERGY RX100 S4, Intel Xeon processor 3070,
2.67 GHz

SPECint_rate_base2006 = 29.3

CPU2006 license: 22


Test date: May-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: May-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Feb-2007



Hardware

CPU Name: Intel Xeon 3070
 CPU Characteristics: 1067 MHz system bus
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 8 GB (4x2 GB DDR2 PC2-4200E, 2 rank, CAS 4-4-4, with ECC)
 Disk Subsystem: SATA (160 GB, 7200 rpm)
 Other Hardware: None

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86_64
 Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package-ID: l_cc_p_9.1.047
 Auto Parallel: No
 File System: ReiserFS
 System State: Multiuser, Runlevel 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Smart Heap Library, Version 8.1



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX100 S4, Intel Xeon processor 3070,
2.67 GHz

SPECint_rate2006 = 30.8

SPECint_rate_base2006 = 29.3

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: May-2007

Hardware Availability: May-2007

Software Availability: Feb-2007

Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	541	36.1	<u>541</u>	<u>36.1</u>	543	36.0	2	494	39.6	495	39.5	<u>495</u>	<u>39.5</u>
401.bzip2	2	780	24.7	788	24.5	<u>784</u>	<u>24.6</u>	2	743	26.0	<u>750</u>	<u>25.7</u>	754	25.6
403.gcc	2	542	29.7	534	30.1	<u>537</u>	<u>30.0</u>	2	542	29.7	534	30.1	<u>537</u>	<u>30.0</u>
429.mcf	2	571	32.0	<u>571</u>	<u>31.9</u>	572	31.9	2	<u>581</u>	<u>31.4</u>	580	31.5	582	31.3
445.gobmk	2	600	34.9	<u>601</u>	<u>34.9</u>	601	34.9	2	556	37.7	<u>556</u>	<u>37.7</u>	556	37.7
456.hmmer	2	<u>830</u>	<u>22.5</u>	830	22.5	830	22.5	2	693	26.9	<u>693</u>	<u>26.9</u>	694	26.9
458.sjeng	2	<u>731</u>	<u>33.1</u>	737	32.8	731	33.1	2	678	35.7	681	35.6	<u>678</u>	<u>35.7</u>
462.libquantum	2	2224	18.6	<u>2222</u>	<u>18.6</u>	2221	18.7	2	<u>2177</u>	<u>19.0</u>	2158	19.2	2186	19.0
464.h264ref	2	806	54.9	<u>806</u>	<u>54.9</u>	807	54.8	2	798	55.5	799	55.4	<u>799</u>	<u>55.4</u>
471.omnetpp	2	592	21.1	596	21.0	<u>593</u>	<u>21.1</u>	2	540	23.1	541	23.1	<u>541</u>	<u>23.1</u>
473.astar	2	654	21.5	<u>652</u>	<u>21.5</u>	652	21.5	2	645	21.8	646	21.7	<u>646</u>	<u>21.7</u>
483.xalancbmk	2	353	39.1	354	39.0	<u>354</u>	<u>39.0</u>	2	353	39.1	354	39.0	<u>354</u>	<u>39.0</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs

General Notes

The system bus runs at 1067 MHz

All binaries were built with 32-bit Intel compiler except:
401.bzip2, 456.hmmer and 462.libquantum in peak were built with
64-bit Intel compiler by changing the path for include and library files.

BIOS configuration:
Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint_rate2006 = 30.8

PRIMERGY RX100 S4, Intel Xeon processor 3070,
2.67 GHz

SPECint_rate_base2006 = 29.3

CPU2006 license: 22

Test date: May-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: May-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Feb-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_X64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-xP -O3 -ipo -no-prec-div -L/opt/SmartHeap_8_1/lib -lsmartheap

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

456.hmmer: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

462.libquantum: /opt/intel/cce/9.1.047/bin/icc
-I/opt/intel/cce/9.1.047/include
-L/opt/intel/cce/9.1.047/lib

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX100 S4, Intel Xeon processor 3070,
2.67 GHz

SPECint_rate2006 = 30.8

SPECint_rate_base2006 = 29.3

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: May-2007

Hardware Availability: May-2007

Software Availability: Feb-2007

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof_gen(pass 1) -prof_use(pass 2) -fast

401.bzip2: -fast

403.gcc: basepeak = yes

429.mcf: -prof_gen(pass 1) -prof_use(pass 2) -fast
-L/opt/SmartHeap_8_1/lib -lsmartheap

445.gobmk: Same as 429.mcf

456.hmmer: Same as 400.perlbench

458.sjeng: Same as 429.mcf

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 429.mcf

C++ benchmarks:

471.omnetpp: -prof_gen(pass 1) -prof_use(pass 2) -xP -O3 -ipo
-no-prec-div -L/opt/SmartHeap_8_1/lib -lsmartheap

473.astar: -prof_gen(pass 1) -prof_use(pass 2) -fast
-L/opt/SmartHeap_8_1/lib -lsmartheap

483.xalancbmk: basepeak = yes

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 14 19:49:48 2009 by SPEC CPU2006 PS/PDF formatter v6323.