SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor 5130,2.00GHz)

SPECint®2006 = 12.9

SPECint_base2006 = 12.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006



Hardware

CPU Name:	Intel Xeon 5130
CPU Characteristics:	2.00 GHz, 4 MB L2, 1333 MHz system bus
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 2 cores/chip
CPU(s) orderable:	1 to 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	24 GB (12x2 GB) FB-DIMM PC2-5300F ECC CL5
Disk Subsystem:	1x73 GB SAS, 15000 RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition X64 Edition Service Pack1
Compiler:	Intel C++ Compiler for IA32 version 9.1 Package ID W_CC_C_9.1.033 Build no 20061103Z Microsoft Visual Studio .NET 2003 (lib & linker)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library 8.0 (shlW32M.lib)

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440
(Intel Xeon processor 5130,2.00GHz)

SPECint2006 = 12.9

SPECint_base2006 = 12.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	**672**	**14.5**	672	14.5	673	14.5	**617**	**15.8**	617	15.8	618	15.8
401.bzip2	920	10.5	**922**	**10.5**	922	10.5	897	10.8	897	10.8	**897**	**10.8**
403.gcc	879	9.16	**882**	**9.13**	883	9.12	856	9.41	**856**	**9.41**	857	9.40
429.mcf	578	15.8	**577**	**15.8**	577	15.8	**618**	**14.8**	618	14.7	618	14.8
445.gobmk	793	13.2	792	13.2	**793**	**13.2**	**701**	**15.0**	701	15.0	701	15.0
456.hmmer	1117	8.35	**1116**	**8.36**	1116	8.36	1086	8.59	1086	8.59	**1086**	**8.59**
458.sjeng	982	12.3	**982**	**12.3**	981	12.3	902	13.4	902	13.4	**902**	**13.4**
462.libquantum	1529	13.6	**1528**	**13.6**	1526	13.6	1512	13.7	**1511**	**13.7**	1511	13.7
464.h264ref	1062	20.8	1062	20.8	**1062**	**20.8**	**1036**	**21.4**	1036	21.4	1036	21.4
471.omnetpp	**597**	**10.5**	597	10.5	597	10.5	541	11.5	**541**	**11.5**	541	11.6
473.astar	**719**	**9.77**	719	9.76	719	9.77	**717**	**9.79**	717	9.79	717	9.78
483.xalancbmk	**443**	**15.6**	443	15.6	442	15.6	438	15.8	437	15.8	**437**	**15.8**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
/NUMPROC=1 flags was added to boot.ini invoke
uniprocessor environment
```

General Notes

```
The NovaScale R440 and the NovaScale R460 models are
electronically equivalent.
The results have been measured on a NovaScale R460 model.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:
```
-fast /F512000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

C++ benchmarks:
```
-fast -Qcxx_features /F512000000 shlw32m.lib
            -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:
```
icl -Qvc7.1
```

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Peak Optimization Flags

C benchmarks:
```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000 shlw32m.lib
            -link /FORCE:MULTIPLE
```

C++ benchmarks:
```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

Peak Other Flags

C benchmarks:

Continued on next page

Peak Other Flags (Continued)

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/flags.20090714.00.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/flags.20090714.00.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:07:31 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 June 2007.