SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T860
(Intel Xeon processor E5310,1.60GHz)

SPECint®2006 = 10.4

SPECint_base2006 = 9.99

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006



Hardware

CPU Name:	Intel Xeon E5310
CPU Characteristics:	1.60 GHz, 8 MB L2, 1066 MHz system bus
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 4 cores/chip
CPU(s) orderable:	1 to 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	24 GB (12x2 GB) FB-DIMM PC2-5300F ECC CL5
Disk Subsystem:	1x147 GB SAS, 15000 RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition X64 Edition Service Pack1
Compiler:	Intel C++ Compiler for IA32 version 9.1 Package ID W_CC_C_9.1.033 Build no 20061103Z Microsoft Visual Studio .NET 2003 (lib & linker)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library 8.0 (shlW32M.lib)

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T860
(Intel Xeon processor E5310,1.60GHz)

SPECint2006 = 10.4

SPECint_base2006 = 9.99

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	841	11.6	841	11.6	**841**	**11.6**	771	12.7	771	12.7	**771**	**12.7**
401.bzip2	1149	8.40	1151	8.38	**1151**	**8.38**	1120	8.61	**1120**	**8.61**	1121	8.61
403.gcc	1094	7.36	1097	7.34	**1097**	**7.34**	1063	7.57	**1064**	**7.56**	1064	7.56
429.mcf	706	12.9	**705**	**12.9**	704	12.9	**755**	**12.1**	755	12.1	755	12.1
445.gobmk	990	10.6	990	10.6	**990**	**10.6**	876	12.0	876	12.0	**876**	**12.0**
456.hmmer	1395	6.69	1395	6.69	**1395**	**6.69**	**1363**	**6.85**	1363	6.85	1363	6.85
458.sjeng	1222	9.90	1223	9.90	**1223**	**9.90**	**1124**	**10.8**	1125	10.8	1124	10.8
462.libquantum	1899	10.9	1900	10.9	**1899**	**10.9**	**1876**	**11.0**	1876	11.0	1877	11.0
464.h264ref	**1328**	**16.7**	1328	16.7	1328	16.7	**1296**	**17.1**	1296	17.1	1296	17.1
471.omnetpp	729	8.57	729	8.58	**729**	**8.57**	663	9.43	**663**	**9.43**	662	9.43
473.astar	895	7.84	**896**	**7.84**	896	7.84	**895**	**7.84**	895	7.84	895	7.85
483.xalancbmk	**551**	**12.5**	551	12.5	551	12.5	**543**	**12.7**	543	12.7	543	12.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
/NUMPROC=1 flags was added to boot.ini to invoke
the uniprocessor environment
```

General Notes

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:
```
-fast /F512000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

C++ benchmarks:
```
-fast -Qcxx_features /F512000000 shlw32m.lib
            -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:
```
icl -Qvc7.1
```

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Peak Optimization Flags

C benchmarks:
```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000 shlw32m.lib
            -link /FORCE:MULTIPLE
```

C++ benchmarks:
```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

Peak Other Flags

C benchmarks:

Continued on next page

Peak Other Flags (Continued)

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/flags.20090714.00.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/flags.20090714.00.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:21:59 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 26 June 2007.