SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon Prosessor 5110)

SPECint®_rate2006 = 40.2

SPECint_rate_base2006 = 37.1

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Jun-2007
Hardware Availability: May-2007
Software Availability: Jun-2007



Hardware

CPU Name:	Intel Xeon 5110
CPU Characteristics:	1.60 GHz, 4MB L2, 1066MHz bus
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	8 GB (8x1 GB DDR2 5300F, 2 rank, CL5-5-5, ECC)
Disk Subsystem:	1x73.2 GB SAS, 15000RPM
Other Hardware:	None

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp for x86_64
Compiler:	Intel C++ Compiler for IA32/EM64T application, Version 10.0 - Build 20070426 Package ID: l_cc_p_10.0.023
Auto Parallel:	No
File System:	ext2
System State:	Multiuser, Runlevel 3
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	MicroQuill SmartHeap library 8.1 binutils-2.17.tar.gz, Version 2.17

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon Prosessor 5110)

SPECint_rate2006 = 40.2

SPECint_rate_base2006 = 37.1

CPU2006 license: 9006
Test sponsor: NEC Corporation
Tested by: NEC Corporation

Test date: Jun-2007
Hardware Availability: May-2007
Software Availability: Jun-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	916	42.6	921	42.4	**918**	**42.6**	4	**782**	**50.0**	778	50.2	786	49.7
401.bzip2	4	1423	27.1	**1420**	**27.2**	1415	27.3	4	1350	28.6	**1347**	**28.6**	1344	28.7
403.gcc	4	892	36.1	888	36.3	**889**	**36.2**	4	892	36.1	888	36.3	**889**	**36.2**
429.mcf	4	990	36.9	989	36.9	**990**	**36.9**	4	**960**	**38.0**	960	38.0	960	38.0
445.gobmk	4	1006	41.7	1012	41.5	**1012**	**41.5**	4	925	45.4	**928**	**45.2**	930	45.1
456.hmmer	4	1120	33.3	**1118**	**33.4**	1117	33.4	4	884	42.2	886	42.1	**885**	**42.2**
458.sjeng	4	1279	37.8	1275	37.9	**1278**	**37.9**	4	1136	42.6	**1142**	**42.4**	1143	42.3
462.libquantum	4	**2295**	**36.1**	2292	36.2	2297	36.1	4	2086	39.7	**2082**	**39.8**	2078	39.9
464.h264ref	4	1365	64.9	1366	64.8	**1365**	**64.9**	4	1292	68.5	1297	68.3	**1296**	**68.3**
471.omnetpp	4	**894**	**28.0**	893	28.0	898	27.8	4	841	29.7	840	29.7	**841**	**29.7**
473.astar	4	**1034**	**27.2**	1034	27.2	1033	27.2	4	957	29.3	**959**	**29.3**	960	29.2
483.xalancbmk	4	586	47.1	**587**	**47.0**	588	47.0	4	586	47.1	**587**	**47.0**	588	47.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
```

General Notes

```
All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer,
for peak, are compiled in 64-bit mode

 The Express5800/120Rg-1(Intel Xeon Prosessor 5110) and
 the Express5800/120Ri-2(Intel Xeon Prosessor 5110) models are electronically equivalent.
 The results have been measured on a Express5800/120Ri-2(Intel Xeon Prosessor 5110) model.
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/opt/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.0.023/bin/icc

456.hmmer: /opt/intel/cce/10.0.023/bin/icc

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -ansi-alias -prefetch`

401.bzip2: `-L/opt/intel/cce/10.0.023/lib -I/opt/intel/cce/10.0.023/include -prof-gen`(pass 1) `-prof-use`(pass 2) `-fast`

403.gcc: `basepeak = yes`

429.mcf: `-fast -prefetch`

445.gobmk: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xT -O2 -ipo -no-prec_div -ansi-alias`

456.hmmer: `-L/opt/intel/cce/10.0.023/lib -I/opt/intel/cce/10.0.023/include -prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -ansi-alias`

458.sjeng: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4`

462.libquantum: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4 -Ob0 -prefetch -opt-streaming-stores always`

464.h264ref: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -ansi-alias`

C++ benchmarks:

471.omnetpp: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xT -O3 -ipo -no-prec_div -ansi-alias -Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmartheap`

473.astar: `Same as 471.omnetpp`

483.xalancbmk: `basepeak = yes`

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/NEC-ic10-linux-flags.20090714.01.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/NEC-ic10-linux-flags.20090714.01.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:21:18 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 24 July 2007.