# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

## Acer Altos R520 (Intel Xeon X5355)

SPECint®_rate2006 = 98.3

SPECint_rate_base2006 = 91.1

**CPU2006 license:** 97
**Test sponsor:** Acer Incorporated
**Tested by:** Acer Incorporated

**Test date:** Jun-2007
**Hardware Availability:** Nov-2006
**Software Availability:** Jun-2007




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon X5355 |
| CPU Characteristics: | 1333MHz system bus |
| CPU MHz: | 2660 |
| FPU: | Integrated |
| CPU(s) enabled: | 8 cores, 2 chips, 4 cores/chip |
| CPU(s) orderable: | 1, 2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 8 MB I+D on chip per chip, 4 MB shared / 2 cores |
| L3 Cache: | None |
| Other Cache: | None |
| Memory: | 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5) |
| Disk Subsystem: | 1 x 73GB 10000RPM SAS HDD |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | SuSE Linux Enterprise Server 10 EM64T (kernel 2.6.16.21-0.8-smp) |
| Compiler: | Intel C++ Compiler for Linux32 and Linux64 version 10.0<br>Build 20070426 Package ID: l_cc_p_10.0.023 |
| Auto Parallel: | No |
| File System: | ReiserFS |
| System State: | Default |
| Base Pointers: | 32-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | MicroQuill SmartHeap Library 8.1 |

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

## Acer Altos R520 (Intel Xeon X5355)

SPECint_rate2006 = 98.3

SPECint_rate_base2006 = 91.1

**CPU2006 license:** 97
**Test sponsor:** Acer Incorporated
**Tested by:** Acer Incorporated

**Test date:** Jun-2007
**Hardware Availability:** Nov-2006
**Software Availability:** Jun-2007

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 8 | 585 | 134 | **586** | **133** | 586 | 133 | 8 | 501 | 156 | 505 | 155 | **504** | **155** |
| 401.bzip2 | 8 | **1086** | **71.1** | 1085 | 71.1 | 1089 | 70.9 | 8 | 1033 | 74.7 | 1039 | 74.3 | **1033** | **74.7** |
| 403.gcc | 8 | 789 | 81.6 | 784 | 82.1 | **786** | **82.0** | 8 | 789 | 81.6 | 784 | 82.1 | **786** | **82.0** |
| 429.mcf | 8 | **1173** | **62.2** | 1173 | 62.2 | 1171 | 62.3 | 8 | 1167 | 62.5 | 1166 | 62.6 | **1166** | **62.5** |
| 445.gobmk | 8 | 652 | 129 | 653 | 128 | **653** | **129** | 8 | **601** | **140** | 600 | 140 | 603 | 139 |
| 456.hmmer | 8 | **718** | **104** | 716 | 104 | 718 | 104 | 8 | 582 | 128 | **584** | **128** | 586 | 127 |
| 458.sjeng | 8 | 801 | 121 | **799** | **121** | 797 | 122 | 8 | 712 | 136 | 715 | 135 | **714** | **136** |
| 462.libquantum | 8 | 3484 | 47.6 | **3483** | **47.6** | 3483 | 47.6 | 8 | 2968 | 55.9 | **2968** | **55.9** | 2965 | 55.9 |
| 464.h264ref | 8 | **846** | **209** | 845 | 210 | 846 | 209 | 8 | 800 | 221 | 803 | 221 | **801** | **221** |
| 471.omnetpp | 8 | 849 | 58.9 | 845 | 59.2 | **847** | **59.1** | 8 | 818 | 61.1 | 819 | 61.0 | **818** | **61.1** |
| 473.astar | 8 | 846 | 66.4 | **832** | **67.5** | 832 | 67.5 | 8 | 785 | 71.6 | **786** | **71.5** | 787 | 71.4 |
| 483.xalancbmk | 8 | 523 | 105 | **523** | **106** | 522 | 106 | 8 | 523 | 105 | **523** | **106** | 522 | 106 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

```
This result was measured on the Acer Altos R520
The Altos R720 and Altos R520 are electronically equivalent.

BIOS settings
Hardware Prefetch is set to disabled
Adjacent Cache Line Prefetch is set to disabled

taskset was used to bind copies to cores
```

## Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

## Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

## Base Optimization Flags

C benchmarks:
`-fast`

C++ benchmarks:
`-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs`
`-L/spec/cpu2006.1.0/lib -lsmartheap`

## Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

## Peak Compiler Invocation

C benchmarks (except as noted below):
`icc`

401.bzip2: `/opt/intel/cce/10.0.023/bin/icc`
`-L/opt/intel/cce/10.0.023/lib`
`-I/opt/intel/cce/10.0.023/include`

456.hmmer: `/opt/intel/cce/10.0.023/bin/icc`
`-L/opt/intel/cce/10.0.023/lib`
`-I/opt/intel/cce/10.0.023/include`

C++ benchmarks:
`icpc`

## Peak Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
401.bzip2: `-DSPEC_CPU_LP64`
456.hmmer: `-DSPEC_CPU_LP64`
462.libquantum: `-DSPEC_CPU_LINUX`
483.xalancbmk: `-DSPEC_CPU_LINUX`

## Peak Optimization Flags

C benchmarks:

Continued on next page

# Peak Optimization Flags (Continued)

400.perlbench: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -ansi-alias -prefetch`

401.bzip2: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast`

403.gcc: `basepeak = yes`

429.mcf: `-fast -prefetch`

445.gobmk: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xT -O2 -ipo -no-prec_div -ansi-alias`

456.hmmer: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -ansi-alias`

458.sjeng: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4`

462.libquantum: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4 -Ob0 -prefetch -opt-streaming-stores always`

464.h264ref: `Same as 456.hmmer`

C++ benchmarks:

471.omnetpp: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xT -O3 -ipo -no-prec_div -ansi-alias -Wl,-z,muldefs -L/spec/cpu2006.1.0/lib -lsmartheap`

473.astar: `Same as 471.omnetpp`

483.xalancbmk: `basepeak = yes`

# Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.41.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.41.xml`

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

## Acer Altos R520 (Intel Xeon X5355)

SPECint_rate2006 = 98.3

SPECint_rate_base2006 = 91.1

**CPU2006 license:** 97
**Test sponsor:** Acer Incorporated
**Tested by:** Acer Incorporated

**Test date:** Jun-2007
**Hardware Availability:** Nov-2006
**Software Availability:** Jun-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:28:03 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 September 2007.