SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

Dell Precision 690 (Intel Xeon X5365, 3.00 GHz)

SPECint®2006 = 20.0

SPECint_base2006 = 18.1

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Jul-2007
Hardware Availability: Aug-2007
Software Availability: Jun-2007



Hardware

CPU Name:	Intel Xeon X5365
CPU Characteristics:	1333 MHz Bus Speed
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8x2 GB 667 MHz ECC CL5 FB-DIMM)
Disk Subsystem:	1 x 73GB SAS 10K RPM
Other Hardware:	None

Software

Operating System:	Windows XP Professional x64 Edition SP2
Compiler:	Intel C++ Compiler for IA-32, Version 10.0 Build 20070426 Package ID: W_CC_P_10.0.025 Microsoft Visual Studio 2005 SP1
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library 8.0

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

Dell Precision 690 (Intel Xeon X5365, 3.00 GHz)

SPECint2006 = 20.0

SPECint_base2006 = 18.1

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Jul-2007
Hardware Availability: Aug-2007
Software Availability: Jun-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	460	21.3	**460**	**21.2**	460	21.2	**404**	**24.2**	404	24.2	404	24.2
401.bzip2	**637**	**15.2**	637	15.2	637	15.1	**618**	**15.6**	618	15.6	618	15.6
403.gcc	623	12.9	622	12.9	**623**	**12.9**	**569**	**14.1**	570	14.1	568	14.2
429.mcf	451	20.2	451	20.2	**451**	**20.2**	451	20.2	451	20.2	**451**	**20.2**
445.gobmk	537	19.5	**537**	**19.5**	537	19.5	485	21.6	485	21.6	**485**	**21.6**
456.hmmer	591	15.8	**591**	**15.8**	591	15.8	585	16.0	585	16.0	**585**	**16.0**
458.sjeng	694	17.4	694	17.4	**694**	**17.4**	**609**	**19.9**	609	19.9	609	19.9
462.libquantum	885	23.4	885	23.4	**885**	**23.4**	**605**	**34.3**	605	34.3	605	34.3
464.h264ref	723	30.6	**723**	**30.6**	723	30.6	684	32.4	**684**	**32.4**	684	32.4
471.omnetpp	479	13.0	**479**	**13.0**	479	13.0	427	14.6	427	14.6	**427**	**14.6**
473.astar	489	14.4	**489**	**14.4**	489	14.4	453	15.5	453	15.5	**453**	**15.5**
483.xalancbmk	**335**	**20.6**	335	20.6	335	20.6	322	21.4	**322**	**21.4**	322	21.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Binaries were built on Windows Vista Ultimate (64-bit)

BIOS Settings
  Snoop Filter                 : OFF
  Adjacent Cache Line Prefetch : OFF
  Hardware Prefetcher          : ON

  Snoop Filter
    Preserves cache coherency while minimizing snoops
    to remote nodes.

  Adjacent Cache Line Prefetch
    Prefetch data in order to shorten execution cycles
    and maximize data processing efficiency.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qstd=c99
```

C++ benchmarks:

```
icl
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:
`-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

C++ benchmarks:
`-fast -Qcxx_features /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
`icl -Qstd=c99`

C++ benchmarks:
`icl`

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Peak Optimization Flags

C benchmarks:

400.perlbench: `ONESTEP -Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast -Qansi-alias -Qprefetch /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

Continued on next page

Peak Optimization Flags (Continued)

401.bzip2: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

403.gcc: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
/F512000000 -link /FORCE:MULTIPLE

429.mcf: basepeak = yes

445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2 -Qipo
-Qprec-div- -Qansi-alias /F512000000
-link /FORCE:MULTIPLE

456.hmmer: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qunroll2 -Qansi-alias /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

458.sjeng: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qunroll4 /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

462.libquantum: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qunroll4 -Ob0 -Qprefetch -Qopt-streaming-stores:always
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

464.h264ref: Same as 456.hmmer

C++ benchmarks:
ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
-Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/dell.ic10.windows.flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/dell.ic10.windows.flags.xml

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

Dell Precision 690 (Intel Xeon X5365, 3.00 GHz)

SPECint2006 = 20.0

SPECint_base2006 = 18.1

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Jul-2007
Hardware Availability: Aug-2007
Software Availability: Jun-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:16:49 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 4 September 2007.