SPEC® CINT2006 Result

IBM Corporation

IBM System x3455 (AMD Opteron 2347)

SPECint®_rate2006 = NC

SPECint_rate_base2006 = NC

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: Advanced Micro Devices

Test date: Aug-2007
Hardware Availability: Nov-2007
Software Availability: Oct-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Copies	
400.perlbench	
401.bzip2	
403.gcc	
429.mcf	
445.gobmk	
456.hmmer	
458.sjeng	
462.libquantum	
464.h264ref	
471.omnetpp	
473.astar	
483.xalancbmk	

Hardware

CPU Name:	AMD Opteron 2347
CPU Characteristics:	
CPU MHz:	1900
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1, 2 chips
Primary Cache:	64 KB I + 64 KB D on chip per core

Continued on next page

Software

Operating System:	SuSE Linux Enterprise Server 10 SP1 64-bit kernel
Compiler:	The Portland Group (PGI) PGI pgcc 7.1-0 C Compiler PGI pgCC 7.1-0 C++ Compiler PathScale Compiler Suite, Release 3.0
Auto Parallel:	No
File System:	ReiserFS

Continued on next page

SPEC CINT2006 Result

IBM Corporation

IBM System x3455 (AMD Opteron 2347)

SPECint_rate2006 = NC

SPECint_rate_base2006 = NC

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: Advanced Micro Devices

Test date: Aug-2007
Hardware Availability: Nov-2007
Software Availability: Oct-2007

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Hardware (Continued)

Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	2 MB I+D on chip per chip
Other Cache:	None
Memory:	16 GB (8 x 2GB, DDR2-667 CL5 ECC Reg Dual Rank)
Disk Subsystem:	1 x 160 GB Serial ATA, 7200 RPM
Other Hardware:	None

Software (Continued)

System State:	Multi-user, run level 3
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap 8.0 32-bit Library for Linux

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
401.bzip2	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
403.gcc	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
429.mcf	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
445.gobmk	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
456.hmmer	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
458.sjeng	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
462.libquantum	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
464.h264ref	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
471.omnetpp	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
473.astar	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC
483.xalancbmk	8	NC	NC	NC	NC	NC	NC	8	NC	NC	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set environment stack size
'ulimit -l 2457600' was used to set environment locked pages in memory quantity
'numactl' was used to bind copies to the cores
Set vm/nr_hugepages=1200 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages
Environment variable PGI_HUGE_PAGES set to 150
```

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Base Compiler Invocation

C benchmarks:
pgcc

C++ benchmarks:
pgcpp

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -Mipa=fast -Mipa=inline -Mipa=noarg -Mfprelaxed
-Msmartalloc=huge:840 -tp barcelona-64 -Bstatic_pgi

C++ benchmarks:
-fastsse -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartalloc=huge:448
--zc_eh -tp barcelona -Bstatic_pgi

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Base Other Flags

C benchmarks:
`-w`

C++ benchmarks:
`-w`

Peak Compiler Invocation

C benchmarks (except as noted below):
`pgcc`

400.perlbench: `pathcc`

403.gcc: `pathcc`

445.gobmk: `pathcc`

464.h264ref: `pathcc`

C++ benchmarks (except as noted below):
`pgCC`

483.xalancbmk: `pathCC`

Peak Portability Flags

400.perlbench: `-DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64`
401.bzip2: `-DSPEC_CPU_LP64`
445.gobmk: `-DSPEC_CPU_LP64`
456.hmmer: `-DSPEC_CPU_LP64`
458.sjeng: `-DSPEC_CPU_LP64`
462.libquantum: `-DSPEC_CPU_LP64 -DSPEC_CPU_LINUX`

Continued on next page

Peak Portability Flags (Continued)

464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
-LNO:opt=0

401.bzip2: -Mpfi(pass 1) -Mpfo(pass 2) -fast -O4
-Msmartalloc=huge:448 -tp barcelona-64 -Bstatic_pgi

403.gcc: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -m32 -O3
-OPT:Ofast

429.mcf: -fastsse -Mipa=fast -Mipa=inline:1 -Msmartalloc=huge:420
-tp barcelona -Bstatic_pgi

445.gobmk: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-OPT:alias=disjoint -LNO:simd=0 -LNO:minvariant=off
-WOPT:retype_expr=on

-fast -Msmartalloc=huge:448 -Mfprelaxed -Msafeptr
-Mipa=const -Mipa=ptr -Mipa=arg -tp barcelona-64
-Bstatic_pgi

458.sjeng: -Mpfi(pass 1) -Mipa=fast(pass 2) -Mipa=inline:1(pass 2)
-Mipa=noarg(pass 2) -Mpfo(pass 2) -fast
-Msmartalloc=huge:448 -Mfprelaxed -tp barcelona-64
-Bstatic_pgi

462.libquantum: -fast -Mfprelaxed -Msmartalloc=huge:448 -Munroll=m:4
-Mipa=fast -Mipa=inline -Mipa=noarg -Bstatic_pgi

Continued on next page

SPEC has determined that this result was not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result would not meet the 3 month availability requirement in the SPEC CPU2006 run rules due to a change in the availability date of the system.

Peak Optimization Flags (Continued)

464.h264ref: `-fb_create fbdata`(pass 1) `-fb_opt fbdata`(pass 2) `-O3 -IPA:plimit=20000 -OPT:alias=disjoint -LNO:prefetch=0`

C++ benchmarks:

471.omnetpp: `basepeak = yes`

473.astar: `basepeak = yes`

483.xalancbmk: `-Ofast -m32 -CG:unroll_times_max=8 -L/cpu2006/work/cpu2006/SmartHeap -lsmartheap`

Peak Other Flags

`Same as Base Other Flags`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/amd814GH-flags.20090714.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/amd814GH-flags.20090714.xml`

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 14 19:18:57 2009 by SPEC CPU2006 PS/PDF formatter v6323.