SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (Intel Xeon E5310)

SPECint®_rate2006 = 36.5

SPECint_rate_base2006 = 33.6

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Aug-2007
Hardware Availability: Nov-2006
Software Availability: Jun-2007



Hardware

CPU Name:	Intel Xeon E5310
CPU Characteristics:	1066MHz system bus
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1, 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
Disk Subsystem:	1 x 73GB 10000RPM SAS HDD
Other Hardware:	None

Software

Operating System:	SuSE Linux Enterprise Server 10 EM64T kernel
Compiler:	Intel C++ Compiler for Linux32 and Linux64 version 10.0 Build 20070426 Package ID: l_cc_p_10.0.023
Auto Parallel:	No
File System:	ReiserFS
System State:	Multi-user, level 3
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	MicroQuill SmartHeap Library 8.1

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (Intel Xeon E5310)

SPECint_rate2006 = 36.5

SPECint_rate_base2006 = 33.6

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Aug-2007
Hardware Availability: Nov-2006
Software Availability: Jun-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	929	42.1	927	42.2	**928**	**42.1**	4	782	50.0	**780**	**50.1**	779	50.1
401.bzip2	4	1513	25.5	**1522**	**25.4**	1530	25.2	4	1453	26.6	**1442**	**26.8**	1439	26.8
403.gcc	4	965	33.4	**968**	**33.2**	972	33.1	4	965	33.4	**968**	**33.2**	972	33.1
429.mcf	4	1182	30.9	1185	30.8	**1184**	**30.8**	4	1162	31.4	**1162**	**31.4**	1161	31.4
445.gobmk	4	1032	40.7	1030	40.7	**1032**	**40.7**	4	947	44.3	**945**	**44.4**	944	44.5
456.hmmer	4	1160	32.2	**1160**	**32.2**	1161	32.1	4	**936**	**39.9**	938	39.8	934	39.9
458.sjeng	4	**1279**	**37.8**	1282	37.8	1273	38.0	4	**1136**	**42.6**	1134	42.7	1141	42.4
462.libquantum	4	**3632**	**22.8**	3628	22.8	3633	22.8	4	**3182**	**26.0**	3182	26.0	3181	26.1
464.h264ref	4	1377	64.3	1379	64.2	**1377**	**64.3**	4	1306	67.8	**1304**	**67.9**	1304	67.9
471.omnetpp	4	961	26.0	960	26.0	**961**	**26.0**	4	904	27.7	**904**	**27.7**	902	27.7
473.astar	4	**1126**	**24.9**	1127	24.9	1123	25.0	4	1046	26.9	**1055**	**26.6**	1055	26.6
483.xalancbmk	4	**676**	**40.8**	676	40.8	676	40.8	4	**676**	**40.8**	676	40.8	676	40.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
This result was measured on the Acer Altos R520
The Altos R720 and Altos R520 are electronically equivalent.

BIOS Settings
  Snoop Filter set to OFF
   Snoop Filter preserves cache coherency while
   minimizing snoops to remote nodes.

  Adjacent Cache Line Prefetch set to OFF
   Prefetch data in order to shorten execution cycles
   and maximize data processing efficiency.

  Optimization for high-frequency FSB applications set to ON

taskset was used to bind copies to cores
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/spec/cpu2006.1.0/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.0.023/bin/icc
-L/opt/intel/cce/10.0.023/lib
-I/opt/intel/cce/10.0.023/include

456.hmmer: /opt/intel/cce/10.0.023/bin/icc
-L/opt/intel/cce/10.0.023/lib
-I/opt/intel/cce/10.0.023/include

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page

Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias -prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast

403.gcc: basepeak = yes

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo -no-prec_div -ansi-alias

456.hmmer: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -ansi-alias

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -Ob0 -prefetch -opt-streaming-stores always

464.h264ref: Same as 456.hmmer

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo -no-prec_div -ansi-alias -Wl,-z,muldefs -L/spec/cpu2006.1.0/lib -lsmartheap

473.astar: Same as 471.omnetpp

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.16.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.16.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:55:35 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 October 2007.